



P1 **P2**



1PC/PE BAG

PIN ASSIGNMENT:



Material:

- Cable: USB2.0 Black UL2725 #28/1P+28#/2C+AEB
  - OD 3.8MM
  - White print
  - USB Cable E189529 AWM 2725 VW-1 30V 80°C 28AWG/1PR and 28AWG/2C
- P1 Connector: Mini USB 4P B/M plug
  - Solder type
  - Plastic Black
- P2 Connector: USB A Male
  - Shell: Nickel
  - Pin: G/F 4PCS type
  - Insulator color: White
- Outer Jacket: Black PVC-40P

Electrical:

- 100% short, open, miswire test
- Conduct resistance: 2Ω (Max.)
- Insulation resistance: 10MΩ (Min.)
- Dielectric test: 300V DC

Unit: MM

RoHS Complaint

Scale	1:1
TOLERANCE	
X.X	±0.40
X.XX	±0.25
X.XXX	±0.15
Angle	±3°

Modification	Date	Name

		Name
Drawn	08.29.11	Chappell
Approved		

ASSMANN WSW components

Item No. **AK670M/2-2-R**

Title USB 2.0 Cable A Male to Mini B Male - 4 Pin, Black, 2 Meters

Drawing No. **rev00**

Replace | Sheet