AME

AME385-1.2 Shunt Bandgap Voltage Reference

■ General Description

The AME385-1.2 is a micropower 2-terminal band-gap voltage regulator diode. It operates over a 30μA to 20mA current range. Each circuit is trimmed at wafer sort to provide a ±0.5% initial tolerance. The design of the AME385-1.2 allows for a large range of load capacitances and operating currents. The low start-up current makes these parts ideal for battery applications.

AME offers this part in a TO-92 and SOP-8 packages as well as the space saving SOT-23.


■ Features

- Small Packages: SOT-23, TO-92, SOP-8
- Tolerates Capacitive Loads
- Fixed Reverse Breakdown Voltage of 1.235V
- Tight Voltage Tolerance ------- ±0.5%
- Wide Operating Current ------- 30μA to 20mA
- Wide Temperature Range ----- -40°C to +85°C
- Low Temperature Coefficient --100ppm/°C (max)
- Excellent Transient Response
- All AME's Lead Free Products Meet RoHS Standards.


■ Applications

- Portable Electronics
- Power Supplies
- Computer Peripherals
- Data Acquisition Systems
- Battery chargers
- Consumer Electronics

■ Functional Block Diagram




■ Typical Application



$$RS = \frac{VS - VR}{I}$$

■ Pin Configuration

SOP-8
Top View




AME 385-1.2

1. NC
2. NC
3. NC
4. -
5. NC
6. NC
7. NC
8. +

*** Die Attach:**
Conductive Epoxy

SOT-23
Top View




AME 385-1.2

1. +
2. -
3. NC*

*** Die Attach:**
Non-Conductive Epoxy

TO-92-3
Top View




AME 385-1.2

1. NC*
2. +
3. -

*** Die Attach:**
Non-Conductive Epoxy

TO-92-2
Top View




AME 385-1.2

1. +
2. -

*** Die Attach:**
Non-Conductive Epoxy

* The NC pin must float or be connected to - (negative)

■ Ordering Information



Accuracy	Operating Ambient Temperature Range	Package Type	Number of Pins	Special Feature1	Special Feature2 (For TO-92 Package Only)	
					Package	Lead Pitch
A: 0.5% (SOT-23) (SOP-8) (TO-92-2) (TO-92-3)	E: -40°C to +85°C	A: TO-92 E: SOT-2X H: SOP	A: 8 S: 2 T: 3	Z: Lead Free	N/A: Taping 1: Bulk	5.08mm 2.54mm

■ Ordering Information (contd.)

Part Number	Marking*	Accuracy	Package	Operating Ambient Temperature Range
AME385AEET	ABXww	0.5%	SOT-23	- 40°C to +85°C
AME385AEETZ	ABXww	0.5%	SOT-23	- 40°C to +85°C
AME385AEAS	AME 385 AEAS yyww	0.5%	TO-92-2	- 40°C to +85°C
AME385AEAS-1	AME 385 AEAS yyww	0.5%	TO-92-2	- 40°C to +85°C
AME385AEASZ	AME 385 AEAS yyww	0.5%	TO-92-2	- 40°C to +85°C
AME385AEASZ-1	AME 385 AEAS yyww	0.5%	TO-92-2	- 40°C to +85°C
AME385AEAT	AME 385 AEAT yyww	0.5%	TO-92-3	- 40°C to +85°C
AME385AEAT-1	AME 385 AEAT yyww	0.5%	TO-92-3	- 40°C to +85°C
AME385AEATZ	AME 385 AEAT yyww	0.5%	TO-92-3	- 40°C to +85°C
AME385AEATZ-1	AME 385 AEAT yyww	0.5%	TO-92-3	- 40°C to +85°C
AME385AEHA	385 AEHA yyww	0.5%	SOP-8	- 40°C to +85°C
AME385AEHAZ	385 AEHA yyww	0.5%	SOP-8	- 40°C to +85°C

Note: ww & yyww represents the date code pls see the Date Code Rule on Package Dimension.

* A line on top of the first letter represents lead free plating such as ABXww.

Please consult AME sales office or authorized Rep./Distributor for the availability of voltage accuracy and package type.

■ Absolute Maximum Ratings

Parameter	Maximum	Unit
Supply Current	50	mA

Caution: Stress above the listed absolute maximum rating may cause permanent damage to the device

■ Recommended Operating Conditions

Parameter	Symbol	Rating	Unit
Ambient Temperature Range	T_A	- 40 to +85	^oC
Junction Temperature Range	T_J	- 40 to +125	^oC
Storage Temperature Range	T_{STG}	- 65 to +150	^oC
Supply Current	100μA ~ 20mA		

■ Electrical Specifications

Unless otherwise specified, T_A= 0~70^{O}C, I_R = 100μA

Parameter	Symbol	Test Condition	Min	Typ	Max	Units
Reference Voltage, ±0.5%	V_{REF}	I_{REF} = 100μA	1.229	1.235	1.241	V
Reference Voltage Change With Current	$dV_{REF/I}$	$I_{MIN} \leq I \leq$ 1mA		1.5	3	mV
		1mA $\leq I \leq$ 20mA		5	20	
Reverse Dynamic Impedence	RDI	I_R= 100μA, f=20Hz		1.5		Ohm
Wideband Noise (rms)	Vn	I_R= 100μA, 10 Hz<f<10KHz		60		μV
Long term Stability		I_R= 100μA, T_A=25^{o}C, T=1000 Hours		20		ppm
Reference Voltage Temp. Coeff.	V_{REFTC}	0^{o}C < T_A < 70^{o}C		100		ppm/^{o}C
Operation Current	I_{OP}		0.030		20	mA


■ Thermal Information

Parameter	Package	Die Attach	Symbol	Maximum	Unit
Thermal Resistance* (Junction to Case)	SOT-23	Non-Conductive Epoxy	θ_{JC}	140	°C / W
	TO-92-2 TO-92-3			80	
	SOP-8	Conductive Epoxy		60	
Thermal Resistance (Junction to Ambient)	SOT-23	Non-Conductive Epoxy	θ_{JA}	280	°C / W
	TO-92-2 TO-92-3			150	
	SOP-8	Conductive Epoxy		150	
Internal Power Dissipation	SOT-23	Non-Conductive Epoxy	P_D	400	mW
	TO-92-2 TO-92-3			625	
	SOP-8	Conductive Epoxy		810	
Maximum Junction Temperature				150	°C
Solder Iron (10 Sec)**				350	°C


***** Measure θ_{JC} on center of molding compound if IC has no tab.
****** MIL-STD-202G 210F

■ Characterization Curve(For reference only)


Normalized Percentage Change vs. Temp.




Reference Voltage Change vs. Current




Reverse Characteristic



Forward Characteristic



Line Transient Response




■ Date Code Rule

Marking			Date Code		Year
A	A	A	W	W	xxx0
A	A	A	W	W	xxx1
A	A	A	W	W	xxx2
A	A	A	W	W	xxx3
A	A	A	W	W	xxx4
A	A	A	W	W	xxx5
A	A	A	W	W	xxx6
A	A	A	W	W	xxx7
A	A	A	W	W	xxx8
A	A	A	W	W	xxx9

■ Tape and Reel Dimension

SOT-23




Carrier Tape, Number of Components Per Reel and Reel Size

Package	Carrier Width (W)	Pitch (P)	Part Per Full Reel	Reel Size
SOT-23	8.0±0.1 mm	4.0±0.1 mm	3000pcs	180±1 mm

■ Tape and Reel Dimension


TO-92-3



Carrier Tape, Number of Components Per Reel and Reel Size

Package	Carrier Width (W)	Pitch (P)	Part Per Full Reel	Reel Size
TO-92-3	$18.0^{+1.0}_{-0.5}$ mm	12.7±0.2 mm	2000pcs	N/A

TO-92-2




Carrier Tape, Number of Components Per Reel and Reel Size

Package	Carrier Width (W)	Pitch (P)	Part Per Full Reel	Reel Size
TO-92-2	$18.0^{+1.0}_{-0.5}$ mm	12.7±0.2 mm	2000pcs	N/A

■ Tape and Reel Dimension

SOP-8




Carrier Tape, Number of Components Per Reel and Reel Size

Package	Carrier Width (W)	Pitch (P)	Part Per Full Reel	Reel Size
SOP-8	12.0±0.1 mm	4.0±0.1 mm	2500pcs	330±1 mm


■ Package Dimension

SOT-23



SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	1.00	1.40	0.0394	0.0551
A_1	0.00	0.15	0.0000	0.0059
b	0.35	0.50	0.0138	0.0197
D	2.70	3.10	0.1063	0.1220
E	1.40	1.80	0.0551	0.0709
e	1.90 BSC		0.0748 BSC	
H	2.40	3.00	0.09449	0.11811
L	0.35BSC		0.0138BSC	
q1	0^o	10^o	0^o	10^o


SOP-8



SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	1.35	1.75	0.05315	0.0689
A_1	0.10	0.30	0.00394	0.01181
A2	1.473 REF		0.05799 REF	
B	0.33	0.51	0.01299	0.02008
C	0.19	0.25	0.00748	0.00984
D	4.80	5.33	0.18898	0.20984
E	3.80	4.00	0.14961	0.15748
e	1.27 BSC		0.05000 BSC	
L	0.40	1.27	0.01575	0.05000
H	5.80	6.30	0.22835	0.24803
y	-	0.10	-	0.00394
q	0^o	8^o	0^o	8^o

■ Package Dimension


TO-92-3 (bulk pack)



SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.80	4.95	0.1102	0.1949
b	0.40REF		0.0157REF	
E	3.94REF		0.1551REF	
e	2.54REF		0.1000REF	
e1	1.27REF		0.0500REF	
L	12.70	15.49	0.5000	0.6098
R	2.29		0.0902	
W	0.35	0.76	0.0138	0.0299
D	3.80	4.95	0.1496	0.1949

Notes:
1. Package outline exclusive of any mold flashes dimension.
2. Package outline exclusive of burr dimension.
3. Lead pitch=2.54mm is bulk pack.
4. Lead pitch=5.08mm is tape pack.

TO-92-2 (bulk pack)




SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.00	4.95	0.1575	0.1949
b	0.40REF		0.0157REF	
E	3.94REF		0.1551REF	
e	2.54REF		0.1000REF	
e1	1.27REF		0.0500REF	
L	12.70	15.49	0.5000	0.6098
R	2.29		0.0902	
W	0.35	0.76	0.0138	0.0299
D	3.80	4.95	0.1496	0.1949

Notes:
1. Package outline exclusive of any mold flashes dimension.
2. Package outline exclusive of burr dimension.
3. Lead pitch=2.54mm is bulk pack.
4. Lead pitch=5.08mm is tape pack.

■ Package Dimension


TO-92-3 (tape pack)



SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.80	4.95	0.1102	0.1949
b	0.40REF		0.0157REF	
E	2.40	3.94	0.0945	0.1551
e	5.08REF		0.2REF	
e1	2.54REF		0.1REF	
L	12.70	15.49	0.5000	0.6098
R	2.00		0.0787	
W	0.35	0.76	0.0138	0.0299
D	3.80	4.95	0.1496	0.1949

Notes:
1. Package outline exclusive of any mold flashes.
2. Package outline exclusive of burr dimension.
3. Lead pitch=2.54mm is bulk pack.
4. Lead pitch=5.08mm is tape pack.

TO-92-2 (tape pack)



SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.80	4.95	0.1102	0.1949
b	0.40REF		0.0157REF	
E	2.40	3.94	0.0945	0.1551
e	5.08REF		0.2REF	
e1	2.54REF		0.1REF	
L	12.70	15.49	0.5000	0.6098
R	2.00		0.0787	
W	0.35	0.76	0.0138	0.0299
D	3.80	4.95	0.1496	0.1949

Notes:
1. Package outline exclusive of any mold flashes.
2. Package outline exclusive of burr dimension.
3. Lead pitch=2.54mm is bulk pack.
4. Lead pitch=5.08mm is tape pack.



www.ame.com.tw
E-Mail: sales@ame.com.tw

Life Support Policy:
These products of AME, Inc. are not authorized for use as critical components in life-support devices or systems, without the express written approval of the president of AME, Inc.
AME, Inc. reserves the right to make changes in the circuitry and specifications of its devices and advises its customers to obtain the latest version of relevant information.
© AME, Inc. , November 2008
Document: 2003/2037-DS385-1.2-G.03

Corporate Headquarter
AME, Inc.
2F, 302 Rui-Guang Road, Nei-Hu District
Taipei 114, Taiwan.
Tel: 886 2 2627-8687
Fax: 886 2 2659-2989