



深圳市信德意电子有限公司

常备现货 快速取样 购买请联系朱小姐

手机: 13510666820 QQ: 2355608068

网址: www.cxtke.com



**Advanced Power  
Electronics Corp.**

**AP9T15GH/J**

**Pb Free Plating Product**

*N-CHANNEL ENHANCEMENT MODE*


*POWER MOSFET*

▼ Low Gate Charge

▼ Capable of 2.5V gate drive

▼ Single Drive Requirement



▼ RoHS Compliant



|              |              |
|--------------|--------------|
| $BV_{DSS}$   | 20V          |
| $R_{DS(ON)}$ | 50m $\Omega$ |
| $I_D$        | 12.5A        |

## Description

The Advanced Power MOSFETs from APEC provide the designer with the best combination of fast switching, ruggedized device design, ultra low on-resistance and cost-effectiveness.



## Absolute Maximum Ratings

| Symbol                      | Parameter                                 | Rating     | Units               |
|-----------------------------|-------------------------------------------|------------|---------------------|
| $V_{DS}$                    | Drain-Source Voltage                      | 20         | V                   |
| $V_{GS}$                    | Gate-Source Voltage                       | $\pm 16$   | V                   |
| $I_D@T_C=25^\circ\text{C}$  | Continuous Drain Current, $V_{GS}$ @ 4.5V | 12.5       | A                   |
| $I_D@T_C=100^\circ\text{C}$ | Continuous Drain Current, $V_{GS}$ @ 4.5V | 8          | A                   |
| $I_{DM}$                    | Pulsed Drain Current <sup>1</sup>         | 60         | A                   |
| $P_D@T_C=25^\circ\text{C}$  | Total Power Dissipation                   | 12.5       | W                   |
|                             | Linear Derating Factor                    | 0.1        | W/ $^\circ\text{C}$ |
| $T_{STG}$                   | Storage Temperature Range                 | -55 to 150 | $^\circ\text{C}$    |
| $T_J$                       | Operating Junction Temperature Range      | -55 to 150 | $^\circ\text{C}$    |

## Thermal Data

| Symbol | Parameter                           | Value    | Units                     |
|--------|-------------------------------------|----------|---------------------------|
| Rthj-c | Thermal Resistance Junction-case    | Max. 10  | $^\circ\text{C}/\text{W}$ |
| Rthj-a | Thermal Resistance Junction-ambient | Max. 110 | $^\circ\text{C}/\text{W}$ |



## AP9T15GH/J

### Electrical Characteristics@T<sub>j</sub>=25°C(unless otherwise specified)

| Symbol                              | Parameter                                            | Test Conditions                                          | Min. | Typ. | Max. | Units |
|-------------------------------------|------------------------------------------------------|----------------------------------------------------------|------|------|------|-------|
| BV <sub>DSS</sub>                   | Drain-Source Breakdown Voltage                       | V <sub>GS</sub> =0V, I <sub>D</sub> =250uA               | 20   | -    | -    | V     |
| ΔBV <sub>DSS</sub> /ΔT <sub>j</sub> | Breakdown Voltage Temperature Coefficient            | Reference to 25°C, I <sub>D</sub> =1mA                   | -    | 0.02 | -    | V/°C  |
| R <sub>DS(ON)</sub>                 | Static Drain-Source On-Resistance                    | V <sub>GS</sub> =4.5V, I <sub>D</sub> =6A                | -    | -    | 50   | mΩ    |
|                                     |                                                      | V <sub>GS</sub> =2.5V, I <sub>D</sub> =5.2A              | -    | -    | 80   | mΩ    |
| V <sub>GS(th)</sub>                 | Gate Threshold Voltage                               | V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250uA | 0.5  | -    | 1.5  | V     |
| g <sub>fs</sub>                     | Forward Transconductance                             | V <sub>DS</sub> =5V, I <sub>D</sub> =10A                 | -    | 10   | -    | S     |
| I <sub>DSS</sub>                    | Drain-Source Leakage Current (T <sub>j</sub> =25°C)  | V <sub>DS</sub> =20V, V <sub>GS</sub> =0V                | -    | -    | 1    | uA    |
|                                     | Drain-Source Leakage Current (T <sub>j</sub> =150°C) | V <sub>DS</sub> =16V, V <sub>GS</sub> =0V                | -    | -    | 25   | uA    |
| I <sub>GSS</sub>                    | Gate-Source Leakage                                  | V <sub>GS</sub> =±16V                                    | -    | -    | ±100 | nA    |
| Q <sub>g</sub>                      | Total Gate Charge <sup>2</sup>                       | I <sub>D</sub> =10A                                      | -    | 5    | 8    | nC    |
| Q <sub>gs</sub>                     | Gate-Source Charge                                   | V <sub>DS</sub> =16V                                     | -    | 1    | -    | nC    |
| Q <sub>gd</sub>                     | Gate-Drain ("Miller") Charge                         | V <sub>GS</sub> =4.5V                                    | -    | 2    | -    | nC    |
| t <sub>d(on)</sub>                  | Turn-on Delay Time <sup>2</sup>                      | V <sub>DS</sub> =10V                                     | -    | 8    | -    | ns    |
| t <sub>r</sub>                      | Rise Time                                            | I <sub>D</sub> =10A                                      | -    | 55   | -    | ns    |
| t <sub>d(off)</sub>                 | Turn-off Delay Time                                  | R <sub>G</sub> =3.3Ω, V <sub>GS</sub> =5V                | -    | 10   | -    | ns    |
| t <sub>f</sub>                      | Fall Time                                            | R <sub>D</sub> =1Ω                                       | -    | 3    | -    | ns    |
| C <sub>iss</sub>                    | Input Capacitance                                    | V <sub>GS</sub> =0V                                      | -    | 360  | 580  | pF    |
| C <sub>oss</sub>                    | Output Capacitance                                   | V <sub>DS</sub> =20V                                     | -    | 70   | -    | pF    |
| C <sub>rss</sub>                    | Reverse Transfer Capacitance                         | f=1.0MHz                                                 | -    | 50   | -    | pF    |
| R <sub>g</sub>                      | Gate Resistance                                      | f=1.0MHz                                                 | -    | 1.67 | -    | Ω     |

### Source-Drain Diode

| Symbol          | Parameter                          | Test Conditions                           | Min. | Typ. | Max. | Units |
|-----------------|------------------------------------|-------------------------------------------|------|------|------|-------|
| V <sub>SD</sub> | Forward On Voltage <sup>2</sup>    | I <sub>S</sub> =10A, V <sub>GS</sub> =0V  | -    | -    | 1.3  | V     |
| t <sub>rr</sub> | Reverse Recovery Time <sup>2</sup> | I <sub>S</sub> =10A, V <sub>GS</sub> =0V, | -    | 17   | -    | ns    |
| Q <sub>rr</sub> | Reverse Recovery Charge            | dI/dt=100A/μs                             | -    | 9    | -    | nC    |

#### Notes:

1.Pulse width limited by safe operating area.

2.Pulse width ≤300us , duty cycle ≤2%.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance v.s. Gate Voltage




Fig 4. Normalized On-Resistance  
v.s. Junction Temperature




Fig 5. Forward Characteristic of  
Reverse Diode




Fig 6. Gate Threshold Voltage v.s.  
Junction Temperature



## AP9T15GH/J




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Switching Time Waveform




Fig 12. Gate Charge Waveform