

Mini-Size InGaAs Avalanche PHOTODIODE with Single-Mode Pigtail

FEATURES

- 2 Data Rate up to 2.7 Gbps
- 2 0.9 A/W Typical Responsivity
- 2 Breakdown voltage: 40V Typical
- 2 Wide Wavelength Band: 1260 nm to 1620 nm
- 2 Case Operating Temperature: -40 to 85°C
- 2 Coaxial Module with 9/125 μ m Single-Mode Fiber
- 2 Mini-size Package

APPLICATIONS


Receiver supports long distance fiber-optics communication systems with performance up to 2.7 Gb/s data rate, -40 to 85 °C operating temperature.

ELECTRICAL AND OPTICAL CHARACTERISTICS (Tc=25°C)						
Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
	Detection Range	λ	1260	-	1620	nm
V _{BR}	Breakdown Voltage	I _{dark} =10 μ A	35		47	V
V _{OP}	Operating Voltage	Best Sensitivity		V _{BR} -3	V _{BR} -2	V
dV _{BR} /dT	Temperature Coefficient of Breakdown Voltage		0.06	0.07	0.10	V/°C
I _{dark}	Dark Current	V _R =0.9 V _{BR}		80	100	nA
R	Responsivity	λ =1550nm, M=1	0.85			A/W
C	Capacitance	V _R =0.9 V _{BR} , f=1MHz		0.5	0.8	pF
ORL	Optical Return Loss	V _{op} , λ = 1550 nm	40			dB
BW	Bandwidth	R _L =50 Ω , -3 dB, M=10	2.5	3		GHz

Absolute Maximum Ratings (Tc=25 °C)				
Symbol	Parameter	Minimum	Maximum	Unit
I _F	APD Forward Current		2	mA
I _R	APD Reverse Current		3	mA
V _R	APD Reverse Voltage		V _{BR}	V
T _{opr}	Operating Temperature	-40	85	°C
T _{stg}	Storage Temperature	-40	85	°C

Stress in excess of the absolute Maximum Ratings may cause permanent damage to the device.

MECHANICAL DIMENSION (mm) and PIN ASSIGNMENT



Note: 1. Specifications subject to change without notice.

2. Other PIN assignment is available upon request.

ORDER INFORMATION

Part No.: A P D - 1 3 5 ☐ - ☐ ☐ ☐

Code	Fiber Buffer (mm)
0	900
1	250

Code	Flange
V	Vertical
H	Horizontal
X	No Flange

Code	Connector Type
S	SC/PC
F	FC/PC
T	ST/PC
L	LC/PC
X	No Connector
SA	SC/APC
FA	FC/APC
LA	LC/APC