## Revision History
## 128k x 8 BIT AS6C1008L

| Revision | Details | Date |
|---|---|---|
| Rev 1.a | Preliminary datasheet | Oct 2007 |
| Rev 2.a | Delete -35ns speed grade information | Apr 2016 |

## FEATURES

- Fast access time : 55ns
- Low power consumption:
  Operating current : 10mA (TYP.)
  Standby current : 1µA (TYP.)
- Single 2.7V ~ 5.5V power supply
- All outputs TTL compatible
- Fully static operation
- Tri-state output
- Data retention voltage : 1.5V (MIN.)
- **Lead freeandgreenpackageavailable**
- Package : 32-pin 450 mil SOP
  32-pin 600 mil P-DIP
  32-pin 8mm x 20mm TSOP-I
  32-pin 8mm x 13.4mm STSOP
  36-ball 6mm x 8mm TFBGA

## GENERAL DESCRIPTION

The AS6C1008L is a 1,048,576-bit low power CMOS static random access memory organized as 131,072 words by 8 bits. It is fabricated using very high performance, high reliability CMOS technology. Its standby current is stable within the range of operating temperature.


The AS6C1008L is well designed for very low power system applications, and particularly well suited for battery back-up nonvolatile memory application.

The AS6C1008-55 operates from a single power supply of 2.7V ~ 5.5V and all inputs and outputs are fully TTL compatible

## PRODUCT FAMILY

| Product Family | Operating Temperature | Vcc Range | Speed |
|---|---|---|---|
| AS6C1008L | -40 ~ 85℃ | 2.7 ~ 5.5V | 55ns |


## FUNCTIONAL BLOCK DIAGRAM





## PIN DESCRIPTION

| SYMBOL | DESCRIPTION |
|---|---|
| A0 - A16 | Address Inputs |
| DQ0 – DQ7 | Data Inputs/Outputs |
| CE#, CE2 | Chip Enable Inputs |
| WE# | Write Enable Input |
| OE# | Output Enable Input |
| Vcc | Power Supply |
| Vss | Ground |
| NC | No Connection |


## PIN CONFIGURATION




SOP/P-DIP




TSOP-I/STSOP




TFBGA

## ABSOLUTE MAXIMUM RATINGS*

| PARAMETER | SYMBOL | RATING | UNIT |
|---|---|---|---|
| Terminal Voltage with Respect to $V_{SS}$ | $V_{TERM}$ | -0.5 to 7.0 | V |
| Operating Temperature | $T_A$ | -40 to 85(I grade) | ℃ |
| Storage Temperature | $T_{STG}$ | -65 to 150 | ℃ |
| Power Dissipation | $P_D$ | 1 | W |
| DC Output Current | $I_{OUT}$ | 50 | mA |
| Soldering Temperature (under 10 sec) | $T_{SOLDER}$ | 260 | ℃ |

*Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to the absolute maximum rating conditions for extended period may affect device reliability.

## TRUTH TABLE

| MODE | CE# | CE2 | OE# | WE# | I/O OPERATION | SUPPLY CURRENT |
|---|---|---|---|---|---|---|
| Standby | H | X | X | X | High-Z | $I_{SB1}$ |
| | X | L | X | X | High-Z | $I_{SB1}$ |
| Output Disable | L | H | H | H | High-Z | $I_{CC}$,$I_{CC1}$ |
| Read | L | H | L | H | $D_{OUT}$ | $I_{CC}$,$I_{CC1}$ |
| Write | L | H | X | L | $D_{IN}$ | $I_{CC}$,$I_{CC1}$ |

Note: H = $V_{IH}$, L = $V_{IL}$, X = Don't care.

## DC ELECTRICAL CHARACTERISTICS

| PARAMETER | SYMBOL | TEST CONDITION | | MIN. | TYP. *4 | MAX. | UNIT |
|---|---|---|---|---|---|---|---|
| Supply Voltage | $V_{CC}$ | | | 2.7 | 3.0 | 5.5 | V |
| Input High Voltage | $V_{IH}$ *1 | | | 0.7*Vcc | - | $V_{CC}$+0.3 | V |
| Input Low Voltage | $V_{IL}$ *2 | | | - 0.2 | - | 0.6 | V |
| Input Leakage Current | $I_{LI}$ | $V_{CC} \geqq V_{IN} \geqq V_{SS}$ | | - 1 | - | 1 | µA |
| Output Leakage Current | $I_{LO}$ | $V_{CC} \geqq V_{OUT} \geqq V_{SS}$, Output Disabled | | - 1 | - | 1 | µA |
| Output High Voltage | $V_{OH}$ | $I_{OH}$ = -1mA | | 2.2 | 2.7 | - | V |
| Output Low Voltage | $V_{OL}$ | $I_{OL}$ = 2mA | | - | - | 0.4 | V |
| Average Operating Power supply Current | $I_{CC}$ | Cycle time = Min.<br>CE# = $V_{IL}$ and CE2 = $V_{IH}$,<br>$I_{I/O}$ = 0mA | | - | 10 | 60 | mA |
| | $I_{CC1}$ | Cycle time = 1µs<br>CE#$\leqq$0.2V and CE2$\geqq$$V_{CC}$-0.2V,<br>$I_{I/O}$ = 0mA<br>other pins at 0.2V or $V_{CC}$-0.2V | | - | 1 | 10 | mA |
| Standby Power Supply Current | $I_{SB1}$ | CE# $\geqq$$V_{CC}$-0.2V<br>or CE2$\leqq$0.2V<br>Other pins at 0.2V<br>or Vcc-0.2V | -SL | - | 1 | 10 | µA |
| | | | -SLE/-SLI | - | 1 | 10 | µA |

Notes:
1. $V_{IH}$(max) = $V_{CC}$ + 3.0V for pulse width less than 10ns.
2. $V_{IL}$(min) = $V_{SS}$ - 3.0V for pulse width less than 10ns.
3. Over/Undershoot specifications are characterized, not 100% tested.
4. Typical values are included for reference only and are not guaranteed or tested.
   Typical valued are measured at $V_{CC}$ = $V_{CC}$(TYP.) and $T_A$ = 25℃

## CAPACITANCE ($T_A$ = 25°C, f = 1.0MHz)

| PARAMETER | SYMBOL | MIN. | MAX | UNIT |
|---|---|---|---|---|
| Input Capacitance | $C_{IN}$ | - | 6 | pF |
| Input/Output Capacitance | $C_{I/O}$ | - | 8 | pF |

Note : These parameters are guaranteed by device characterization, but not production tested.

## AC TEST CONDITIONS

| | |
|---|---|
| Input Pulse Levels | 0.2V to $V_{CC}$ - 0.2V |
| Input Rise and Fall Times | 3ns |
| Input and Output Timing Reference Levels | 1.5V |
| Output Load | $C_L$ = 50pF + 1TTL, $I_{OH}/I_{OL}$ = -1mA/2mA |

## AC ELECTRICAL CHARACTERISTICS

### (1) READ CYCLE

| PARAMETER | SYM. | AS6C1008L | | UNIT |
|---|---|---|---|---|
| | | MIN. | MAX. | |
| Read Cycle Time | $t_{RC}$ | 35 | - | ns |
| Address Access Time | $t_{AA}$ | - | 35 | ns |
| Chip Enable Access Time | $t_{ACE}$ | - | 35 | ns |
| Output Enable Access Time | $t_{OE}$ | - | 25 | ns |
| Chip Enable to Output in Low-Z | $t_{CLZ}$* | 10 | - | ns |
| Output Enable to Output in Low-Z | $t_{OLZ}$* | 5 | - | ns |
| Chip Disable to Output in High-Z | $t_{CHZ}$* | - | 15 | ns |
| Output Disable to Output in High-Z | $t_{OHZ}$* | - | 15 | ns |
| Output Hold from Address Change | $t_{OH}$ | 10 | - | ns |


### (2) WRITE CYCLE

| PARAMETER | SYM. | AS6C1008L | | UNIT |
|---|---|---|---|---|
| | | MIN. | MAX. | |
| Write Cycle Time | $t_{WC}$ | 35 | - | ns |
| Address Valid to End of Write | $t_{AW}$ | 30 | - | ns |
| Chip Enable to End of Write | $t_{CW}$ | 30 | - | ns |
| Address Set-up Time | $t_{AS}$ | 0 | - | ns |
| Write Pulse Width | $t_{WP}$ | 25 | - | ns |
| Write Recovery Time | $t_{WR}$ | 0 | - | ns |
| Data to Write Time Overlap | $t_{DW}$ | 20 | - | ns |
| Data Hold from End of Write Time | $t_{DH}$ | 0 | - | ns |
| Output Active from End of Write | $t_{OW}$* | 5 | - | ns |
| Write to Output in High-Z | $t_{WHZ}$* | - | 15 | ns |


*These parameters are guaranteed by device characterization, but not production tested.

## TIMING WAVEFORMS

**READ CYCLE 1** (Address Controlled) (1,2)





**READ CYCLE 2** (CE# and CE2 and OE# Controlled) (1,3,4,5)





Notes :
1.WE# is high for read cycle.
2.Device is continuously selected OE# = low, CE# = low., CE2 = high.
3.Address must be valid prior to or coincident with CE# = low, CE2 = high; otherwise $t_{AA}$ is the limiting parameter.
4.$t_{CLZ}$, $t_{OLZ}$, $t_{CHZ}$ and $t_{OHZ}$ are specified with $C_L$ = 5pF. Transition is measured ±500mV from steady state.
5.At any given temperature and voltage condition, $t_{CHZ}$ is less than $t_{CLZ}$ , $t_{OHZ}$ is less than $t_{OLZ}$.

**WRITE CYCLE 1** (WE# Controlled) (1,2,3,5,6)




**WRITE CYCLE 2** (CE# and CE2 Controlled) (1,2,5,6)




Notes :
1.WE#, CE# must be high or CE2 must be low during all address transitions.
2.A write occurs during the overlap of a low CE#, high CE2, low WE#.
3.During a WE#controlled write cycle with OE# low, $t_{WP}$ must be greater than $t_{WHZ} + t_{DW}$ to allow the drivers to turn off and data to be placed on the bus.
4.During this period, I/O pins are in the output state, and input signals must not be applied.
5.If the CE#low transition and CE2 high transition occurs simultaneously with or after WE# low transition, the outputs remain in a high impedance state.
6.$t_{OW}$ and $t_{WHZ}$ are specified with $C_L$ = 5pF. Transition is measured ±500mV from steady state.


## DATA RETENTION CHARACTERISTICS

| PARAMETER | SYMBOL | TEST CONDITION | | MIN. | TYP. | MAX. | UNIT |
|---|---|---|---|---|---|---|---|
| $V_{CC}$ for Data Retention | $V_{DR}$ | CE# ≧ $V_{CC}$ - 0.2V<br>or CE2 ≦ 0.2V | | 1.5 | - | 5.5 | V |
| Data Retention Current | $I_{DR}$ | $V_{CC}$ = 1.5V<br>CE# ≧ $V_{CC}$ - 0.2V<br>or CE2 ≦ 0.2V<br>others at 0.2V or Vcc-0.2V | -SL | - | 0.5 | 8 | µA |
| | | | -SLE/-SLI | - | 0.5 | 8 | µA |
| Chip Disable to Data Retention Time | $t_{CDR}$ | See Data Retention Waveforms (below) | | 0 | - | - | ns |
| Recovery Time | $t_R$ | | | $t_{RC*}$ | - | - | ns |


$t_{RC*}$ = Read Cycle Time

## DATA RETENTION WAVEFORM

**Low Vcc Data Retention Waveform (1)** (CE# controlled)





**Low Vcc Data Retention Waveform (2)** (CE2 controlled)




## PACKAGE OUTLINE DIMENSION

**32 pin 450 mil SOP Package Outline Dimension**




| UNIT / SYM. | INCH.(BASE) | MM(REF) |
|---|---|---|
| A | 0.118 (MAX) | 2.997 (MAX) |
| A1 | 0.004(MIN) | 0.102(MIN) |
| A2 | 0.111(MAX) | 2.82(MAX) |
| b | 0.016(TYP) | 0.406(TYP) |
| c | 0.008(TYP) | 0.203(TYP) |
| D | 0.817(MAX) | 20.75(MAX) |
| E | 0.445 ±0.005 | 11.303 ±0.127 |
| E1 | 0.555 ±0.012 | 14.097 ±0.305 |
| e | 0.050(TYP) | 1.270(TYP) |
| L | 0.0347 ±0.008 | 0.881 ±0.203 |
| L1 | 0.055 ±0.008 | 1.397 ±0.203 |
| S | 0.026(MAX) | 0.660 (MAX) |
| y | 0.004(MAX) | 0.101(MAX) |
| ? | $0^o$ -$10^o$ | $0^o$ -$10^o$ |


**32 pin 600 mil P-DIP Package Outline Dimension**




| SYM. \ UNIT | INCH(BASE) | MM(REF) |
|---|---|---|
| A1 | 0.001 (MIN) | 0.254 (MIN) |
| A2 | 0.150 ± 0.005 | 3.810 ± 0.127 |
| B | 0.018 ± 0.005 | 0.457 ± 0.127 |
| D | 1.650 ± 0.005 | 41.910 ± 0.127 |
| E | 0.600 ± 0.010 | 15.240 ± 0.254 |
| E1 | 0.544 ± 0.004 | 13.818 ± 0.102 |
| e | 0.100 (TYP) | 2.540 (TYP) |
| eB | 0.640 ± 0.020 | 16.256 ± 0.508. |
| L | 0.130 ± 0.010 | 3.302 ± 0.254 |
| S | 0.075 ± 0.010 | 1.905 ± 0.254 |
| Q1 | 0.070 ± 0.005 | 1.778 ± 0.127 |


Note : D/E1/S dimension do not include mold flash.

**32 pin 8mm x 20mm TSOP-I Package Outline Dimension**





| UNIT / SYM. | INCH(BASE) | MM(REF) |
|---|---|---|
| A | 0.047 (MAX) | 1.20 (MAX) |
| A1 | 0.004 ±0.002 | 0.10 ±0.05 |
| A2 | 0.039 ±0.002 | 1.00 ±0.05 |
| b | 0.008 + 0.002 - 0.001 | 0.20 + 0.05 -0.03 |
| c | 0.005 (TYP) | 0.127 (TYP) |
| D | 0.724 ±0.004 | 18.40 ±0.10 |
| E | 0.315 ±0.004 | 8.00 ±0.10 |
| e | 0.020 (TYP) | 0.50 (TYP) |
| HD | 0.787 ±0.008 | 20.00 ±0.20 |
| L | 0.0197 ±0.004 | 0.50 ±0.10 |
| L1 | 0.0315 ±0.004 | 0.08 ±0.10 |
| y | 0.003 (MAX) | 0.076 (MAX) |
| Θ | 0°～5° | 0°～5° |


**32 pin 8mm x 13.4mm STSOP Package Outline Dimension**





| SYM. \ UNIT | INCH(BASE) | MM(REF) |
|---|---|---|
| A | 0.049 (MAX) | 1.25 (MAX) |
| A1 | 0.005 ±0.002 | 0.130 ±0.05 |
| A2 | 0.039 ±0.002 | 1.00 ±0.05 |
| b | 0.008 ±0.01 | 0.20±0.025 |
| c | 0.005 (TYP) | 0.127 (TYP) |
| D | 0.465 ±0.004 | 11.80 ±0.10 |
| E | 0.315 ±0.004 | 8.00 ±0.10 |
| e | 0.020 (TYP) | 0.50 (TYP) |
| HD | 0.528±0.008 | 13.40 ±0.20. |
| L | 0.0197 ±0.004 | 0.50 ±0.10 |
| L1 | 0.0315 ±0.004 | 0.8 ±0.10 |
| y | 0.003 (MAX) | 0.076 (MAX) |
| Θ | 0°～5° | 0°～5° |

**36 ball 6mm × 8mm TFBGA Package Outline Dimension**




SIDE VIEW




DETAIL B

## ORDERING INFORMATION

| Alliance | Organization | VCC Range | Package | Operating Temp | Speed ns |
|---|---|---|---|---|---|
| AS6C1008-55SINL | 128K x 8 | 2.7 - 5.5V | 32 pin 450mil SOP | Industrial ~ -40 C - 85℃ | 55 |
| AS6C1008-55TINL | 128K x 8 | 2.7 - 5.5V | 32 pin TSOP-1(8x20mm) | Industrial ~ -40 C - 85℃ | 55 |
| AS6C1008-55STINL | 128K x 8 | 2.7 - 5.5V | 32 pin sTSOP (8x13.3mm) | Industrial ~ -40 C - 85℃ | 55 |

## PART NUMBERING SYSTEM

| AS6C | 1008 | -55 | X | X | N | L |
|---|---|---|---|---|---|---|
| SRAM prefix | Device Number<br>10 = 1M<br>08 = x8 | Access Time | Package Option<br>S=32 pin 450mil SOP<br>T=32 pin TSOP-1(8x20mm)<br>ST=32 pin sTSOP (8x13.3mm) | Temperature Range<br>I = Industrial<br>(-40 to + 85℃ | N = Lead Free RoHS compliant part | super low power |



Alliance Memory, Inc.
511 Taylor Way,
San Carlos, CA 94070
Tel: 650-610-6800
Fax: 650-620-9211
www.alliancememory.com

Copyright © Alliance Memory
All Rights Reserved

© Copyright 2007 Alliance Memory, Inc. All rights reserved. Our three-point logo, our name and Intelliwatt are trademarks or registered trademarks of Alliance. All other brand and product names may be the trademarks of their respective companies. Alliance reserves the right to make changes to this document and its products at any time without notice. Alliance assumes no responsibility for any errors that may appear in this document. The data contained herein represents Alliance's best data and/or estimates at the time of issuance. Alliance reserves the right to change or correct this data at any time, without notice. If the product described herein is under development, significant changes to these specifications are possible. The information in this product data sheet is intended to be general descriptive information for potential customers and users, and is not intended to operate as, or provide, any guarantee or warrantee to any user or customer. Alliance does not assume any responsibility or liability arising out of the application or use of any product described herein, and disclaims any express or implied warranties related to the sale and/or use of Alliance products including liability or warranties related to fitness for a particular purpose, merchantability, or infringement of any intellectual property rights, except as express agreed to in Alliance's Terms and Conditions of Sale (which are available from Alliance). All sales of Alliance products are made exclusively according to Alliance's Terms and Conditions of Sale. The purchase of products from Alliance does not convey a license under any patent rights, copyrights; mask works rights, trademarks, or any other intellectual property rights of Alliance or third parties. Alliance does not authorize its products for use as critical components in life-supporting systems where a malfunction or failure may reasonably be expected to result in significant injury to the user, and the inclusion of Alliance products in such life-supporting systems implies that the manufacturer assumes all risk of such use and agrees to indemnify Alliance against all claims arising from such use.