



GaAs MMIC Control FET in SOT 143 DC–2.5 GHz



AF002C1–32

Features

- Low Cost
- Small SOT 143 Package
- Series or Shunt Configuration
- Low DC Current Drain
- Ideal Switch Building Block



Description

The AF002C1–32 consists of a single GaAs switching FET that can be used in both series and shunt configurations. A positive control voltage may be used by simply adding 3 DC blocking capacitors.

Isolation performance degrades at higher frequencies due to package parasitics. These parasitics can be tuned out in narrow band applications as shown in a AF002C1–39 data sheet.

Absolute Maximum Ratings

RF Input Power:	2W > 500 MHz 0/–8V
	0.5W @ 50 MHz 0/–8V
Control Voltage:	+0.2V, –10V
Operating Temperature:	–40°C to 85°C
Storage Temperature:	–65°C to 150°C
Θ _{JC} :	25°C/W

Note: Exceeding these parameters may cause irreversible damage.

Operating Characteristics at 25°C

Switching Characteristics			
RISE, FALL (10/90% or 90/10% RF)	3	ns	Typ
ON, OFF (50% CTL to 90/10% RF)	6	ns	Typ
Input Power for 1 dB Compression			
Control Voltages (Vdc)	0/–5	0/–8	
0.5–2.0 GHz	+20	24	dBm Typ
Control Voltages			
V _O (Low)	0 to –0.2V @ 20 μA Max		
V _O (High)	–5V @ 50 μA to –9V @ 200 μA Max		


Electrical Specifications at 25°C

R _{ON} ¹	C _{OFF} ²	Insertion Loss 1 GHz ^{3,4}	
		Series	Shunt
6.4	0.13	0.7 dB	0.2


1. R_{ON} – Resistance in ohms in low impedance state when '0' Volts is applied on Gate (G).
2. C_{OFF} – Capacitance (FET) in pF in high impedance state when –5V is applied on Gate (G).
3. Package inductance is 3 nH, package capacitance is 0.17 pF.
4. Insertion loss changes by 0.003 dB/°C.

Typical Performance Data

Series Configuration (Not Tuned)




Insertion Loss vs. Frequency



Isolation vs. Frequency

Pin Out




Truth Table (Negative Voltage Operation)


Shunt			
S	D	G	State
GND	RF	−5	Insertion Loss
		0	Isolation
Series			
RF	RF	−5	Isolation
		0	Insertion Loss

Positive Voltage Operation

Shunt



Series



C_{BL} , C_{BP} - Choose value for low impedance at desired operating frequency.

Truth Table (Positive Voltage Operation)

Shunt			
S	D	G	State
GND	RF	0	Insertion Loss
		+5	Isolation
Series			
RF	RF	0	Isolation
		+5	Insertion Loss

RF GaAs MMIC Products in Metal Packages

2

Numerical Index

Part Number	Page	Part Number	Page	Part Number	Page
AD004T2-00	2-44	AK006R2-01	2-30	AS006M1-01	2-8
AD004T2-11	2-44	AK006R2-10	2-30	AS006M1-10	2-8
AE002M2-29	2-74	AK006R2-00	2-28	AS006M2-00	2-16
AE002M4-05	2-42	AK402D4-11	2-64	AS006M2-01	2-22
AH002R2-11	2-26	AK402D4-31	2-68	AS006M2-10	2-22
AK002D2-11	2-70	AN002M2-29	2-72	AS006R1-00	2-4
AK002D4-11	2-62	AN002M4-31	2-38	AS006R2-00	2-16
AK002D4-31	2-66	AN002M4-05	2-40	AS006R2-01	2-20
AK002M4-00	2-36	AS002M4-00	2-34	AS006R2-10	2-20
AK002M4-31	2-38	AS004L1-08	2-6	AS406M2-01	2-24
AK004L1-11	2-12	AS004L1-11	2-6	AS406R2-01	2-24
AK004M1-11	2-14	AS004L2-11	2-18	AT001D3-11	2-60
AK004M2-11	2-32	AS004M1-08	2-8	AT001D4-31	2-56
AK004R2-11	2-30	AS004M1-11	2-8	AT001D6-31	2-58
AK006L1-00	2-10	AS004M2-08	2-22	AT002D8-31	2-54
AK006L1-01	2-12	AS004M2-11	2-22	AT002N5-00	2-49
AK006L1-10	2-12	AS004R2-08	2-20	AT002N5-01	2-49
AK006M1-00	2-10	AS004R2-11	2-20	AT002N5-10	2-49
AK006M1-01	2-14	AS006L1-00	2-4	AT002N5-11	2-49
AK006M1-10	2-14	AS006L1-01	2-6	AT002S3-11	2-52
AK006M2-01	2-32	AS006L1-10	2-6	AT004N3-11	2-46
AK006M2-10	2-32	AS006L2-00	2-18	AT006N3-00	2-46
AK006M2-00	2-28	AS006L2-01	2-18	AT006N3-10	2-46
AK006R1-00	2-10	AS006M1-00	2-4	AT006N3-01	2-46

 0585443 0002501 710 