

TSSOP ORDERING CODE ADDENDUM

1. Ordering Information

1.1 AT97SC3205 SPI TPM – TSSOP

Table 1-1. AT97SC3205 SPI TPM TSSOP Ordering Information

Atmel Ordering Code	Package	Description	Operation Range
AT97SC3205-X3A12-10	28-pin 4.4mm TSSOP	Lead-free, RoHS v1.2 rev 116 Standard Mode SPI TPM with Real Mode EK, 2066B User NV	Commercial (0°C to 70°C)
AT97SC3205-U3A12-10			Industrial (-40°C to 85°C)
AT97SC3205-X3A12-20		Lead-free, RoHS v1.2 rev 116 Standard Mode SPI TPM with Signed EK (X.509 Certificate), 2066B User NV	Commercial (0°C to 70°C)
AT97SC3205-U3A12-20			Industrial (-40°C to 85°C)
AT97SC3205-X3A15-10		Lead-free, RoHS v1.2 rev 116 FIPS/Flex Mode SPI TPM with Real Mode EK, 2066 User NV	Commercial (0°C to 70°C)
AT97SC3205-U3A15-10			Industrial (-40°C to 85°C)
AT97SC3205-X3A15-20		Lead-free, RoHS v1.2 rev 116 FIPS/Flex Mode SPI TPM with Signed EK (X.509 Certificate), 2066 User NV	Commercial (0°C to 70°C)
AT97SC3205-U3A15-20			Industrial (-40°C to 85°C)

1.2 AT97SC3205T I²C TPM – TSSOP

Table 1-2. AT97SC3205T I²C TPM TSSOP Ordering Information

Atmel Ordering Code	Package	Description	Operation Range
AT97SC3205T-X3A14-10	28-pin 4.4mm TSSOP	Lead-free, RoHS v1.2 rev 116 Standard Mode I ² C TPM with Real Mode EK, 2066 User NV	Commercial (0°C to 70°C)
AT97SC3205T-U3A14-10			Industrial (-40°C to 85°C)
AT97SC3205T-X3A14-20		Lead-free, RoHS v1.2 rev 116 Standard Mode I ² C TPM with Signed EK (X.509 Certificate), 2066 User NV	Commercial (0°C to 70°C)
AT97SC3205T-U3A14-20			Industrial (-40°C to 85°C)
AT97SC3205T-X3A16-10		Lead-free, RoHS v1.2 rev 116 FIPS/Flex Mode I ² C TPM with Real Mode EK, 2066 User NV	Commercial (0°C to 70°C)
AT97SC3205T-U3A16-10			Industrial (-40°C to 85°C)
AT97SC3205T-X3A16-20		Lead-free, RoHS v1.2 rev 116 FIPS/Flex Mode I ² C TPM with Signed EK (X.509 Certificate), 2066 User NV	Commercial (0°C to 70°C)
AT97SC3205T-U3A16-20			Industrial (-40°C to 85°C)

2. TPM Configuration

2.1 TPM TSSOP Package EK Configuration

The Atmel® Trusted Platform Module (TPM) TSSOP package is shipped with pregenerated endorsement key pairs resident on the TPM. This configuration is considered the Real or Normal mode of the operation. Atmel can optionally support an X.509 EK Certificate (Signed-Real-Mode) stored in NV Storage as defined in the TCG Client Specific Implementation Specification for Conventional BIOS. Please contact Atmel for more information regarding Atmel EK Certificates.

2.2 FIPS/Flexible Mode

The FIPS/Flexible devices are shipped by Atmel in Flexible mode allowing the customer to permanently set and lock the device into either Standard, Legacy FIPS-140-2 certified, or WIN8 FIPS-140-2 certified mode during platform or device initialization. Please reference the Atmel Application Note, “Configuring FIPS/Flexible Devices” by contacting an Atmel Sales Representative:

<http://www.atmel.com/about/contact/distributors/default.aspx?contactType=Sales%20Representative>

3. Revision History

Doc. Rev.	Date	Comments
8872B	06/2014	Add AT97SC3205T I ² C TSSOP ordering codes. Add and update AT97SC3205 SPI TSSOP codes.
8872A	12/2013	Initial document release.



© 2014 Atmel Corporation. / Rev.: Atmel-8872B-TPM-AT97SC3205-3205T-TSSOP-Addendum_062014.

Atmel®, Atmel logo and combinations thereof, Enabling Unlimited Possibilities, and others are registered trademarks or trademarks of Atmel Corporation in U.S. and other countries. Other terms and product names may be trademarks of others.

DISCLAIMER: The information in this document is provided in connection with Atmel products. No license, express or implied, by estoppel or otherwise, to any intellectual property right is granted by this document or in connection with the sale of Atmel products. EXCEPT AS SET FORTH IN THE ATMEL TERMS AND CONDITIONS OF SALES LOCATED ON THE ATMEL WEBSITE, ATMEL ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLIED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL ATMEL BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS AND PROFITS, BUSINESS INTERRUPTION, OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF ATMEL HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. Atmel makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and products descriptions at any time without notice. Atmel does not make any commitment to update the information contained herein. Unless specifically provided otherwise, Atmel products are not suitable for, and shall not be used in, automotive applications. Atmel products are not intended, authorized, or warranted for use as components in applications intended to support or sustain life.

SAFETY-CRITICAL, MILITARY, AND AUTOMOTIVE APPLICATIONS DISCLAIMER: Atmel products are not designed for and will not be used in connection with any applications where the failure of such products would reasonably be expected to result in significant personal injury or death ("Safety-Critical Applications") without an Atmel officer's specific written consent. Safety-Critical Applications include, without limitation, life support devices and systems, equipment or systems for the operation of nuclear facilities and weapons systems. Atmel products are not designed nor intended for use in military or aerospace applications or environments unless specifically designated by Atmel as military-grade. Atmel products are not designed nor intended for use in automotive applications unless specifically designated by Atmel as automotive-grade.