maxiFLOW™ Heat Sink for Full Brick DC-DC Converter

ATS PART # ATS-1108-C1-R0




*Image is for illustration purposes only.

Features & Benefits

- High performance maxiFLOW™ design features less pressure drop and more surface area that maximizes the effective convection (air) cooling
- Hole pattern fits standard full power brick modules
- Pre-assembled with Chomerics T766 phase change material
- Heat sink assembly packaged with 3 sets of screws (M3 Philips Pan Head) at 5, 6 and 8 mm lengths


Assembly Part Number 4 Screws per Set	Length (mm)
ATS-1108-C2-R0	5
ATS-1108-C3-R0	6
ATS-1108-C4-R0	8

Thermal Performance

AIR VELOCITY		THERMAL RESISTANCE	
FT/MIN	M/S	°C/W (UNDUCTED FLOW)	°C/W (DUCTED FLOW)
200	1.0	9.36	1.63
300	1.5	6.82	
400	2.0	4.89	
500	2.5	3.69	
600	3.0	2.87	
700	3.5	2.35	
800	4.0	1.99	

Product Details

DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D	DIMENSION E	DIMENSION F	INTERFACE MATERIAL	FINISH
116.80 mm	61.00 mm	6.10 mm	61.60 mm	50.80 mm	106.68 mm	CHOMERICS T766	GOLD ANODIZED



NOTES:

1) Thermal performance data are provided for reference only. Actual performance may vary by application.
2) ATS reserves the right to update or change its products without notice to improve the design or performance.
3) Standard lead time is 4-6 weeks ARO.
4) Contact ATS to learn about custom options available.
5) Dimension D = heat sink height from bottom of the base to the top of the fin field.
6) Dimension E = Hole Width
7) Dimension F = Hole Length

ATS ADVANCED THERMAL SOLUTIONS, INC.
Innovations in Thermal Management®

For further technical information, please contact Advanced Thermal Solutions, Inc.
89-27 ACCESS ROAD, NORWOOD, MA 02062 USA | T: 781.769. 2800 F: 781.769.9979 | WWW.QATS.COM