High Performance BGA Cooling Solutions w/ Thermal Tape Attachment




Image above is for illustration purpose only.

ATS Part#: **ATS-54330K-C1-R0**

Description: High Performance Extrusion, T412, BLACK-ANODIZED

Heat Sink Type: Straight Fin

Heat Sink Attachment: THERMAL TAPE

Equivalent Part Number: ATS-54330K-C2-R0

Features & Benefits

- High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- Designed specifically for BGAs and other surface mount packages
- Comes pre-assembled with high performance thermal interface material

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	5.78 °C/W	4.36 °C/W	3.70 °C/W	3.29 °C/W	3.00 °C/W	2.78 °C/W	2.61 °C/W
	Ducted Flow	3.19	n/a	n/a	n/a	n/a	n/a	n/a

Product Detail


Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish
	33.0 mm	33.0 mm	14.5 mm	mm	T412	BLACK-ANODIZED

Image above is for illustration purpose only.

Notes:

- Dimension A and B refer to component size.
- Dimension C is the heat sink height from the bottom of the base to the top of the fin field.
- ATS-54330K-C2-R0 is the exact heat sink assembly with an equivalent thermal interface material (Saint Gobain C675).
- Thermal performance data are provided for reference only. Actual performance may vary by application.
- ATS reserves the right to update or change its products without notice to improve the design or performance.
- ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant.
- Contact ATS to learn about custom options available.

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.

© 2012 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA

ATS ADVANCED THERMAL SOLUTIONS, INC. Innovations in Thermal Management®

Rev - 121101