

High Performance ASIC Cooling Solutions



ATS Part#: **ATS-56011-C4-R0**
Description: maxiFLOW Heat Sink, NO TIM, BLACK-ANODIZED

Heat Sink Type: maxiFLOW
Heat Sink Attachment: THERMAL TAPE
Equivalent Part Number:

**Image above is for illustration purpose only.*

Features & Benefits

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- Designed specifically for ASIC package and their unique cooling requirements
- Also available with thermal interface material (TIM) applied to the base of the heat sink. Contact ATS for TIM options available.

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	2.30 °C/W	1.80 °C/W	1.30 °C/W	1.20 °C/W	1.00 °C/W	0.80 °C/W	0.70 °C/W
	Ducted Flow	1.10	n/a	n/a	n/a	n/a	n/a	n/a

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish
	57.5 mm	57.5 mm	12.5 mm	70.0 mm	NO TIM	BLACK-ANODIZED
<p>Notes:</p> <ul style="list-style-type: none">Dimension A and B refer to heat sink length and widthDimension C is the heat sink height from the bottom of the base to the top of the fin field.Thermal performance data are provided for reference only. Actual performance may vary by application.ATS reserves the right to update or change its products without notice to improve the design or performance.ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant.Contact ATS to learn about custom options available.						

**Image above is for illustration purpose only.*

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.

© 2012 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA



Rev - 121101