Acriche
semiconductor eco lighting

SEOUL SEMICONDUCTOR

AX32X1

AX32X1



Acriche series is designed for AC source operation and high flux output applications.

Acriche is a semi-permanent and environmental friendly semiconductor lighting that can be used in AC without additional device.

Acriche's thermal management perform exceeds other power LED solutions.
It incorporates state of the art SMD design and Thermal emission material.
Acriche is ideal light sources for general illumination Applications.

Features

- Connect directly in AC power
- Power Saving
- Long Life Time
- Simple BOM
- Miniaturization
- Low thermal resistance
- SMT solderbility
- Lead Free product
- RoHS compliant

Applications

- Architectural lighting
- Task lighting
- Decorative / Pathway lighting
- Household appliances

* The appearance and specifications of the product can be changed for improvement without notice.

Part number of AX32X1

1. Part Number form : A X_1 X_2 X_3 X_4 X_5

X_1	Color
W	Pure White
N	Warm White

X_2	Acriche Series
1	-
2	-
3	A3

X_3	LENS Type
2	Dome Type

X_4	Operating Voltage [V]
0	100
1	110
2	220
3	230


X_5	PCB Type
0	-
1	4W PCB

2. Part Number of AX32X0


Part number	Operating voltage	Operating current
AW3200 / AN3200	100V/110V [RMS]	40mA [RMS]
AW3220 / AN3220	220V/230V [RMS]	20mA [RMS]

Outline dimensions

1. AX3201/AX3211



2. AX3221/AX3231



Notes :

[1] All dimensions are in millimeters. (tolerance : ±0.2)
[2] Scale : none
[3] This drawing without tolerances are for reference only
[4] Slug of package isn't connected to anode or cathode
[5] NC pin isn't connected to electrode

Characteristics of Acriche

1. AW3201/AW3211

1-1 Electro-Optical characteristics at 100V/110V Ta=25ºC

Parameter	Symbol	Value			Unit
		Min	Typ	Max	
Luminous Flux [1]	Φ_V [2]	-	195	-	lm
Illuminance [3]	Φ_I	-	220	-	lx
Correlated Color Temperature [4]	CCT	-	6300	-	K
CRI	R_a	-	70	-	-
Operating Current	I_{opt}	-	40	-	mA [RMS]
Power Dissipation	P_D	4			W
Operating Frequency	Freq	50 / 60			Hz
View Angle	2Θ 1/2	110			deg.

1-2 Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Operating Voltage	v_{opt} [5]	115/127	V [RMS]
Power Dissipation	P_D	7.5	W
Junction Temperature	T_j	125	ºC
Operating Temperature	T_{opr}	-30 ~ +85	ºC
Storage Temperature	T_{stg}	-40 ~ +120	ºC
ESD Sensitivity	-	±2,000V HBM	-

*Notes :

[1] Acriche series maintains a tolerance of ±10% on flux and power measurements.

[2] Φ_V is the total luminous flux output as measured with an integrated sphere.

[3] Illuminance is measured at 50cm distance

[4] Correlated Color Temperature is derived from the CIE 1931 Chromaticity diagram. CCT ±5% tester tolerance

[5] 'Operating Voltage' doesn't indicate the maximum voltage which customers use, but it means tolerable voltage according to the voltage variation rate by one's country. It is recommended that the temperature of lead frame should be below 70 ℃.

Characteristics of Acriche

2. AN3201/AN3211 (CRI 70)

2-1 Electro-Optical characteristics at 100V/110V Ta=25ºC

Parameter	Symbol	Value			Unit
		Min	Typ	Max	
Luminous Flux [1]	Φ_V [2]	-	150	-	lm
Illuminance [3]	Φ_I	-	170	-	lx
Correlated Color Temperature [4]	CCT	-	3000	-	K
CRI	R_a	-	70	-	-
Operating Current	I_{opt}	-	40	-	mA [RMS]
Power Dissipation	P_D	4			W
Operating Frequency	Freq	50 / 60			Hz
View Angle	2Θ 1/2	110			deg.

2-2 Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Operating Voltage	v_{opt} [5]	115/127	V [RMS]
Power Dissipation	P_D	7.5	W
Junction Temperature	T_j	125	ºC
Operating Temperature	T_{opr}	-30 ~ +85	ºC
Storage Temperature	T_{stg}	-40 ~ +120	ºC
ESD Sensitivity	-	±2,000V HBM	-

*Notes :

[1] Acriche series maintains a tolerance of ±10% on flux and power measurements.

[2] Φ_V is the total luminous flux output as measured with an integrated sphere.

[3] Illuminance is measured at 50cm distance

[4] Correlated Color Temperature is derived from the CIE 1931 Chromaticity diagram. CCT ±5% tester tolerance

[5] 'Operating Voltage' doesn't indicate the maximum voltage which customers use, but it means tolerable voltage according to the voltage variation rate by one's country. It is recommended that the temperature of lead frame should be below 70 ℃.

Characteristics of Acriche

3. AW3221/AW3231

3-1 Electro-Optical characteristics at 220V/230V Ta=25ºC

Parameter	Symbol	Value			Unit
		Min	Typ	Max	
Luminous Flux [1]	Φ_V [2]	-	195	-	lm
Illuminance [3]	Φ_I	-	220	-	lx
Correlated Color Temperature [4]	CCT	-	6300	-	K
CRI	R_a	-	70	-	-
Operating Current	I_{opt}	-	20	-	mA [RMS]
Power Dissipation	P_D	4			W
Operating Frequency	Freq	50 / 60			Hz
View Angle	2Θ 1/2	110			deg.

3-2 Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Operating Voltage	v_{opt} [5]	253/265	V [RMS]
Power Dissipation	P_D	7.5	W
Junction Temperature	T_j	125	ºC
Operating Temperature	T_{opr}	-30 ~ +85	ºC
Storage Temperature	T_{stg}	-40 ~ +120	ºC
ESD Sensitivity	-	±2,000V HBM	-

*Notes :

[1] Acriche series maintains a tolerance of ±10% on flux and power measurements.

[2] Φ_V is the total luminous flux output as measured with an integrated sphere.

[3] Illuminance is measured at 50cm distance

[4] Correlated Color Temperature is derived from the CIE 1931 Chromaticity diagram. CCT ±5% tester tolerance

[5] 'Operating Voltage' doesn't indicate the maximum voltage which customers use, but it means tolerable voltage according to the voltage variation rate by one's country. It is recommended that the temperature of lead frame should be below 70 ℃.

Characteristics of Acriche

4. AN3221/AN3231 (CRI 70)

4-1 Electro-Optical characteristics at 220V/230V Ta=25ºC

Parameter	Symbol	Value			Unit
		Min	Typ	Max	
Luminous Flux [1]	Φ_V [2]	-	150	-	lm
Illuminance [3]	Φ_I	-	170	-	lx
Correlated Color Temperature [4]	CCT	-	3000	-	K
CRI	R_a	-	70	-	-
Operating Current	I_{opt}	-	20	-	mA [RMS]
Power Dissipation	P_D	4			W
Operating Frequency	Freq	50 / 60			Hz
View Angle	2Θ 1/2	110			deg.

4-2 Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Operating Voltage	v_{opt} [5]	253/265	V [RMS]
Power Dissipation	P_D	7.5	W
Junction Temperature	T_j	125	ºC
Operating Temperature	T_{opr}	-30 ~ +85	ºC
Storage Temperature	T_{stg}	-40 ~ +120	ºC
ESD Sensitivity	-	±2,000V HBM	-

*Notes :

[1] Acriche series maintains a tolerance of ±10% on flux and power measurements.

[2] Φ_V is the total luminous flux output as measured with an integrated sphere.


[3] Illuminance is measured at 50cm distance

[4] Correlated Color Temperature is derived from the CIE 1931 Chromaticity diagram. CCT ±5% tester tolerance


[5] 'Operating Voltage' doesn't indicate the maximum voltage which customers use, but it means tolerable voltage according to the voltage variation rate by one's country. It is recommended that the temperature of lead frame should be below 70 ℃.

Color spectrum

1. Pure white




2. Warm white




Current – Voltage characteristics

1. AX3201




2. AX3211




Current – Voltage characteristics

3. AX3221




4. AX3231




Voltage – Relative flux characteristics

1. AX3201




2. AX3211




Voltage – Relative flux characteristics

3. AX3221




4. AX3231




Relative Flux – Junction temperature characteristics

1. AX32X1




Typical dome type radiation pattern

1. AX32X1



Acriche Binning structure graphical representation

1. AX32X1



*Notes : For more detail Acriche binning, see the Acriche Binning and Labeling document.

Operating instructions of AX32X1


1. Operating temperature



Surface Temperature (Ts)

Parameter	Value	Unit
$R\Theta_{jS}$	6 ~ 7	℃/W
T_j max	125	℃
T_s max	100	℃

2. Thermal modeling



Notes :

[1] Acriche must be used with proper heat management.


[2] It is recommended that the temperature of board should be below 70 ℃.

[3] For more information, refer to Z Power led Thermal Management Guide.
(www.essc.co.kr/_HOMEPAGE/home_kor/product/spec/thermal.pdf)


Operating instructions of AX32X0

3. Heat sink






Specification & Size	T_B(°C)	$R\Theta_{BA}$(°C /W)
Size : 44 x 44 mm S : 7mm T_B : 4mm, D_H : 22.mm F_H : 18mm N : 7ea Footprint: 745mm^2 Power Dissipation:4W	73.8	10



Specification & Size	T_B(°C)	$R\Theta_{BA}$(°C /W)
Size : 50 x 50 mm S : T_B : mm, D_H : 25 mm F_H : mm N : Footprint: 745mm^2 Power Dissipation:4W	56.2	5

PCB type Reel Packaging




Note :

1. The number of loaded products in the reel is 100ea
2. All dimensions are in millimeters (tolerance : ±0.2)
3. Scale none


*The appearance and specifications of the product may be changed for improvement without notice.

Packaging Structure

Aluminum Vinyl Bag



Outer Box



TYPE	SIZE(mm)		
	ⓐ	ⓑ	ⓒ
	350	350	370

Note :

1. 5 reels are loaded in box
2. Scale none
3. For more information about binning and labeling, refer to the Application Note - 1

Precaution for use

[1] Acriche series run on high voltage such as 110 V or 220 V.
[2] Please don't touch the PCB surface, which has built-in terminals and chips, with your hands or metals, while Acriche series is running.
[3] Please don't add or change wires,while Acriche series is running.

Handling of silicone resin for LEDS

[1] Acriche series is encapsulated by silicone resin for the highest flux efficiency.
[2] Notes for handling of Silicone resin Acriche series.
[3] Avoid touching silicone resin parts especially by sharp tools such as Pincette (Tweezers).
[4] Avoid leaving fingerprints on silicone resin parts.
[5] Dust sensitivity silicone resin need containers having cover for storage.
[6] When populating boards in SMT production, there are basically no restrictions regarding the form of the pick and place nozzle, except that mechanical pressure on the surface of the resin must be prevent.
[7] Please do not force over 3000 gf impact or pressure diagonally on the silicon lens. It will cause fatal damage of this product.
[8] Please do not recommend to cover the silicone resin of the Acriche series with other resin (epoxy, urethane, etc).