
AXTAL ADVANCED XTAL PRODUCTS

Specification	AXQCM598-AI	Issue: 01	Date: 2008-04-10


Oscillator type : Quartz Crystal Microbalance Element

Parameter	min.	typ.	max.	Unit	Condition
Nominal frequency		5.983		MHz	
Crystal cut		AT			
Overtone		1			
Adjustment tolerance	-7		+7	kHz	@ 25°C
Frequency stability					
Over operating temperature range	-50		+50	ppm	
Resonance resistance R_r			60	Ω	
Motional capacitance C_1				fF	
Shunt capacitance C_0			7	pF	
Drive level		100		µW	
Operating temperature range	0		+70	°C	
Storage temperature range	-40		+105	°C	
QCM diameter		13.97 ± 0.03		mm	
Blank surface quality		Fine lapped			
Elextrode diameter Side A		13.0 ± 0.1		mm	Fully plated
Electrode material Side A		Al - Cr			
Electrode diameter Side B		6.5 ± 0.2		mm	See drawing
Electrode material Side B		Ag - Cr			

Side A



Side B



AXTAL GmbH & Co. KG
Wasemweg 8
D-74821 Mosbach
Germany

www.axtal.com
fon: +49 (6261) 939834
fax: +49 (6261) 939836
E-mail: info@axtal.com