Zibo Seno Electronic Engineering Co., Ltd.


淄博圣诺

B40C800DM B80C800DM B125C800DM B250C800DM B380C800DM

1.0A SURFACE MOUNT GLASS PASSIVATED BRIDGE RECTIFIER

Features

- Glass Passivated Die Construction
- Low Forward Voltage Drop
- High Current Capability
- High Surge Current Capability
- Designed for Surface Mount Application
- Plastic Material – UL Recognition Flammability Classification 94V-O



DFM		
Dim	**Min**	**Max**
A	6.20	6.50
B	6.80	8.40
C	7.24	8.70
D	0.20	0.38
E	8.12	8.80
G	2.15	3.40
H	1.30	-
J	3.80	4.90
K	0.90	1.40
L	0.45	0.58
M	5.00	5.20
All Dimensions in mm		

Mechanical Data

- Case: DFM , Molded Plastic
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: As Marked on Case
- Weight: 0.38 grams (approx.)
- Mounting Position: Any
- Marking: Type Number
- **Lead Free: For RoHS / Lead Free Version**

Maximum Ratings and Electrical Characteristics @T_A=25°C unless otherwise specified

Single Phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

Characteristic	Symbol	B40 C800DM	B80 C800DM	B125 C800DM	B250 C800DM	B380 C800DM	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	100	200	400	600	1000	V
RMS Reverse Voltage	$V_{R(RMS)}$	40	80	125	250	380	V
Average Rectified Output Current @T_A = 40°C	I_O	1.0					A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	50					A
Forward Voltage per element @I_F = 1.0A	V_{FM}	0.98					V
Peak Reverse Current @T_A = 25°C At Rated DC Blocking Voltage @T_A = 125°C	I_{RM}	2.0 500					μA
Typical Junction Capacitance per element (Note 1)	C_j	25					pF
Typical Thermal Resistance per leg (Note 2)	$R_{\theta JA}$ $R_{\theta JL}$	40 15					°C/W
Operating and Storage Temperature Range	T_j, T_{STG}	-55 to +150					°C

Note: 1. Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.
2. Mounted on PC board with 13mm^2 copper pad.

淄博圣诺

B40C800DM B80C800DM B125C800DM B250C800DM B380C800DM




Fig. 1 Output Current Derating Curve




Fig. 2 Typ Forward Characteristics (per element)




Fig. 3 Max Non-Repetitive Peak Forward Surge Current




Fig. 4 Typ Junction Capacitance (per element)




Fig. 5 Typ Reverse Characteristics (per element)

alldatasheet.com
https://www.alldatasheet.com