

# BA16E38

by Burndy
Catalog ID: BA16E38

Prop 65 Notice

TERMINAL-POLYVINYLCHLORIDE INSULATED, RING , 600 VOLTS MAX. 105° C MAX, 22-16 AWG, 3/8 STUD SIZE

## Product Details

### General

| | |
|---|---|
| Connector Type | Terminal |
| Feature - Barrel Style | Shrouded |
| Insulation | Y |
| Insulation Type | Vinyl |
| Material | Copper |
| Physical Attribute - Number of Holes | 1 |
| Physical Attribute - Tongue Type | Ring |
| Plated | Y |
| Plating Type | Tin |
| Trade Name | VINYLUG™ |
| Type | Ring Tongue |
| UPC | 781810026724 |
| UPC 12 Digit | 7818100267244 |

### Dimensions

| | |
|---|---|
| Dimension - Hole Size fraction | 16/41 |
| Dimension - Hole Size inch | 0.39 in |
| Dimension - Length Overall inch | 1.15 in |
| Dimension - Pad Width inch | 0.53 in |
| Dimension - Stud Size inch | 3/8 |
| Dimension - Z inch | 0.45 in |

### Conductor Related

| | |
|---|---|
| Conductor - Copper Solid Size Range | 20 AWG -22 AWG; 16 AWG -18 AWG |
| Conductor - Copper Str Size Range | 20 AWG -22 AWG; 16 AWG -18 AWG |
| Conductor Type | CU C Str-Size |

### Certifications and Compliance

| | |
|---|---|
| Certification - CSA Approved | Yes |
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |

| | |
|---|---|
| Industry Standard(s) | UL467 |
| Standards - Industry Standards Met | UL467 |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

## Logistics

| | |
|---|---|
| Minimum Pack Quantity | 1000 |

**For further technical assistance, please contact us**

**BURNDY Headquarters**
47 East Industrial Park Drive
Manchester, New Hampshire 03109

**Customer Service Hours:**
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)