

BCX51,BCX52,BCX53■ Electrical Characteristics $T_a = 25^\circ\text{C}$

Parameter	Symbol	Testconditions	Min	Typ	Max	Unit
Collector cutoff current	I _{CBO}	V _{CB} = -30 V, I _E = 0			-100	nA
		V _{CB} = -30 V, I _E = 0; T _j = 125°C			-10	μA
Emitter cutoff current	I _{EBO}	V _{EB} = -5 V, I _C = 0			-100	nA
DC current gain	h _{FE}	I _C = -5 mA; V _{CE} = -2 V	63			
		I _C = -150 mA; V _{CE} = -2 V	63		250	
		I _C = -500 mA; V _{CE} = -2 V	40			
DC current gain BCX51-10,BCX52-10,BCX53-10 BCX51-16,BCX52-16,BCX53-16	h _{FE}	I _C = -150 mA; V _{CE} = -2 V	63		160	
		I _C = -150 mA; V _{CE} = -2 V	100		250	
Collector-emitter saturation voltage	V _{CE(sat)}	I _C = -500 mA; I _B = -50 mA			-500	mV
Base to emitter voltage	V _{BE}	I _C = -500 mA; V _{CE} = -2 V			-1	V
Transition frequency	f _T	I _C = -10 mA; V _{CE} = -5 V; f = 100 MHz		50		MHz

■ h_{FE} Classification

TYPE	BCX51	BCX51-10	BCX51-16
Marking	AA	AC	AD

TYPE	BCX52	BCX52-10	BCX52-16
Marking	AE	AG	AM

TYPE	BCX53	BCX53-10	BCX53-16
Marking	AH	AK	AL