

# BD135G, BD137G, BD139G

## Plastic Medium-Power Silicon NPN Transistors

This series of plastic, medium-power silicon NPN transistors are designed for use as audio amplifiers and drivers utilizing complementary or quasi complementary circuits.

### Features

- High DC Current Gain
- BD 135, 137, 139 are complementary with BD 136, 138, 140
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant\*

### MAXIMUM RATINGS

| Rating                                                                                    | Symbol         | Value           | Unit                          |
|-------------------------------------------------------------------------------------------|----------------|-----------------|-------------------------------|
| Collector-Emitter Voltage<br>BD135G<br>BD137G<br>BD139G                                   | $V_{CEO}$      | 45<br>60<br>80  | Vdc                           |
| Collector-Base Voltage<br>BD135G<br>BD137G<br>BD139G                                      | $V_{CBO}$      | 45<br>60<br>100 | Vdc                           |
| Emitter-Base Voltage                                                                      | $V_{EBO}$      | 5.0             | Vdc                           |
| Collector Current                                                                         | $I_C$          | 1.5             | Adc                           |
| Base Current                                                                              | $I_B$          | 0.5             | Adc                           |
| Total Device Dissipation<br>@ $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 1.25<br>10      | Watts<br>mW/ $^\circ\text{C}$ |
| Total Device Dissipation<br>@ $T_C = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 12.5<br>100     | Watts<br>mW/ $^\circ\text{C}$ |
| Operating and Storage Junction Temperature Range                                          | $T_J, T_{stg}$ | -55 to +150     | $^\circ\text{C}$              |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

### THERMAL CHARACTERISTICS

| Characteristic                          | Symbol          | Max | Unit               |
|-----------------------------------------|-----------------|-----|--------------------|
| Thermal Resistance, Junction-to-Case    | $R_{\theta JC}$ | 10  | $^\circ\text{C/W}$ |
| Thermal Resistance, Junction-to-Ambient | $R_{\theta JA}$ | 100 | $^\circ\text{C/W}$ |



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.



**ON Semiconductor®**


<http://onsemi.com>

## 1.5 A POWER TRANSISTORS NPN SILICON 45, 60, 80 V, 12.5 W



TO-225  
CASE 77-09  
STYLE 1

### MARKING DIAGRAM



Y = Year  
WW = Work Week  
BD1xx = Device Code  
xx = 35, 37, 39  
G = Pb-Free Package

### ORDERING INFORMATION

| Device  | Package             | Shipping        |
|---------|---------------------|-----------------|
| BD135G  | TO-225<br>(Pb-Free) | 500 Units / Box |
| BD135TG | TO-225<br>(Pb-Free) | 50 Units / Rail |
| BD137G  | TO-225<br>(Pb-Free) | 500 Units / Box |
| BD139G  | TO-225<br>(Pb-Free) | 500 Units / Box |

# BD135G, BD137G, BD139G

## ELECTRICAL CHARACTERISTICS ( $T_C = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic                                                                                                                                                                 | Symbol          | Min            | Max           | Unit            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|----------------|---------------|-----------------|
| Collector-Emitter Sustaining Voltage*<br>( $I_C = 0.03\text{ A}$ , $I_B = 0$ )<br>BD135G<br>BD137G<br>BD139G                                                                   | $BV_{CEO}^*$    | 45<br>60<br>80 | —<br>—<br>—   | Vdc             |
| Collector Cutoff Current<br>( $V_{CB} = 30\text{ Vdc}$ , $I_E = 0$ )<br>( $V_{CB} = 30\text{ Vdc}$ , $I_E = 0$ , $T_C = 125^\circ\text{C}$ )                                   | $I_{CBO}$       | —<br>—         | 0.1<br>10     | $\mu\text{Adc}$ |
| Emitter Cutoff Current<br>( $V_{BE} = 5.0\text{ Vdc}$ , $I_C = 0$ )                                                                                                            | $I_{EBO}$       | —              | 10            | $\mu\text{Adc}$ |
| DC Current Gain<br>( $I_C = 0.005\text{ A}$ , $V_{CE} = 2\text{ V}$ )<br>( $I_C = 0.15\text{ A}$ , $V_{CE} = 2\text{ V}$ )<br>( $I_C = 0.5\text{ A}$ , $V_{CE} = 2\text{ V}$ ) | $h_{FE}^*$      | 25<br>40<br>25 | —<br>250<br>— | —               |
| Collector-Emitter Saturation Voltage*<br>( $I_C = 0.5\text{ A}$ , $I_B = 0.05\text{ A}$ )                                                                                      | $V_{CE(sat)}^*$ | —              | 0.5           | Vdc             |
| Base-Emitter On Voltage*<br>( $I_C = 0.5\text{ A}$ , $V_{CE} = 2.0\text{ Vdc}$ )                                                                                               | $V_{BE(on)}^*$  | —              | 1             | Vdc             |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

\*Pulse Test: Pulse Width  $\leq 300\text{ }\mu\text{s}$ , Duty Cycle  $\leq 2.0\%$ .

## TYPICAL CHARACTERISTICS




Figure 1. DC Current Gain




Figure 2. Collector-Emitter Saturation Voltage

# BD135G, BD137G, BD139G

## TYPICAL CHARACTERISTICS




Figure 3. Base-Emitter Saturation Voltage




Figure 4. Base-Emitter On Voltage




Figure 5. Capacitance




Figure 6. Active-Region Safe Operating Area





Figure 7. Power Derating

# MECHANICAL CASE OUTLINE PACKAGE DIMENSIONS


ON Semiconductor®

ON



TO-225  
CASE 77-09  
ISSUE AD

DATE 25 MAR 2015




## NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. NUMBER AND SHAPE OF LUGS OPTIONAL.

| MILLIMETERS |       |       |
|-------------|-------|-------|
| DIM         | MIN   | MAX   |
| A           | 2.40  | 3.00  |
| A1          | 1.00  | 1.50  |
| b           | 0.60  | 0.90  |
| b2          | 0.51  | 0.88  |
| c           | 0.39  | 0.63  |
| D           | 10.60 | 11.10 |
| E           | 7.40  | 7.80  |
| e           | 2.04  | 2.54  |
| L           | 14.50 | 16.63 |
| L1          | 1.27  | 2.54  |
| P           | 2.90  | 3.30  |
| Q           | 3.80  | 4.20  |

## GENERIC MARKING DIAGRAM\*



Y = Year  
WW = Work Week  
XXXXX = Device Code  
G = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present.

|                                                           |                                                       |                                                           |                                                         |                                                       |
|-----------------------------------------------------------|-------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------|-------------------------------------------------------|
| STYLE 1:<br>PIN 1. EMITTER<br>2., 4. COLLECTOR<br>3. BASE | STYLE 2:<br>PIN 1. CATHODE<br>2., 4. ANODE<br>3. GATE | STYLE 3:<br>PIN 1. BASE<br>2., 4. COLLECTOR<br>3. EMITTER | STYLE 4:<br>PIN 1. ANODE 1<br>2., 4. ANODE 2<br>3. GATE | STYLE 5:<br>PIN 1. MT 1<br>2., 4. MT 2<br>3. GATE     |
| STYLE 6:<br>PIN 1. CATHODE<br>2., 4. GATE<br>3. ANODE     | STYLE 7:<br>PIN 1. MT 1<br>2., 4. GATE<br>3. MT 2     | STYLE 8:<br>PIN 1. SOURCE<br>2., 4. GATE<br>3. DRAIN      | STYLE 9:<br>PIN 1. GATE<br>2., 4. DRAIN<br>3. SOURCE    | STYLE 10:<br>PIN 1. SOURCE<br>2., 4. DRAIN<br>3. GATE |

|                  |             |                                                                                                                                                                                     |
|------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98ASB42049B | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | TO-225      | PAGE 1 OF 1                                                                                                                                                                         |

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Email Requests to: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

### TECHNICAL SUPPORT

#### North American Technical Support:

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

#### Europe, Middle East and Africa Technical Support:

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative