Frontier Electronics Corp.


667 E. COCHRAN STREET, SIMI VALLEY, CA 93065
TEL: (805) 522-9998 FAX: (805) 522-9989
E-mail: frontiersales@frontierusa.com
Web: http://www.frontierusa.com

2A BRIDGE RECTIFIER

BJ2-005 THRU BJ2-10

FEATURES

- PLASTIC MATERIAL USED CARRIES UNDERWRITERS LABORATORY FLAMMABILITY CLASSIFICATION 94V-0
- TYPICAL IR LESS THAN 1μA
- GLASS PASSIVATED CHIP JUNCTION
- IDEAL FOR PRINTED CIRCUIT BOARD
- HIGH TEMPERATURE SOLDERING GUARANTEED: 260°C/10S (9.5mm) LEAD LENGTH / 5LBS., (2.3KG) TENSION
- SURGE OVERLOAD RATING: 50A PEAK



MECHANICAL DATA

- CASE: VOID FREE PLASTIC PACKAGE
  DIMENSIONS IN INCHES AND (MILLIMETERS)
- TERMINALS: AXIAL LEADS, SOLDERABLE PER MIL-STD-202 METHOD 208
- MOUNTING POSITION: ANY
- WEIGHT: 3.6 GRAMS

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS RATINGS AT 25°C AMBIENT TEMPERATURE UNLESS OTHERWISE SPECIFIED SINGLE PHASE, HALF WAVE, 60 HZ, RESISTIVE OR INDUCTIVE LOAD. FOR CAPACITIVE LOAD, DERATE CURRENT BY 20%

RATINGS	SYMBOL	BJ2-005	BJ2-01	BJ2-02	BJ2-04	BJ2-06	BJ2-08	BJ2-10	UNITS
MAXIMUM RECURRENT PEAK REVERSE VOLTAGE	V_{RRM}	50	100	200	400	600	800	1000	V
MAXIMUM RMS VOLTAGE	V_{RMS}	35	70	140	280	420	560	700	V
MAXIMUM DC BLOCKING VOLTAGE	V_{DC}	50	100	200	400	600	800	1000	V
MAXIMUM AVERAGE FORWARD RECTIFIED OUTPUT CURRENT AT 40°C TA	I_O	2.0							A
PEAK FORWARD SURGE CURRENT, 8.3ms SINGLE HALF SINE-WAVE SUPERIMPOSED ON RATED LOAD	I_{FSM}	120							A
STORAGE TEMPERATURE RANGE	T_{STG}	- 55 TO + 150							℃
OPERATING TEMPERATURE RANGE	T_{OP}	- 55 TO + 150							℃

ELECTRICAL CHARACTERISTICS (A_T T_A =25°C UNLESS OTHERWISE NOTED)

CHARACTERISTICS	SYMBOL	BJ2-005	BJ2-01	BJ2-02	BJ2-04	BJ2-06	BJ2-08	BJ2-10	UNITS
MAXIMUM FORWARD VOLTAGE DROP PER BRIDGE ELEMENT AT 1.0A PEAK	V_F	0.95							V
MAXIMUM REVERSE CURRENT AT RATED DC BLOCKING VOLTAGE PER ELEMENT	I_R	10							μA

RATINGS AND CHARACTERISTIC CURVES BJ2-005 THRU BJ2-10

FIG. 1 - DERATING CURVE FOR
OUTPUT RECTIFIED CURRENT




FIG. 2 - DERATING CURVE FOR
OUTPUT RECTIFIED CURRENT




FIG. 3 - TYPICAL FORWARD
CHARACTERISTICS




FIG. 4 - MAXIMUM FORWARD SURGE CURRENT

