百流光电
BetLux Electronics

LED LAMP CLUSTER

BL-CS21AR2G4

Features:

- 21mm Square LED lamp cluster
- High visibility
- Emitting Color: red,green,blue
- No of Built-in 5mm LED Lamps :
- Ultra orange - 2pcs,green – 4pcs
- Waterproof Package With Hood Suitable
- For Outdoor and Indoor Information Boards

RoHs Compliance

■ Selection Guide

Part No.	Description
BL-CS21AR2G4	21mm square Lamp cluster .2red ,4 green, square packed

■ Description:

• Color Code & Chip characteristics: (Test Condition: IF=20mA)

Part No.	Built-in Lamp Package	Built-in Lamp Part No. BL-	Chip		Lens Appearance	Electro-optical Data(At 20mA)			Viewing Angle 2θ1/2 (deg)
			Material/ Emitted Color	Peak Wave Length λp (nm)		Vf (V)		Iv (mcd)	
						Typ	Max	Typ	
BL-CS21AR2G4	4x5x7mm 1.0" Lead Oval	L563UEC	AlGaInP/ Ultra Orange	630	Water clear	2.10	2.50	750	X-X 45 Y-Y 25
		L563UGC	AlGaInP/ Ultra Green	574	Water clear	2.20	2.50	600	

Notes:

1. θ 1/2 Is the angle from optical centerline where the luminous intensity is1/2 the optical centerline value.

■ Absolute Maximum Rating (Each Lamp,Ta=25℃ Derate above 25℃)

Characteristic	Symbol	Ultra Orang	Ultra Green		Unit
Spectral Line Half width	△λ	17	30		nm
Pulse Forward Current	IFp	150	150		mA
DC Forward Current	IF	30	30		mA
Reverse Voltage	V_R	5	5		V
Power Dissipature	PD	65	75		mW
Operating Temperature	Topr	-40℃-80℃			
Storage Temperature	Tstg	-40℃-85℃			
Lead Soldering Temperature		Max.260±5℃ for 3 sec Max. (1.6mm from the base of the epoxy bulb)			

www.betlux.com

LED LAMP CLUSTER

BL-CS21AR2G4

■ Package configuration & Internal circuit diagram:



www.bet

Notes:

- All dimensions are in millimeters (inches)
- Tolerance is ±0.25(0.01")unless otherwise noted.
- Specifications are subject to change without notice.

LED LAMP CLUSTER

BL-CS21AR2G4

Typical electrical-optical characteristics curves:



RELATIVE INTENSITY Vs WAVELENGTH(λ p)

(1) - GaAsP/GaAs 655nm/Red
(2) - GaP 570nm/Yellow Green
(3) - GaAsP/GaP 585nm/Yellow
(4) - GaAsp/GaP 635nm/Orange & Hi-Eff Red
(5) - GaP 700nm/Bright Red
(6) - GaAlAs/GaAs 660nm/Super Red
(8) - GaAsP/GaP 610nm/Super Red
(9) - GaAlAs 880nm
(10) - GaAs/GaAs & GaAlAs/GaAs 940nm
(A) - GaN/SiC 430nm/Blue
(B) - InGaN/SiC 470nm/Blue
(C) - InGaN/SiC 505nm/Ultra Green
(D) - InGaAl/SiC 525nm/Ultra Green



FORWARD VOLTAGE (Vf)
FORWARD CURRENT VS.
FORWARD VOLTAGE



FORWARD CURRENT (mA)
RELATIVE LUMINOUS
INTENSITY VS. FORWARD
CURRENT



AMBIENT TEMPERATURE Ta(℃)
FORWARD CURRENT VS. AMBIENT
TEMPERATURE

www.betlux.com



AMBIENT TEMPERATURE Ta(℃)



tp-PULSE DURATION uS
(1,2,3,4,6,8,B.D.J.K)



tp-PULSE DURATION uS
(5)

NOTE:25℃ free air temperature unless otherwise specified