END- LOOK PACKAGE PIN PHOTO DIODE

Features

1. Wide receiving angle
2. Linear response vs. irradiance
3. Fast switching time
4. End-looking Package ideal for space limited applications
5. Lens Appearance: Water Clear.
6. This product doesn't contain restriction substance, comply ROHS standard

Description

The BPD-BQB334 device consists of a PIN silicon photodiode molded in a clear epoxy package which allows spectral response from visible to infrared light wavelengths. The wide receiving angle provides relatively even reception over a large area. The end-looking package is designed for easy PC board mounting. This photodiode is mechanically and spectrally matched to BRIGHT's GaAs and GaAlAs series of infrared emitting diodes.

●Package Dimensions:



NOTES:
1.All dimensions are in millimeters (inches).
2.Tolerance is ±0.25mm (0.01") unless otherwise specified.
3.Lead spacing is measured where the leads emerge from the package
4. Specifications are subject to change without notice

Absolute Maximum Ratings(Ta=25℃)

Parameter	Maximum Rating	Unit
Power Dissipation	100	mW
Reverse Breakdown Voltage	60V	
Operating Temperature	-45℃~+85℃	
Storage Temperature Range	-45℃~+100℃	
Lead Soldering Temperature	260℃ for 5 seconds	

Electrical Characteristics (TA=25℃ unless otherwise noted)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	TEST CONDITIONS
Reverse Light Current	I_L	-	50	-	μA	V_R=5V.Ee=1mW/cm^2
Reverse Dark Current	I_D	-	-	30	nA	V_R=10V.Ee=0 mW/cm^2
Reverse Break down Voltage	$V_{(BR)}$	30	-	-	V	I_R=100μA
Forward Voltage	V_F	-	-	1.2	V	I_F=1mA
Total Capacitance	C_T	-	21	-	PF	V_R=4V.Ee=0,f=1.0MHZ
Rise Time/ Fall Time	tr/tf	-	40	-	ns	V_R=20V,λ=850nm.RL=50Ω

Typical Optical-Electrical Characteristic Curves

Relative Response vs. Wavelength



Coupling Characteristics



Normalized Light Current vs Reverse Voltage



Total Capacitance vs Reverse Voltage



Normalized Light and Dark Current vs Ambient Temperture



Light Current vs. Irradiance



Switching Time Test Circuit



Light Current vs. Angular Displacement



● Tapping and packaging specifications(Units: mm)



● Packaging Bag Dimensions



Notes:

1、500pcs per bag,5Kpcs per box.

2、All dimensions are in millimeters(inches).

3、Specifications are subject to change without notice.