BSR802N

OptiMOS™2 Small-Signal-Transistor


Features


- N-channel
- Enhancement mode
- Ultra Logic level (1.8V rated)
- Avalanche rated
- Footprint compatible to SOT23
- Qualified according to AEC Q101
- 100% lead-free; RoHS compliant

Product Summary

V_{DS}		20	V
$R_{DS(on),max}$	V_{GS}=2.5 V	23	mΩ
	V_{GS}=1.8 V	32	
I_D		3.7	A

PG-SC59





Type	Package	Tape and Reel Information	Marking	Lead Free	Packing
BSR802N	PG-SC59	L6327 = 3000 pcs. / reel	LFs	Yes	Non dry

Maximum ratings, at T_j=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	T_A=25 °C	3.7	A
		T_A=25 °C	2.9	
Pulsed drain current	$I_{D,pulse}$	T_A=70 °C	14.8	
Avalanche energy, single pulse	E_{AS}	I_D=3.8 A, R_{GS}=25 Ω	30	mJ
Reverse diode dv/dt	dv/dt	I_D=3.8 A, V_{DS}=16 V, di/dt=200 A/µs, $T_{j,max}$=150 °C	6	kV/µs
Gate source voltage	V_{GS}		±8	V
Power dissipation [1)]	P_{tot}	T_A=25 °C	0.5	W
Operating and storage temperature	T_j, T_{stg}		-55 ... 150	°C
ESD Class		JESD22-A114-HBM	0 (<250V)	
Soldering Temperature			260 °C	
IEC climatic category; DIN IEC 68-1			55/150/56	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal characteristics						
Thermal resistance, junction - ambient	R_{thJA}	minimal footprint [1]	-	-	250	K/W
Electrical characteristics, at T_j=25 °C, unless otherwise specified						
Static characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS}= 0 V, I_D= 250 µA	20	-	-	V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS} , I_D=30 µA	0.3	0.55	0.75	
Drain-source leakage current	I_{DSS}	V_{DS}=20 V, V_{GS}=0 V, T_j=25 °C	-	-	1	µA
		V_{DS}=20 V, V_{GS}=0 V, T_j=150 °C	-	-	100	
Gate-source leakage current	I_{GSS}	V_{GS}=8 V, V_{DS}=0 V	-	-	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=1.8 V, I_D=3.2 A	-	22	32	mΩ
		V_{GS}=2.5 V, I_D=3.7 A	-	17	23	
Transconductance	g_{fs}	$\|V_{DS}\|>2\|I_D\|R_{DS(on)max}$, I_D=2.9 A		16	-	S

[1] Performed on 40mm^2 FR4 PCB. The traces are 1mm wide, 70µm thick and 20mm long; they are present on both sides of the PCB.

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic characteristics						
Input capacitance	C_{iss}	V_{GS}=0 V, V_{DS}=10 V, f=1 MHz	-	1013	1447	pF
Output capacitance	C_{oss}		-	290	414	
Reverse transfer capacitance	C_{rss}		-	51	73.0	
Turn-on delay time	$t_{d(on)}$	V_{DD}=10 V, V_{GS}=2.5 V, I_D=3.7 A, R_G=6 Ω	-	9.8	-	ns
Rise time	t_r		-	18	-	
Turn-off delay time	$t_{d(off)}$		-	26	-	
Fall time	t_f		-	4.1	-	
Gate Charge Characteristics						
Gate to source charge	Q_{gs}	V_{DD}=10 V, I_D=3.7 A, V_{GS}=0 to 2.5 V	-	1.4	-	nC
Gate to drain charge	Q_{gd}		-	1.5	-	
Gate charge total	Q_g		-	4.7	-	
Gate plateau voltage	$V_{plateau}$		-	1.4	-	V
Reverse Diode						
Diode continous forward current	I_S	T_A=25 °C	-	-	0.5	A
Diode pulse current	$I_{S,pulse}$		-	-	15	
Diode forward voltage	V_{SD}	V_{GS}=0 V, I_F=3.7 A, T_j=25 °C	-	0.78	1.1	V
Reverse recovery time	t_{rr}	V_R=10 V, I_F=3.7 A, di_F/dt=100 A/µs	-	15		ns
Reverse recovery charge	Q_{rr}		-	5.2	-	nC