

isc N-Channel MOSFET Transistor

BUK455-50A/B

DESCRIPTION

- Drain Source Voltage
: $V_{DS} = 50V(\text{Min})$
- Low $R_{DS(ON)}$
- Fast Switching Speed
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- Designed for Switched Mode Power Supplies (SMPS), motor control, welding, and in general purpose switching resistance applications

ABSOLUTE MAXIMUM RATINGS($T_a = 25^\circ\text{C}$)

SYMBOL	ARAMETER	VALUE	UNIT
V_{DS}	Drain-Source Voltage ($V_{GS}=0$)	50	V
V_{GS}	Gate-Source Voltage	± 30	V
I_D	Drain Current-continuous@ $TC=25^\circ\text{C}$	BUK455-50A	A
		BUK455-50B	
P_{tot}	Total Dissipation@ $TC=25^\circ\text{C}$	125	W
T_j	Max. Operating Junction Temperature	175	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-55-175	$^\circ\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.2	$^\circ\text{C/W}$



isc N-Channel Mosfet Transistor

BUK455-50A/B

ELECTRICAL CHARACTERISTICS (T_c=25°C)

SYMBOL	PARAMETER	CONDITIONS		MIN	MAX	UNIT
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0; I _D = 0.25mA		50	--	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} ; I _D = 1.0mA		2.1	4.0	V
R _{DS(on)}	Drain-Source On-stage Resistance	V _{GS} = 10V; I _D = 20A	BUK455-50A	--	38	mΩ
			BUK455-50B	--	45	mΩ
I _{GSS}	Gate Source Leakage Current	V _{GS} = ±30V; V _{DS} = 0		--	±100	nA
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 50V; V _{GS} = 0		--	10	μA
V _{SD}	Forward On-Voltage	I _S = 41A; V _{GS} = 0		--	2	V

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.