
DATA SHEET



BZV55 series
Voltage regulator diodes

Product specification
Supersedes data of 1999 May 21

2002 Feb 28

Philips
Semiconductors

PHILIPS

Voltage regulator diodes BZV55 series

FEATURES


- Total power dissipation: max. 500 mW
- Two tolerance series: ±2%, and approx. ±5%
- Working voltage range: nom. 2.4 to 75 V (E24 range)
- Non-repetitive peak reverse power dissipation: max. 40 W.

APPLICATIONS

- Low voltage stabilizers or voltage references.

DESCRIPTION

Low-power voltage regulator diodes in small hermetically sealed glass SOD80C SMD packages. The diodes are available in the normalized E24 ±2% (BZV55-B) and approx. ±5% (BZV55-C) tolerance range. The series consists of 37 types with nominal working voltages from 2.4 to 75 V.



The cathode is indicated by a yellow band.

Fig.1 Simplified outline (SOD80C) and symbol.

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 60134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
I_F	continuous forward current		–	250	mA
I_{ZSM}	non-repetitive peak reverse current	t_p = 100 µs; square wave; T_j = 25 °C prior to surge	see Tables 1 and 2		A
P_{tot}	total power dissipation	$T_{amb} \leq$ 50 °C; note 1	–	400	mW
		tie-point ≤ 50 °C; note 1	–	500	mW
P_{ZSM}	non-repetitive peak reverse power dissipation	t_p = 100 µs; square wave; T_j = 25 °C prior to surge; see Fig.3	–	40	W
T_{stg}	storage temperature		–65	+200	°C
T_j	junction temperature		–65	+200	°C

Note

1. Device mounted on a ceramic substrate of 10 × 10 × 0.6 mm.

ELECTRICAL CHARACTERISTICS

Total BZV55-B and BZV55-C series

T_j = 25 °C; unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MAX.	UNIT
V_F	forward voltage	I_F = 10 mA; see Fig.4	0.9	V
I_R	reverse current			
	BZV55-B/C2V4	V_R = 1 V	50	µA
	BZV55-B/C2V7	V_R = 1 V	20	µA
	BZV55-B/C3V0	V_R = 1 V	10	µA
	BZV55-B/C3V3	V_R = 1 V	5	µA
	BZV55-B/C3V6	V_R = 1 V	5	µA
	BZV55-B/C3V9	V_R = 1 V	3	µA
	BZV55-B/C4V3	V_R = 1 V	3	µA
	BZV55-B/C4V7	V_R = 2 V	3	µA
	BZV55-B/C5V1	V_R = 2 V	2	µA
	BZV55-B/C5V6	V_R = 2 V	1	µA
	BZV55-B/C6V2	V_R = 4 V	3	µA
	BZV55-B/C6V8	V_R = 4 V	2	µA
	BZV55-B/C7V5	V_R = 5 V	1	µA
	BZV55-B/C8V2	V_R = 5 V	700	nA
	BZV55-B/C9V1	V_R = 6 V	500	nA
	BZV55-B/C10	V_R = 7 V	200	nA
	BZV55-B/C11	V_R = 8 V	100	nA
	BZV55-B/C12	V_R = 8 V	100	nA
	BZV55-B/C13	V_R = 8 V	100	nA
	BZV55-B/C15 to BZV55-B/C75	$V_R = 0.7V_{Znom}$	50	nA

Table 1 Per type, BZV55-**B/C2V4** to BZV55-**B/C24**

T_j = 25 °C unless otherwise specified.

BZV55-Bxxx Cxxx	WORKING VOLTAGE V_Z (V) at I_{Ztest} = 5 mA				DIFFERENTIAL RESISTANCE r_{dif} (Ω)				TEMP. COEFF. S_Z (mV/K) at I_{Ztest} = 5 mA (see Figs 5 and 6)			DIODE CAP. C_d (pF) at f = 1 MHz; V_R = 0 V	NON-REPETITIVE PEAK REVERSE CURRENT I_{ZSM} (A) at t_p = 100 μs; T_{amb} = 25 °C
	Tol. ±2% (B)		Tol. approx. ±5% (C)		at I_{Ztest} = 1 mA		at I_{Ztest} = 5 mA						
	MIN.	MAX.	MIN.	MAX.	TYP.	MAX.	TYP.	MAX.	MIN.	TYP.	MAX.	MAX.	MAX.
2V4	2.35	2.45	2.2	2.6	275	600	70	100	–3.5	–1.6	0	450	6.0
2V7	2.65	2.75	2.5	2.9	300	600	75	100	–3.5	–2.0	0	450	6.0
3V0	2.94	3.06	2.8	3.2	325	600	80	95	–3.5	–2.1	0	450	6.0
3V3	3.23	3.37	3.1	3.5	350	600	85	95	–3.5	–2.4	0	450	6.0
3V6	3.53	3.67	3.4	3.8	375	600	85	90	–3.5	–2.4	0	450	6.0
3V9	3.82	3.98	3.7	4.1	400	600	85	90	–3.5	–2.5	0	450	6.0
4V3	4.21	4.39	4.0	4.6	410	600	80	90	–3.5	–2.5	0	450	6.0
4V7	4.61	4.79	4.4	5.0	425	500	50	80	–3.5	–1.4	0.2	300	6.0
5V1	5.00	5.20	4.8	5.4	400	480	40	60	–2.7	–0.8	1.2	300	6.0
5V6	5.49	5.71	5.2	6.0	80	400	15	40	–2.0	1.2	2.5	300	6.0
6V2	6.08	6.32	5.8	6.6	40	150	6	10	0.4	2.3	3.7	200	6.0
6V8	6.66	6.94	6.4	7.2	30	80	6	15	1.2	3.0	4.5	200	6.0
7V5	7.35	7.65	7.0	7.9	30	80	6	15	2.5	4.0	5.3	150	4.0
8V2	8.04	8.36	7.7	8.7	40	80	6	15	3.2	4.6	6.2	150	4.0
9V1	8.92	9.28	8.5	9.6	40	100	6	15	3.8	5.5	7.0	150	3.0
10	9.80	10.20	9.4	10.6	50	150	8	20	4.5	6.4	8.0	90	3.0
11	10.80	11.20	10.4	11.6	50	150	10	20	5.4	7.4	9.0	85	2.5
12	11.80	12.20	11.4	12.7	50	150	10	25	6.0	8.4	10.0	85	2.5
13	12.70	13.30	12.4	14.1	50	170	10	30	7.0	9.4	11.0	80	2.5
15	14.70	15.30	13.8	15.6	50	200	10	30	9.2	11.4	13.0	75	2.0
16	15.70	16.30	15.3	17.1	50	200	10	40	10.4	12.4	14.0	75	1.5
18	17.60	18.40	16.8	19.1	50	225	10	45	12.4	14.4	16.0	70	1.5
20	19.60	20.40	18.8	21.2	60	225	15	55	12.3	15.6	18.0	60	1.5
22	21.60	22.40	20.8	23.3	60	250	20	55	14.1	17.6	20.0	60	1.25
24	23.50	24.50	22.8	25.6	60	250	25	70	15.9	19.6	22.0	55	1.25

Table 2 Per type, BZV55-**B/C27** to BZV55-**B/C75**

T_j = 25 °C unless otherwise specified.

BZV55-Bxxx Cxxx	WORKING VOLTAGE V_Z (V) at I_{Ztest} = 2 mA				DIFFERENTIAL RESISTANCE r_{dif} (Ω)				TEMP. COEFF. S_Z (mV/K) at I_{Ztest} = 2 mA (see Figs 5 and 6)			DIODE CAP. C_d (pF) at f = 1 MHz; V_R = 0 V	NON-REPETITIVE PEAK REVERSE CURRENT I_{ZSM} (A) at t_p = 100 μs; T_{amb} = 25 °C
	Tol. ±2% (B)		Tol. approx. ±5% (C)		at I_{Ztest} = 0.5 mA		at I_{Ztest} = 2 mA						
	MIN.	MAX.	MIN.	MAX.	TYP.	MAX.	TYP.	MAX.	MIN.	TYP.	MAX.	MAX.	MAX.
27	26.50	27.50	25.1	28.9	65	300	25	80	18.0	22.7	25.3	50	1.0
30	29.40	30.60	28.0	32.0	70	300	30	80	20.6	25.7	29.4	50	1.0
33	32.30	33.70	31.0	35.0	75	325	35	80	23.3	28.7	33.4	45	0.9
36	35.30	36.70	34.0	38.0	80	350	35	90	26.0	31.8	37.4	45	0.8
39	38.20	39.80	37.0	41.0	80	350	40	130	28.7	34.8	41.2	45	0.7
43	42.10	43.90	40.0	46.0	85	375	45	150	31.4	38.8	46.6	40	0.6
47	46.10	47.90	44.0	50.0	85	375	50	170	35.0	42.9	51.8	40	0.5
51	50.00	52.00	48.0	54.0	90	400	60	180	38.6	46.9	57.2	40	0.4
56	54.90	57.10	52.0	60.0	100	425	70	200	42.2	52.0	63.8	40	0.3
62	60.80	63.20	58.0	66.0	120	450	80	215	58.8	64.4	71.6	35	0.3
68	66.60	69.40	64.0	72.0	150	475	90	240	65.6	71.7	79.8	35	0.25
75	73.50	76.50	70.0	79.0	170	500	95	255	73.4	80.2	88.6	35	0.2

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th\ j\text{-}tp}$	thermal resistance from junction to tie-point		300	K/W
$R_{th\ j\text{-}a}$	thermal resistance from junction to ambient	see Fig.2 and note 1	380	K/W

Note

1. Device mounted on a ceramic substrate of $10 \times 10 \times 0.6$ mm.

GRAPHICAL DATA






Fig.2 Thermal resistance from junction to ambient as a function of pulse duration.




(1) T_j = 25 °C (prior to surge).
(2) T_j = 150 °C (prior to surge).

Fig.3 Maximum permissible non-repetitive peak reverse power dissipation versus duration.




T_j = 25 °C.

Fig.4 Typical forward current as a function of forward voltage.



BZV55-B/C2V4 to BZV55-B/C4V3.
T_j = 25 to 150 °C.

Fig.5 Temperature coefficient as a function of working current; typical values.




BZV55-B/C4V7 to BZV55-B/C12.
T_j = 25 to 150 °C.

Fig.6 Temperature coefficient as a function of working current; typical values.


PACKAGE OUTLINE

Hermetically sealed glass surface mounted package; 2 connectors **SOD80C**



DIMENSIONS (mm are the original dimensions)

UNIT	D	H	L
mm	1.60 1.45	3.7 3.3	0.3



Note

1. The marking band indicates the cathode.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	EIAJ			
SOD80C	100H01					97-06-20

DATA SHEET STATUS

DATA SHEET STATUS[1]	PRODUCT STATUS[2]	DEFINITIONS
Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.
Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.
Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Changes will be communicated according to the Customer Product/Process Change Notification (CPCN) procedure SNW-SQ-650A.

Notes

1. Please consult the most recently issued data sheet before initiating or completing a design.
2. The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL http://www.semiconductors.philips.com.

DEFINITIONS

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

DISCLAIMERS

Life support applications — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes, without notice, in the products, including circuits, standard cells, and/or software, described or contained herein in order to improve design and/or performance. Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no licence or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

NOTES

NOTES

Philips Semiconductors – a worldwide company

Contact information

For additional information please visit **http://www.semiconductors.philips.com**. Fax: **+31 40 27 24825**
For sales offices addresses send e-mail to: **sales.addresses@www.semiconductors.philips.com**.

© Koninklijke Philips Electronics N.V. 2002 SCA74

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands 613514/03/pp12 Date of release: 2002 Feb 28 Document order number: 9397 750 09386

Let's make things better.

Philips
Semiconductors

PHILIPS