


C-13-DFB2.5-XX-SXXXX/XXX-X-XX



Features

- Un-cooled laser diode with MQW structure
- High temperature operation without active cooling
- Hermetically sealed active component
- Built-in InGaAs monitor photodiode
- Complies with Telcordia Technologies GR-468-CORE
- Single frequency operation with high SMSR

Packaging

- TOSA
- FC/ST/SC receptacle package with 2-hole flange
- Fiber pigtailed with optional FC/ST/SC/MU/LC connector

Application

- Design for 2.5Gbps high speed optics networks
- RoHS Compliant available

Absolute Maximum Ratings (Tc=25°C)

Parameter	Symbol	Rating	Unit
Fiber Output Power L/M/H/2	P_f	1(L) / 1.5(M) / 2.5(H) / 3(2)	mW
LD Reverse Voltage	V_{RLD}	2	V
PD Reverse Voltage	V_{RPD}	10	V
PD Forward Current	I_{FPD}	2.0	mA
Operating Temperature	T_{opr}	0 ~+70	°C
Storage Temperature	T_{stg}	-40 ~+85	°C

(All optical data refer to a coupled 9/125μm SM fiber)

Optical and Electrical Characteristics (Tc=25°C)

Parameter	Symbol	Min	Typ	Max	Unit	Test Conditions
Threshold Current	I_{th}	-	10	15	mA	CW
Fiber Output Power	L	0.2	-	0.5	mW	CW, I_{th} +20mA, kink free
	M	0.5	-	1		
	H	1	1.6	-		
	2	2	2.5	-		
Peak Wavelength	λ	1295	1310	1325	nm	Note 3
Side mode Suppression Ratio	Sr	30	35	-	dB	CW, $P_f = P_f$ (Min), 0~70°C
Forward Voltage	V_f	-	1.2	1.5	V	CW, $P_f = P_f$ (Min)
Rise/Fall Time	t_r / t_f	-	-	150	ps	$I_{bias} = I_{th}$, 20~80% Lead length=1mm
Tracking Error	$\Delta P_f / P_f$	-1.5	-	1.5	dB	APC, 0~70°C
PD Monitor Current	I_m	100	-	-	μA	CW, $P_f = P_f$ (Min), $V_{RPD}=2V$
PD Dark Current	I_{DARK}	-	-	0.1	μA	$V_{RPD}=5V$
PD Capacitance	C_t	-	6	15	pF	$V_{RPD}=5V, f=1MHz$

Note: 1.Pin assignment can be customized.


2.Specifications subject to change without notice.

3.Selected wavelength is available for WDM application.

C-13-DFB2.5-XX-SXXXX/XXX-X-XX

LD Pin Assignment

Part Number: C-13-DFB2.5-RX-SXXXX-XX




Pin 1 : Laser Cathode
Pin 2 : Laser Anode and Case Gnd
Pin 3 : Monitor Diode Anode
Pin 4 : Monitor Diode Cathode




Pin 1 : Monitor Diode Anode
Pin 2 : Laser Anode and Case Gnd
Pin 3 : Laser Cathode
Pin 4 : Monitor Diode Cathode





Pin 1 : Laser Anode and Monitor Diode Cathode
Pin 2 : Case Gnd
Pin 3 : Laser Cathode
Pin 4 : Monitor Diode Anode




FC Receptacle





ST Receptacle




SC Receptacle





Part Number: C-13-DFB2.5-TX-SSCXX-XX


DIMENSION A:7.77~8.37mm



SC TOSA
(L&M Power with Isolator)
C-13-DFB2.5-TX-SSCXI-XX



SC TOSA (H&2 Power)
C-13-DFB2.5-TX-SSCXX-XX




C-13-DFB2.5-XX-SXXXX/XXX-X-XX

Packaging Dimension


Units in mm.

Part Number: C-13-DFB2.5-TX-SLCXX-XX


P.C.D. 2.0 ± 0.5





LC TOSA (L&M Power)
C-13-DFB2.5-TX-SLCX-XX




DIMENSION A: 7.77~8.37mm



LC TOSA
(L&M Power with Isolator)
C-13-DFB2.5-TX-SLCXI-XX



LC TOSA (H&2 Power)
C-13-DFB2.5-TX-SLCXX-XX







Packaging Dimension

Units in mm.

Part Number: C-15-DFB2.5-PX-SXXXX/XXX-X-XX


P.C.D. 2.0 ± 0.5



Flange Type


4-ø0.45

"":Flangeless




Connector Type


FC:FC/PC




SC:SC/PC



"O":Horizontal (Omega Housing)




ST:ST/PC



MU:MUJ /PC




"V":Vertical



LC:LC/PC


"K":Horizontal (KX Housing)



C-13-DFB2.5-XX-SXXXXX/XXX-X-XX

Ordering Information

C-13-DFB2.5-XX-SXXXXX/XXX-X-XX



Warnings

Handling Precautions: This device is susceptible to damage as a result of electrostatic discharge (ESD). A static free environment is highly recommended. Follow guidelines according to proper ESD procedures.

Laser Safety: Radiation emitted by laser devices can be dangerous to human eyes. Avoid eye exposure to direct or indirect radiation.

Legal Notice

IMPORTANT NOTICE!

All information contained in this document is subject to change without notice, at LuminentOIC's sole and absolute discretion. LuminentOIC warrants performance of its products to current specifications only in accordance with the company's standard one-year warranty; however, specifications designated as "preliminary" are given to describe components only, and LuminentOIC expressly disclaims any and all warranties for said products, including express, implied, and statutory warranties, warranties of merchantability, fitness for a particular purpose, and non-infringement of proprietary rights. Please refer to the company's Terms and Conditions of Sale for further warranty information.

LuminentOIC assumes no liability for applications assistance, customer product design, software performance, or infringement of patents, services, or intellectual property described herein. No license, either express or implied, is granted under any patent right, copyright, or intellectual property right, and LuminentOIC makes no representations or warranties that the product(s) described herein are free from patent, copyright, or intellectual property rights. Products described in this document are NOT intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. LuminentOIC customers using or selling products for use in such applications do so at their own risk and agree to fully defend and indemnify LuminentOIC for any damages resulting from such use or sale.

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROVIDED ON AN "AS IS" BASIS. Customer agrees that LuminentOIC is not liable for any actual, consequential, exemplary, or other damages arising directly or indirectly from any use of the information contained in this document. Customer must contact LuminentOIC to obtain the latest version of this publication to verify, before placing any order, that the information contained herein is current.

© LuminentOIC, Inc. 2005
All rights reserved