MIRA-W

~40° wide beam



TECHNICAL SPECIFICATIONS:

Dimensions	Ø 32.4 mm
Height	14.7 mm
Fastening	glue
ROHS compliant	yes

MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
MIRA-W	Single lens	PC	clear	

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C12501_MIRA-W » Box size: 480 x 280 x 300 mm	840	120	60	7.2

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



Isometric view



Bottom view



Front view



Top view

Dimension D:
- C12500_MIRA-M 29,7mm
- C12501_MIRA-W 28,4mm
- C12502_MIRA-WW 28,4mm

Material: PC

This drawing is our property.
It can't be reproduced
or communicated without
our written agreement.

Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

DRAWN BY: mav	DATE: 02.04.2012	DRAWING TITLE: Datasheet MIRA lens			
CHECKED BY: sn	DATE: 02.04.2012	SIZE: A4	DRAWING NUMBER: -		REV: 1
DESIGNED BY: mav	DATE: 29.11.2011	SCALE: 1:1	WEIGHT(g):		SHEET: 1/1

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

bridgelux

LED	BXRA ES Star
FWHM	39.0°
Efficiency	82 %
LEDs/each optic	1
Light colour	White

Required components:



bridgelux

LED	V10 Gen6
FWHM	44.0°
Efficiency	77 %
Peak intensity	1.3 cd/lm
LEDs/each optic	1
Light colour	White

Required components:



CREE

LED	CXA/B 15xx
FWHM	39.0°
Efficiency	80 %
Peak intensity	1.4 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

CREE

LED	MHD-E/G
FWHM	43.0°
Efficiency	81 %
Peak intensity	1.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:





PHOTOMETRIC DATA (MEASURED):

CREE

LED	MT-G
FWHM	38.0°
Efficiency	80 %
Peak intensity	1.4 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





CREE

LED	XHP70
FWHM	42.0°
Efficiency	80 %
Peak intensity	1.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





LUMILEDS

LED	LUXEON M/MX
FWHM	39.0°
Efficiency	82 %
LEDs/each optic	1
Light colour	White
Required components:	



LUMILEDS

LED	LUXEON MZ
FWHM	31.0°
Efficiency	79 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

NICHIA

LED	NFMW48xA
FWHM	32.0°
Efficiency	80 %
Peak intensity	1.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





NICHIA

LED	NSCxL036A
FWHM	42.0°
Efficiency	79 %
Peak intensity	1.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





NICHIA

LED	NSMx286M
FWHM	28.0°
Efficiency	77 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





OSRAM
Opto Semiconductors

LED	Duris S10
FWHM	34.0°
Efficiency	83 %
Peak intensity	1.9 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

bridgelux

LED	VERO10
FWHM	38.8°
Efficiency	88 %
Peak intensity	1.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LUMILEDS

LED	LUXEON 5258
FWHM	31.0°
Efficiency	92 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LUMILEDS

LED	LUXEON K4
FWHM	34.0°
Efficiency	87 %
Peak intensity	1.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



OSRAM
Opto Semiconductors

LED	OSCONIQ P 7070
FWHM	51.0°
Efficiency	91 %
Peak intensity	1.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.