# PRODUCT DATASHEET
# Flare series
last update 25/9/2015

## DETAILS



| | |
|---|---|
| **Product Number** | C12837_FLARE-MINI-A-PIN |
| **Family** | Flare |
| **Type** | Lens |
| **Color** | clear |
| **Diameter** | 16 mm |
| **Height** | 8,6 mm |
| **Style** | round |
| **Optic Material** | PMMA |
| **Holder Material** | |
| **Fastening** | glue, pin |
| **Status** | production ready |
| **ROHS Comliant** | Yes |
| **Date Updated** | 25/09/2015 |


## OPTICAL PROPERTIES

| LED | Viewing Angle | Light Beam | Effi-ciency | cd/lm | Connector |
|---|---|---|---|---|---|
| XP-E | 95+17 deg | Oval | 95 % | 1.500 | - |
| XP-G | 99+21 deg | Oval | 95 % | 1.070 | - |
| XB-D | 95+16 deg | Oval | 95 % | 1.300 | - |
| XT-E | 95+19 deg | Oval | 94 % | 1.200 | - |
| XP-E2 | 94+16 deg | Oval | 94 % | 1.600 | - |
| XP-L | 106+29 deg | Oval | 94 % | 0.830 | - |
| XP-L2 | 100+30 deg | Oval | 94 % | 0.800 | - |
| LUXEON C | sim: 14+88 | Oval | sim: 93 % | sim: 1.460 | - |
| NCSxx19A | 87+15 deg | Oval | 95 % | 1.500 | - |
| NCSxx19B | 95+17 deg | Oval | 94 % | 1.500 | - |
| Oslon Square EC | 90+20 deg | Oval | 94 % | 1.250 | - |
| Oslon SSL 80 | 81+13 deg | Oval | 93 % | 2.000 | - |
| Oslon SSL 150 | 108+12 deg | Oval | 93 % | 1.600 | - |



*Ledil Oy*
*Salorankatu 10*
*24240 SALO, Finland*

*http://www.ledil.com*
*email: ledil@ledil.com*
*FAX: +358-2-733 8001*




Tolerances if not otherwise shown
According to DIN ISO 2768-1
Linear measures:
Up to 30mm class M, otherwise class C.
According to DIN ISO 2768-2
Form and position: class L

Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

THIRD ANGLE PROJECTION:

This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy."


DRAWING TITLE

# Datasheet FLARE-MINI_PIN


| SIZE | PART NUMBER |
|---|---|
| A4 | - |

| SCALE | WEIGHT | | SHEET |
|---|---|---|---|
| 2:1 | (g) | | 1/1 |


Luminaire: LEDIL OY C12763 & C12837_FLARE-MINI-A (XP-E) Efficiency=95%
Lamps: 1 x Cree XP-E (74lm@250mA)




Luminaire: LEDIL OY C12763 & C12837 FLARE-MINI-A (XP-G) Efficiency=95%
Lamps: 1 x Cree XP-G (92lm@250mA)




Luminaire: LEDIL OY C12763 & C12837_FLARE-MINI-A (XB-D) Efficiency=95%
Lamps: 1 x Cree XB-D white (97lm @ 250mA)




Luminaire: LEDIL OY C12763 & C12837_FLARE-MINI-A (XT-E AWT) Efficiency=94%
Lamps: 1 x Cree XT-E AWT (108lm@250mA)




Luminaire: Ledil Oy C12837_FLARE-MINI-A-PIN (CREE XP-E2 (92 lm @ 250 mA)) Efficiency=94%
Lamps: 1 x CREE XP-E2 (92 lm @ 250 mA)




Luminaire: LEDil Oy C12837_FLARE-MINI-A-PIN_(XP-L)
Lamps: 1 x Cree XP-L (125 lm @ 250mA) P=0.7W I=250mA




Luminaire: Ledil C12837_FLARE-MINI-A-PIN_(XP-L2)
Lamps: 1 x Cree_XP-L2_(XPLWT-00-0000-000HU630G)_115.505lm@250mA_P=0.72165W_I=0.25A




Luminaire: LEDIL OY C12763 & C12837_FLARE-MINI-A (NCS19) Efficiency=95%
Lamps: 1 x Nichia NCS19 (95lm@250mA)




Luminaire: Ledil Oy CANDEB_Flare-Mini-A-Re_(FBCBxx1M)(LEfficiency=94%
Lamps: 1 x Nichia NCSxx1ME-(NCSL11(BC) 695m @ 250mA CCT=3000K P=6.8W I=250mA




Luminaire: LEDIL OY C12763 & C12837_FLARE-MINI-A (SQ EC) Efficiency=94%
Lamps: 1 x Osram Oslon Square EC (69lm@250mA)




Luminaire: Ledil Oy C12763/C12837_FLARE-MINI-A (Osram OSL80 84lm @ 250mA) Efficiency=93%
Lamps: 1 x Osram OSL80 84lm @ 250mA




Luminaire: Ledil Oy C12763/C12837_FLARE-MINI-A (Osram OSL150 95lm @ 250mA) Efficiency=93%
Lamps: 1 x Osram OSL150 95lm @ 250mA




Luminaire: LEDIL OY C12763 & C12837_FLARE-MINI-A (XP-E) Efficiency=95%
Lamps: 1 x Cree XP-E (74lm@250mA)




Luminaire: LEDIL OY C12763 & C12837 FLARE-MINI-A (XP-G) Efficiency=95%
Lamps: 1 x Cree XP-G (92lm@250mA)



Luminaire: LEDIL OY C12763 & C12837_FLARE-MINI-A (XB-D) Efficiency=95%
Lamps: 1 x Cree XB-D white (97lm @ 250mA)




Luminaire: LEDIL OY C12763 & C12837_FLARE-MINI-A (XT-E AWT) Efficiency=94%
Lamps: 1 x Cree XT-E AWT (108lm@250mA)





cd/klm

C0 - C180 C90 - C270


Luminaire: Ledil Oy C12837_FLARE-MINI-A-PIN (CREE XP-E2 (92 lm @ 250 mA)) Efficiency=94%
Lamps: 1 x CREE XP-E2 (92 lm @ 250 mA)




Luminaire: LEDil Oy C12837_FLARE-MINI-A-PIN_(XP-L)
Lamps: 1 x Cree XP-L (125 lm @ 250mA) P=0.7W I=250mA




Luminaire: Ledil C12837_FLARE-MINI-A-PIN_(XP-L2)
Lamps: 1 x Cree_XP-L2_(XPLWT-00-0000-000HU630G)_115.505lm@250mA_P=0.72165W_I=0.25A



Luminaire: LEDIL OY C12763 & C12837_FLARE-MINI-A (NCS19) Efficiency=95%
Lamps: 1 x Nichia NCS19 (95lm@250mA)




Luminaire: Ledil Oy CX12035 Flare-Mini-A-Pro_(NCSxx*8E) Efficiency=94%
Lamp: 1 x Nichia NCSxx*8E (NESL119DE) 58lm @ 250mA CCT=3000K Pin=0.9W I=250mA





cd/klm
C0 - C180 C90 - C270


Luminaire: LEDIL OY C12763 & C12837_FLARE-MINI-A (SQ EC) Efficiency=94%
Lamps: 1 x Osram Oslon Square EC (69lm@250mA)



Luminaire: Ledil Oy C12763/C12837_FLARE-MINI-A (Osram OSL80 84lm @ 250mA) Efficiency=93%
Lamps: 1 x Osram OSL80 84lm @ 250mA



Luminaire: Ledil Oy C12763/C12837_FLARE-MINI-A (Osram OSL150 95lm @ 250mA) Efficiency=93%
Lamps: 1 x Osram OSL150 95lm @ 250mA



**NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.**