

Part Number: C9018A

Revision Date:

9/4/2012

2C 20 AWG 7/28 TC PVC / PVC



A. CONSTRUCTION

Conductor: #20 AWG 7/.0121" Tinned Copper
 Insulation: .016" Polyvinyl Chloride (PVC)
 Cable Core: Cable 2/C @ 2.00" LHL w/ clear polyester wrap, 100% coverage
 Jacket: ".032"" Polyvinyl Chloride (PVC) jacket
 Ripcord under Jacket"

DIAMETERS

.036" Nom
 .068" Nom
 .146" Nom
 .205" Nom

CAROL® EXZEL™ -- C9018A -- 2C 20 AWG
E105765-H (UL) TYPE CM 105C OR AWM 2464 80C 300V
VW-1 --- LL69381 CSA TYPE CMG 105C FT4 --CE --
-- ROHS -- MADE IN USA
(DATE CODE) (TRUMARK SEQUENTIAL FOOTAGE)

Print Legend:

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

Temperature:	CM/CMG: 105C, AWM: 80C
Suggested Working Voltage:	300V
Conductor DCR:	10.63 Ohms/M' @ 20°C
Mutual Capacitance:	22 pF/ft. @ 1 kHz

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	RED