





FCS-1152 Version: 1

- ! Mounting kits are to be ordered separately.
- ! Power supply unit is to be ordered separately.

## Varifocal IP Network Camera, 5-Megapixel, 802.3af PoE



- 1. Ethernet Port
- 2. Memory Card Slot
- 3. Power LED
- 4. Reset Button
- 5. Audio Input/ Output & Digital Input/ Output



- 6. Monitor Distance Adjustment
- 7. Focal Length Adjustment
- 8. DC Iris Port

### Key Features

- Built-in Micro SDHC/SDXC card slot for local storage
- 5-Megapixel high-definition resolution
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Video compression: H.264, MJPEG
- Removable IR-cut filter for day and night surveillance
- Power support: PoE (IEEE 802.3af)
- Free surveillance and CMS (Central Management System) software packages with 64-channel license

## Specifications

### System Specifications

#### Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet

IEEE 802.3u 100-BASE-TX, Fast Ethernet

IEEE 802.3af Power over Ethernet (PoE)

TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour

#### Image Sensor:

5-Megapixel 1/3.2" Progressive Scan CMOS

#### Lens:

Vari-focal, DC iris, Manual focus, f2.8-12mm, F1.4

#### Port:

1 x RJ-45 10/100 Mbps PoE Port

1 x Auto Iris (DC Drive)

I/O terminal block (1 DI/1 DO)

1 x MicroSDHC/ MicroSDXC card slot

#### Button/Knob:

Reset Button

#### Indicator:

Power

#### IR Cut Filter:

Removable infrared-cut filter for day & night function

#### Shutter Time:

1/5 ~ 1/10,000 sec

#### Angle of View:

70.9° - 29.2°

#### Pan/Tilt/Zoom:

Digital Zoom to very high detail available on Software

#### Video Compression:

H.264 / MJPEG

#### Resolution:

5M (2592x1944)

#### Output Video Format:

RAW

#### Audio Compression:

G.711

#### Power Input:

802.3af PoE

#### Power Consumption:

PoE Class 2 (IEEE802.3af) / 4.002W

#### Data Rate:

10/100Mbps

#### Storage Capacity:

SD/MicroSD memory card of up to 64GB

### Features

**General:**

Backup: MicroSDHC /MicroSDXC card slot for local storage

**Video:**

Image Setting: - Adjustable image size, quality and bit rate

- Configurable brightness, sharpness, contrast, saturation, white balance and exposure

- AGC/AWB/AES

- Back Light Compensation (BLC)

- Wide Dynamic Range (WDR), Basic WDR (74 dB)

- 2D Noise Reduction (2DNR)

Streaming: Up to 2 video streams

**Performance****Frame Rate (fps):**

15fps at 2592 x 1944; 15 fps at 2048x1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 720; 30 fps at 640 x 480; 15 fps at 320 x 240

**Minimum illumination:**

Color: 0.1 lux at F1.4

B/W: 0.05 lux at F1.4

**Environment****Operating Temperature (°C):**

Operating: -10°C ~ 50°C

**Operating Humidity (Non-condensing):**

Operating: 10% ~ 85%

**Installation:**

Wall Mount

**Physical Specifications****Dimensions (W x D x H mm):**

67 x 169 x 65 mm

**Weight (g):**

438 g

**Approval and Compliance****EMI/EMS:**


CE, RoHS, FCC, ONVIF

**Others****Operation Systems:**

Microsoft Windows 8/7/Vista/XP



## Diagram



---

## Order Information

FCS-1152

---

## Package Contents

FCS-1152  
Screw Kit  
Quick Installation Guide  
Resource CD (User Manual, QIG)

---

## Optional Accessory



**CAS-3104**  
Wall Mount Bracket



**CAS-3105**  
Bracket for Zoom Box Cameras

No liability or responsibility for any errors or omissions in the content.  
Specifications are subject to change without notice.  
All mentioned brand names are registered trademarks and property of their owners.  
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.