CAT6202

LDO Regulator - Adjustable CMOS

500 mA, 13 V

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR ON SEMICONDUCTOR
REPRESENTATIVE FOR INFORMATION

Description

The CAT6202 is a 13 V rated 500 mA CMOS low dropout regulator that provides fast response time to load current and line voltage changes in an automotive environment.

CAT6202 features a low R_{ON} P−channel pass element with internal control circuitry which prevents reverse current flow should the voltage at V_{OUT} exceed V_{IN} as in the case of the car's battery voltage accidentally being applied to V_{OUT}.

Thermal protection and current limiting circuitry combine to protect the pass device against faults and abuse. Current limiting is user controlled through a single resistor to ground. A fault output ($\overline{FLT}$) provides an alert should an over−current event or thermal shutdown occur.

CAT6202 comes on−line gracefully even though it may be driving heavy capacitive loads thanks to built−in soft−start circuitry. Its output is protected against accidental connection to voltages greater than V_{IN} and will not conduct current backwards into its supply.

CAT6202 is available in 8−pad 2 mm x 3 mm TDFN package.

Features

- Guaranteed 500 mA Continuous Output Current
- Low Dropout Voltage of 250 mV Typical at 500 mA
- Input Voltage Range: 3.3 V to 13.5 V
- User Adjustable Output Voltage
- User Programmable Current Limit
- Fault Output to Indicate Under−voltage, Current Limiting or Thermal Shutdown has Occurred
- Fault Blanking: 3 ms
- V_{OUT} Withstands Battery Fault Voltages of up to 14 V
- Soft−Start Prevents Current Surges
- Stable with Ceramic Output Capacitor
- ±1.0% Output Voltage Initial Accuracy
- ±2.0% Accuracy Over Temperature
- Thermal Protection
- 8 Pad TDFN Package
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant


ON Semiconductor®

http://onsemi.com




TDFN−8
VP2 SUFFIX
CASE 511AK

PIN CONNECTIONS



TDFN−8
(Top View)

MARKING DIAGRAMS



HXC	= CAT6202VP2−GT3
L	= Assembly Location
AA	= Last Two Digits of Assembly Lot Number
Y	= Production Year (Last Digit)
M	= Production Month (1−9, O, N, D)
▪	= Pb−Free Microdot

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 10 of this data sheet.

© Semiconductor Components Industries, LLC, 2014




Figure 1. CAT6202 Typical Application




Figure 2. CAT6202 Functional Block Diagram

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR ON SEMICONDUCTOR
REPRESENTATIVE FOR INFORMATION

Table 1. PIN FUNCTION DESCRIPTION

Pin No.	Pin Name	Description
1	VIN	Supply voltage input
2	$\overline{FLT}$	Fault indicator (active low)
3	EN	Enable input (active high)
4	BYP	A capacitor between BYP and GND controls the regulator's turn−on speed and improves PSRR
5	GND	Ground reference
6	ILIM	Current limit control pin
7	VADJ	Output voltage adjustment
8	VOUT	LDO Output Voltage

Table 2. ABSOLUTE MAXIMUM RATINGS

Rating	Value	Unit
V_{IN}, V_{OUT}	0 to 16	V
All other pins	−0.3 to +6.0	V
Junction Temperature, T_J	+150	°C
Power Dissipation, P_D	Internally Limited (Note 1)	mW
Storage Temperature Range, T_S	−65 to +150	°C
Lead Temperature (soldering, 5 sec.)	260	°C
ESD Rating (Human Body Model)	1000	V
ESD Rating (Machine Model)	350	V

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. The maximum allowable power dissipation at any T_A (ambient temperature) is $P_{Dmax} = (T_{Jmax} − T_A) / \theta_{JA}$. Exceeding the maximum allowable power dissipation will result in excessive die temperature, and the regulator will go into thermal shutdown.

Table 3. RECOMMENDED OPERATING CONDITIONS (Note 2)

Parameter	Range	Unit
V_{IN}, V_{OUT}	3.3 to 13.5	V
All other pins	0 to 6.0	V
Junction Temperature Range, T_J	−40 to +125	°C
Package Thermal Resistance (SOIC), θ_{JA}	235	°C/W
Package Thermal Resistance (TDFN), θ_{JA}	92	°C/W

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

2. The device is not guaranteed to work outside its operating rating.

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR ON SEMICONDUCTOR
REPRESENTATIVE FOR INFORMATION

Pin Function

VIN is the supply pin for both the LDO's operation and the load the LDO is driving. It is recommended that a 1 μF ceramic bypass capacitor be placed between the V_{IN} pin and ground in close proximity to the device. When using longer connections to the power supply, C_{IN} value can be increased without limit. The operating input voltage range is from 3.3 V to 13 V.

$\overline{\text{FLT}}$ is an active low open−drain output indicating one of 3 fault conditions:

1. Input under−voltage: V_{IN} is below the intended output voltage
2. Over−current. Brief over−current events are masked by a 3 ms time delay. CAT6202 will limit current anytime the load tries to draw more than the maximum allowed however reporting of this event will occur only if the event lasts longer than the delay timer. Events terminating before the timer reaches its full count are ignored and the timer is reset.
3. Over−temperature shutdown has occurred.

EN is an active HIGH logic level input for switching the regulator's output between ON and OFF. A weak internal pull down assures that if EN pin is left open, the circuit is disabled.

BYP controls the soft−start feature for the regulator. When large capacitive loads are present at the regulator's output, enabling the regulator will produce large current surges on the V_{IN} supply line. To reduce these surges the regulator can be turned on gently by connecting a capacitor between the BYP pin and ground. The larger the capacitance value the more slowly V_{OUT} approaches its programmed value. The table below gives a list of common capacitor values and their resulting turn−on times. If the soft−start feature is not desired, this pin should be left floating.

Capacitance [nF]	t_{ON} [ms]
0	0.2
10	1
100	10

GND is the ground reference for the LDO. The TDFN package center metal pad is internally connected to GND. If electrical contact is made with this pad, it should be to GND and/or the ground plane of the PCB. Connection to the ground plane enhances thermal conductivity drawing heat out of the package and into the surrounding PCB.

ILIM stands for Current Limit and is the control input for setting the point at which the current limit is invoked. I_{LIM} is defined as the current at which V_{OUT} is still within 80% of its nominal value and should not be confused with I_{SC}, the short circuit current, measured at V_{OUT} = 0 V, which is typically 100 mA greater than I_{LIM}.

A resistor R_{EXT} placed between I_{LIM} and GND selects the trip current according to a formula:

$$I_{LIMIT} = I_{LIMIT0} + \frac{\text{Current_Limit_Factor(CLF)}}{R_{EXT}} \quad \text{(eq. 1)}$$

I_{LIM0} is the built−in minimum current limit (typically 150 mA), and CLF is a numerical value (typical 30,000 Volts) which relates the allowable load current to a resistance value. The value of this resistor is determined by the following equation:

$$R_{EXT}(\Omega) = \frac{CLF(V)}{I_{LIM}(A) - I_{LIM0}(A)} \quad \text{(eq. 2)}$$

It is recommended that I_{LIM} be set with at least 50%, and preferably 60%, higher than the maximum intended continuous I_{OUT}.

Example: Set I_{LIMIT} = 800 mA

$$R_{EXT}(\Omega) = \frac{30,000\ V}{0.8\ A - 0.15\ A} = 47\ K\Omega \quad \text{(eq. 3)}$$

VADJ is the output voltage control pin. A resistor divider placed between VOUT and GND whose center point connects to VADJ sets the LDO regulator's output voltage. Typical VADJ value is 1.25 V. The current through the resistor divider can be anywhere between 10 μA and 1 mA. The higher this current is, the lower the noise.

VOUT is the LDO regulator output. A small 2.2 μF ceramic bypass capacitor is required between VOUT and ground. For better transient response, its value can be increased to 4.7 μF. This capacitor should be located near the device.

$$V_{OUT} = V_{ADJ}\left(1 + \frac{R_1}{R_2}\right) \quad \text{(eq. 4)}$$

VOUT is protected against short circuits and over−temp operation by internal circuitry. In the event of an over−current, the LDO behaves like a current source, limiting current at the output. The maximum current allowed is set by R_{EXT}, the resistor between ILIM and GND. If the load attempts to draw more than the allowed current, VOUT and IOUT decrease together and thus limit the total power delivered.

VOUT is protected against the application of voltages greater than VIN. For example, in automotive applications, if CAT6202 is powering a remote load and damage occurs to a wiring harness shorting a powered line, Battery + for instance, to VOUT, CAT6202 will not be damaged by this higher voltage being applied to VOUT.

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR ON SEMICONDUCTOR
REPRESENTATIVE FOR INFORMATION

Table 4. ELECTRICAL CHARACTERISTICS
(V_{IN} = V_{OUT} + 1 V, V_{EN} = High, I_{OUT} = 1 mA, C_{IN} = 1 μF, C_{OUT} = 2.2 μF, R_{EXT} = 47 kΩ, ambient temperature of 25°C (over recommended operating conditions unless specified otherwise). **Bold numbers** apply for the entire junction temperature range.)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{IN}	Input Voltage		**3.3**		**13.5**	V
V_{OUT}	Output Voltage		**V_{ADJ}**		**12.5**	
V_{ADJ}	ADJ Voltage		1.238	1.250	1.262	V
I_{ADJ}	ADJ Input Current		0.5		**2.0**	μA
TC_{OUT}	Output Voltage Temp. Coefficient			40		ppm/°C
V_{R-LINE}	Line Regulation	V_{OUT} + 1.0 < V_{IN} < 13 V	−0.2	±0.1	+0.2	%/V
			−0.4		**+0.4**	
V_{R-LOAD}	Load Regulation	I_{OUT} = 1 mA to 500 mA		1	**2.5**	%
V_{DROP}	Dropout Voltage (Note 3)	I_{OUT} = 500 mA		250	**350**	mV
I_{GND}	Ground Current	I_{OUT} = 0 mA		100	**150**	μA
		I_{OUT} = 500 mA		160	**300**	
I_{GND-SD}	Shutdown Ground Current	V_{EN} < 0.4 V			**2**	μA
PSRR	Power Supply Rejection Ratio	f = 1 kHz, C_{BYP} = 10 nF		62		dB
		f = 20 kHz, C_{BYP} = 10 nF		52		
T_{ON}	Turn−On Time	C_{BYP} = 10 nF		700		μs
I_{SC}	Output short circuit current	V_{OUT} < 0.8 V	700	800	1000	mA
I_{LIM}	Output current limit	V_{OUT} = 0.8 V_{OUT} (1 mA)	600	650	800	mA
CLF	Current Limit Factor	V_{OUT} < 0.8 V	24	30	36	KV
t_{FD}	Fault Delay		1.5	3	6	ms
$V_{IN-UVLO}$	Under voltage lockout threshold			3.1		V
ESR	R_{OUT} equivalent series resistance		5		500	mΩ
ENABLE INPUT						
V_{HI}	Logic High Level	V_{IN} = 3.3 to 13 V	**2**			V
V_{LO}	Logic Low Level	V_{IN} = 3.3 to 13 V			**0.4**	V
I_{EN}	Enable Input Current	V_{EN} = 0.4 V		0.15	1	μA
		V_{EN} = V_{IN}		3	5	
THERMAL PROTECTION						
T_{SD}	Thermal Shutdown			140		°C
T_{HYS}	Thermal Hysteresis			10		°C

3. Dropout voltage is defined as the input−to−output differential at which the output voltage drops 2% below its nominal value. During test, the input voltage stays always above the minimum 3.3 V. The given values are for V_{OUT} = 7.5 V.

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR ON SEMICONDUCTOR
REPRESENTATIVE FOR INFORMATION

TYPICAL CHARACTERISTICS (shown for 7.5 V output)
(V_{IN} = 8.5 V, R_1 = 5.1 kΩ, R_2 = 1 kΩ, C_{IN} = 1 μF, C_{OUT} = 2.2 μF, C_{BYP} = 10 nF, R_{EXT} = 47 kΩ, $\overline{FLT}$ not connected, T_A = 25°C unless otherwise specified.)




Figure 3. Dropout Characteristics




Figure 4. Line Regulation




Figure 5. Load Regulation




Figure 6. Adjustable Voltage vs. Temperature




Figure 7. Ground Current vs. Load Current




Figure 8. Ground Current vs. Temperature

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR ON SEMICONDUCTOR
REPRESENTATIVE FOR INFORMATION

TYPICAL CHARACTERISTICS (shown for 7.5 V output)
(V_{IN} = 8.5 V, R_1 = 5.1 kΩ, R_2 = 1 kΩ, C_{IN} = 1 μF, C_{OUT} = 2.2 μF, C_{BYP} = 10 nF, R_{EXT} = 47 kΩ, $\overline{FLT}$ not connected, T_A = 25°C unless otherwise specified.)




Figure 9. Output Short−circuit Current vs. Input Voltage




Figure 10. Ground Current vs. Input Voltage




Figure 11. Enable Threshold vs. Input Voltage




Figure 12. Fault Bar Voltage vs. Input Voltage




Figure 13. Output Voltage vs. Load Current




Figure 14. Output Current (Sink) vs. Output Voltage

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR ON SEMICONDUCTOR
REPRESENTATIVE FOR INFORMATION

TYPICAL CHARACTERISTICS (shown for 7.5 V output)

(V_{IN} = 8.5 V, R_1 = 5.1 kΩ, R_2 = 1 kΩ, C_{IN} = 1 μF, C_{OUT} = 2.2 μF, C_{BYP} = 10 nF, R_{EXT} = 47 kΩ, T_A = 25°C unless otherwise specified. All transient characteristics are generated using the evaluation board CAT6202EVAL1.)




Figure 15. Enable Turn−On (No Load)




Figure 16. Enable Turn−On (15 Ω Load)




Figure 17. Enable Operation (No Load)




Figure 18. Enable Operation (15 Ω Load)




Figure 19. Load Transient Response (1 mA to 500 mA)





Figure 20. Fault Operation (VIN = 7 V and 15 Ω Load)


OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR ON SEMICONDUCTOR
REPRESENTATIVE FOR INFORMATION

PACKAGE DIMENSIONS

TDFN8, 2x3
CASE 511AK−01
ISSUE A



TOP VIEW **SIDE VIEW** **BOTTOM VIEW**



FRONT VIEW

SYMBOL	MIN	NOM	MAX
A	0.70	0.75	0.80
A1	0.00	0.02	0.05
A2	0.45	0.55	0.65
A3		0.20 REF	
b	0.20	0.25	0.30
D	1.90	2.00	2.10
D2	1.30	1.40	1.50
E	2.90	3.00	3.10
E2	1.20	1.30	1.40
e		0.50 TYP	
L	0.20	0.30	0.40

Notes:
(1) All dimensions are in millimeters.
(2) Complies with JEDEC MO-229.

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR ON SEMICONDUCTOR
REPRESENTATIVE FOR INFORMATION

Table 5. ORDERING INFORMATION

Device Order Number	Specific Device Marking	Package Type	Lead Finish	Shipping†
CAT6202VP2−GT3	HXC	TDFN−8	NiPdAu	Tape & Reel, 3,000 Units / Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR ON SEMICONDUCTOR
REPRESENTATIVE FOR INFORMATION

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative