

CC3-2403SS-E



Sales Region	Worldwide
Series	CC-E
Status	Production
Option	SIP type
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics	
Rated Input Voltage[DC]	24V
Input Voltage Range[DC]	18 to 36V
Efficiency	73% Typ.
Rated Output Voltage[DC]	3.3V
Output Voltage Range[DC]	3.15 to 3.67V
Maximum Output Current	
Maximum Ripple Noise	120mV
Maximum Output Power	2.64W
Withstanding Voltage1	Input - Case: 500VAC: 1min.
Withstanding Voltage2	Input - Output: 500VAC: 1min.
Withstanding Voltage3	Output - Case: 500VAC: 1min.

Cases Shape & Size	
Case'□' shape	On board/Power module
Width(W)	27.8mm Nom.
Height(H)	17.9mm Nom.
Depth(D)	9.2mm Nom.
Weight	7g Typ.
Industry Standard Size	
Terminal Style	SIP

Other	
Operating Temp. Range	-40 to 85°C
Isolated / Non-isolated	Isolated
Feature	
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 (C-UL) EN60950-1 (NEMKO)
Safety Standard(Conformed)	

Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.
---------	---

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.