

CC30-2415SFP-E



Sales Region	Worldwide
Series	CC-P-E
Status	Production
Option	DIP type Parallel operation
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics	
Rated Input Voltage[DC]	24V
Input Voltage Range[DC]	18 to 36V
Efficiency	90% Typ.
Rated Output Voltage[DC]	15V
Output Voltage Range[DC]	Fixed
Maximum Output Current	
Maximum Ripple Noise	150mV
Maximum Output Power	30W
Withstanding Voltage1	Input - Output: 1000VDC: 1min.
Withstanding Voltage2	Input - Case: 500VDC: 1min.
Withstanding Voltage3	Output - Case: 500VDC: 1min.

Cases Shape & Size	
Case'□' shape	On board/Power module
Width(W)	38.2mm Nom.
Height(H)	8.3mm Nom.
Depth(D)	33.5mm Nom.
Weight	20g Typ.
Industry Standard Size	
Terminal Style	DIP

Other	
Operating Temp. Range	-40 to 85°C
Isolated / Non-isolated	Isolated
Feature	
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 (C-UL) EN60950-1 (NEMKO)
Safety Standard(Conformed)	

Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.
---------	---

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.