
Crystal Clock Oscillator Specification
CFPS-40 AUTO

ISSUE 1; May 2016

Description

- Ceramic package with a hermetically seam sealed metal lid suitable for automotive applications. Qualified to AEC-Q200 and with TS16949 release.



Frequency Parameters

- Frequency 2.0MHz to 50.0MHz
- Frequency Stability ±25.00ppm to ±100.00ppm
- Ageing ±5ppm max per year @ 25°C

Electrical Parameters

- Supply Voltage 2.5V ±5%

Operating Temperature Ranges

- -40 to 85°C
- -40 to 125°C

Output Details

- Output Compatability CMOS
- Drive Capability 15pF

Output Control

- Enable/Disable Operation:
  Logic '1' (>70% Vs) to pad 1 enables oscillator output.
  Logic '0' (<30% Vs) to pad 1 disables oscillator output; the oscillator output goes to the high impedance state.
  No connection to pad 1 enables oscillator output.
- Standby Current:
  -40 to 85°C: 10µA max
  -40 to 125°C: 20µA max

Environmental Parameters

- Storage Temperature Range: -55 to 150°C
- Qualified to AEC-Q200

Ordering Information

- Frequency*
  Model*
  Output
  Frequency Stability*
  Operating Temperature Range*
  Supply Voltage
  (*minimum required)
- Example
  20.0MHz CFPS-40 AUTO
  CMOS ±100ppm –40 to 125C 2.5V


Compliance

- RoHS Status (2011/65/EU) Compliant
- REACh Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable

Packaging Details

- Pack Style: Reel Tape & reel in accordance with EIA-481-D
  Pack Size: 1,000

Outline (mm)



Sales Office Contact Details:

UK: +44 (0)1460 270200 France: 0800 901 383 Email: info@iqdfrequencyproducts.com
Germany: 0800 1808 443 USA: +1.760.318.2824 Web: www.iqdfrequencyproducts.com

Electrical Specification - maximum limiting values 2.5V ±5%

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
2.0MHz	9.999999MHz	-40 to 85	±25.0	6	5	40/60%
		-40 to 125	±50.0	6	5	40/60%
10.0MHz	19.999999MHz	-40 to 85	±25.0	8	5	40/60%
		-40 to 125	±50.0	8	5	40/60%
20.0MHz	31.999999MHz	-40 to 85	±25.0	8	5	40/60%
		-40 to 125	±50.0	8	5	40/60%
32.0MHz	50.0MHz	-40 to 85	±25.0	20	5	40/60%
		-40 to 125	±50.0	20	5	40/60%

This document was correct at the time of printing; please contact your local sales office for the latest version.
Click to view latest version on our website.

Sales Office Contact Details:
UK: +44 (0)1460 270200
France: 0800 901 383
Email: info@iqdfrequencyproducts.com
Germany: 0800 1808 443
USA: +1.760.318.2824
Web: www.iqdfrequencyproducts.com