36-40GHz Integrated Down Converter


GaAs Monolithic Microwave IC

Description


The CHR2296 is a multifunction chip which integrates a LO time two multiplier, a balanced cold FET mixer, and a RF LNA. It is designed for a wide range of applications, typically commercial communication systems. The backside of the chip is both RF and DC grounds. This helps simplify the assembly process.

The circuit is manufactured with a pHEMT process, 0.25µm gate length, via holes through the substrate, air bridges and electron beam gate lithography.
It is available in chip form.

LO



Typical on wafer measurement:
Conversion Gain & Image suppression
@ IF=1GHz



Main Features

- Broadband performances: 36-40GHz
- 11 dB conversion gain
- 5dB noise figure, for IF>0.1GHz
- 10dBm LO input power
- -10dBm RF input power (1dB gain comp.)
- Low DC power consumption, 110mA@3.5V
- Chip size: 2.49 X 1.97 X 0.10mm

Main Characteristics

Tamb. = 25°C

Symbol	Parameter	Min	Typ	Max	Unit
F_{RF}	RF frequency range	36		40	GHz
F_{LO}	LO frequency range	17		20	GHz
F_{IF}	IF frequency range	DC		1.5	GHz
G_c	Conversion gain	9	11		dB

ESD Protection: Electrostatic discharge sensitive device. Observe handling precautions!

United Monolithic Semiconductors S.A.S.
Route Départementale 128 - B.P.46 - 91401 Orsay Cedex France
Tel. : +33 (0)1 69 33 03 08 - Fax : +33 (0)1 69 33 03 09

Electrical Characteristics for Broadband Operation

Tamb = +25°C, Vd = 3.5V

Symbol	Parameter	Min	Typ	Max	Unit
F_{RF}	RF frequency range	36		40	GHz
F_{LO}	LO frequency range	17		20	GHz
F_{IF}	IF frequency range	DC		1.5	GHz
G_c	Conversion gain (1)	9	11		dB
NF	Noise Figure, for IF>0.1GHz (1)		5		dB
P_{LO}	LO Input power		+10		dBm
Img Sup	Image Suppression	13	15		dBc
P1dB	Input power at 1dB gain compression		-10		dBm
LO VSWR	Input LO VSWR (1)		2.0:1		
RF VSWR	Input RF VSWR (1)		3.0:1		
Id	Bias current (2)		110		mA

(1) On Wafer measurements
(2) Current source biasing network is recommended. Optimum performances for Idm = 50mA and Idl = 60mA

Absolute Maximum Ratings

Tamb. = 25°C (1)

Symbol	Parameter	Values	Unit
Vd	Maximum drain bias voltage	4.0	V
Id	Maximum drain bias current	200	mA
Vg	Gate bias voltage	-2.0 to +0.4	V
Vgd	Minimum negative gate drain voltage (Vg – Vd)	-5	V
Pin	Maximum peak input power overdrive (2)	+15	dBm
Tch	Maximum channel temperature	175	°C
Ta	Operating temperature range	-40 to +85	°C
Tstg	Storage temperature range	-55 to +125	°C


(1) Operation of this device above anyone of these parameters may cause permanent damage.
(2) Duration < 1s.

Route Départementale 128, B.P.46 - 91401 ORSAY Cedex - FRANCE
Tel.: +33 (0)1 69 33 03 08 - Fax : +33 (0)1 69 33 03 09


united monolithic semiconductors

Typical On-wafer Measurements

Bias Conditions : Vdm= Vdl= 3.5 V, Vgm= -0.9V, Vgb= -0.4V, Vgx= -0.8V, Vga= -0.5V



Conversion gain & Image suppression with a 90° IQ combiner @ IF=1GHz




Input RF compression by channel


Route Départementale 128, B.P.46 - 91401 ORSAY Cedex - FRANCE
Tel.: +33 (0)1 69 33 03 08 - Fax : +33 (0)1 69 33 03 09

united monolithic semiconductors

Chip Assembly and Mechanical Data



Note: Supply feed should be bypassed. 25µm diameter gold wire is recommended



Bonding pad positions
(Chip thickness: 100µm. All dimensions are in micrometers)

Route Départementale 128, B.P.46 - 91401 ORSAY Cedex - FRANCE
Tel.: +33 (0)1 69 33 03 08 - Fax : +33 (0)1 69 33 03 09

Notes

Route Départementale 128, B.P.46 - 91401 ORSAY Cedex - FRANCE
Tel.: +33 (0)1 69 33 03 08 - Fax : +33 (0)1 69 33 03 09

united monolithic semiconductors

Recommended ESD management

Refer to the application note AN0020 available at http://www.ums-gaas.com for ESD sensitivity and handling recommendations for the UMS products.

Ordering Information

Chip form: CHR2296-99F/00

Information furnished is believed to be accurate and reliable. However **United Monolithic Semiconductors S.A.S.** assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of **United Monolithic Semiconductors S.A.S.**. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. **United Monolithic Semiconductors S.A.S.** products are not authorised for use as critical components in life support devices or systems without express written approval from **United Monolithic Semiconductors S.A.S.**

Route Départementale 128, B.P.46 - 91401 ORSAY Cedex - FRANCE
Tel.: +33 (0)1 69 33 03 08 - Fax : +33 (0)1 69 33 03 09