
TO-251/TO-252-2L Plastic-Encapsulate Voltage Regulators

CJ7812 Three-terminal positive voltage regulator


TO-251
TO-252-2L



1.IN

2.GND

3.OUT



FEATURES

Maximum Output current I_{OM}: 1.5 A
Output voltage V_o: 12 V
Continuous total dissipation
P_D: 1.25 W (T_a = 25℃)
10 W (T_C= 25℃)

ABSOLUTE MAXIMUM RATINGS (Operating temperature range applies unless otherwise specified)

Parameter	Symbol	Value	Unit
Input Voltage	V_i	35	V
Thermal Resistance from Junction to Air	$R_{\theta JA}$	100	℃/W
Thermal Resistance from Junction to Case	$R_{\theta JC}$	12.5	℃/W
Operating Junction Temperature Range	T_{OPR}	0-150	℃
Storage Temperature Range	T_{STG}	-65-150	℃

ELECTRICAL CHARACTERISTICS AT SPECIFIED VIRTUAL JINCTION TEMPERATURE (Vi=19V, Io=500mA,Ci=0.33μF, Co=0.1μF, unless otherwise specified)

Parameter	Symbol	Test conditions		Min	Typ	Max	Unit
Output Voltage	Vo		25℃	11.5	12.0	12.5	V
		Io= 5.0mA-1.0A, P≤10W 14.5V≤ V_i ≤27V	0-125℃	11.4	12	12.6	V
Load Regulation	ΔVo	14.5V≤ Vi ≤30V	25℃		10	240	mV
		16V≤V_i≤22V	25℃		3	120	mV
Line Regulation	ΔVo	I_O=5mA - 1.5A	25℃		12	240	mV
		I_O=250mA - 750mA	25℃		4	120	mV
Quiescent Current	Iq		25℃		4.3	8	mA
Quiescent Current Change	ΔIq	5.0mA≤ I_O ≤1.0A	0-125℃			0.5	mA
		14.5V ≤V_i≤ 30V	0-125℃			1.0	mA
Output Voltage Drift	△Vo/△T	I_O=5mA	0-125℃		-1		mV/℃
Output Noise Voltage	V_N	f =10Hz to 100KHz	25℃		75		μV
Ripple Rejection	RR	f =120Hz, 15V≤ V_i ≤25V	0-125℃	55	71		dB
Dropout Voltage	V_d	I_O=1.0A	25℃		2		V
Output Resistance	R_O	f =1KHz	25℃		18		mΩ
Short Circuit Current	Isc		25℃		350		mA
Peak Current	Ipk		25℃		2.2		A

TYPICAL APPLICATION

