
CM1400DUC-24S

Powerex, Inc., 173 Pavilion Lane, Youngwood, Pennsylvania 15697 (724) 925-7272
www.pwrx.com

Mega Power Dual IGBT
1400 Amperes/1200 Volts



Tolerance Otherwise Specified (mm)


Division of Dimension			Tolerance
	0.5 to	3	±0.2
over	3 to	6	±0.3
over	6 to	30	±0.5
over	30 to	120	±0.8
over	120 to	400	±1.2

Outline Drawing and Circuit Diagram

Dimensions	Inches	Millimeters
A	5.91	150.0
B	5.10	129.5
C	1.67±0.01	42.5±0.25
D	5.41±0.01	137.5±0.25
E	6.54	166.0
F	2.91±0.01	74.0±0.25
G	1.65	42.0
H	0.55	14.0
J	1.50±0.01	38.0±0.25
K	0.16	4.0
L	1.36 +0.04/-0.02	34.6 +1.0/-0.5

Housing Type (J.S.T. MFG. CO. LTD)
BB = VHR-2N
CC = VHR-5N

Dimensions	Inches	Millimeters
M	0.075±0.008	1.9±0.2
N	0.47	12.0
P	0.26	6.5
R	M6 Metric	M6
S	0.08	2.0
T	0.99	25.1
U	0.62	15.7
V	0.71	18.0
W	0.75	19.0
X	0.43	11.0
Y	0.83	21.0
Z	0.41	10.5
AA	0.22	5.5



Description:
Powerex Mega Power Dual (MPD) Modules are designed for use in switching applications. Each module consists of two IGBT Transistors having a reverse-connected super-fast recovery free-wheel diode. All components and interconnects are isolated from the heat sinking baseplate, offering simplified system assembly and thermal management.

Features:
- ☐ Low Drive Power
- ☐ Low $V_{CE(sat)}$
- ☐ Discrete Super-Fast Recovery Free-Wheel Diode
- ☐ Isolated Baseplate for Easy Heatsinking
- ☐ RoHS Compliant

Applications:
- ☐ High Power DC Power Supply
- ☐ Large DC Motor Drives
- ☐ Utility Interface Inverters

Ordering Information:
Example: Select the complete module number you desire from the table - i.e. CM1400DUC-24S is a 1200V (V_{CES}), 1400 Ampere Dual IGBTMOD Power Module.


Type	Current Rating Amperes	V_{CES} Volts (x 50)
CM	1400	24

CM1400DUC-24S
Mega Power Dual IGBT
1400 Amperes/1200 Volts

Absolute Maximum Ratings, T_j = 25°C unless otherwise specified

Characteristics	Symbol	Rating	Units
Collector-Emitter Voltage (V_{GE} = 0V)	V_{CES}	1200	Volts
Gate-Emitter Voltage (V_{CE} = 0V)	V_{GES}	±20	Volts
Collector Current (DC, T_C = 124°C)*2,*4	I_C	1400	Amperes
Collector Current (Pulse, Repetitive)*3	I_{CRM}	2800	Amperes
Total Power Dissipation (T_C = 25°C)*2,*4	P_{tot}	9370	Watts
Emitter Current*2	I_E*1	1400	Amperes
Emitter Current (Pulse, Repetitive)*3	I_{ERM}*1	2800	Amperes
Isolation Voltage (Terminals to Baseplate, RMS, f = 60Hz, AC 1 minute)	V_{isol}	4000	Volts
Maximum Junction Temperature	$T_{j(max)}$	175	°C
Maximum Case Temperature*4	$T_{C\ (max)}$	125	°C
Operating Junction Temperature	$T_{j(op)}$	-40 to +150	°C
Storage Temperature	T_{stg}	-40 to +125	°C

*1 Represent ratings and characteristics of the anti-parallel, emitter-to-collector clamp diode.
*2 Junction temperature (T_j) should not increase beyond maximum junction temperature ($T_{j(max)}$) rating.
*3 Pulse width and repetition rate should be such that device junction temperature (T_j) does not exceed $T_{j(max)}$ rating.
*4 Case temperature (T_C) and heatsink temperature (T_s) is measured on the surface (mounting side) of the baseplate and the heatsink side just under the chips. Refer to the figure to the right for chip location. The heatsink thermal resistance should be measured just under the chips.




Tr1, Tr2: IGBT, Di1, Di2: FWDi
Each mark points to the center position of each chip.

CM1400DUC-24S
Mega Power Dual IGBT
1400 Amperes/1200 Volts

Electrical Characteristics, T_j = 25°C unless otherwise specified

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Collector-Emitter Cutoff Current	I_{CES}	$V_{CE} = V_{CES}$, V_{GE} = 0V	—	—	1	mA
Gate-Emitter Leakage Current	I_{GES}	$V_{GE} = V_{GES}$, V_{CE} = 0V	—	—	3.0	µA
Gate-Emitter Threshold Voltage	$V_{GE(th)}$	I_C = 140mA, V_{CE} = 10V	5.4	6.0	6.6	Volts
Collector-Emitter Saturation Voltage (Terminal)	$V_{CE(sat)}$	I_C = 1400A, V_{GE} = 15V, T_j = 25°C*6	—	1.55	1.90	Volts
		I_C = 1400A, V_{GE} = 15V, T_j = 125°C*6	—	1.75	—	Volts
		I_C = 1400A, V_{GE} = 15V, T_j = 150°C*6	—	1.80	—	Volts
Collector-Emitter Saturation Voltage (Chip)	$V_{CE(sat)}$	I_C = 1400A, V_{GE} = 15V, T_j = 25°C*6	—	1.55	1.90	Volts
		I_C = 1400A, V_{GE} = 15V, T_j = 125°C*6	—	1.75	—	Volts
		I_C = 1400A, V_{GE} = 15V, T_j = 150°C*6	—	1.80	—	Volts
Input Capacitance	C_{ies}	V_{CE} = 10V, V_{GE} = 0V	—	—	150	nF
Output Capacitance	C_{oes}		—	—	30	nF
Reverse Transfer Capacitance	C_{res}		—	—	2.5	nF
Gate Charge	Q_G	V_{CC} = 600V, I_C = 1400A, V_{GE} = 15V	—	3500	—	nC
Turn-on Delay Time	$t_{d(on)}$	V_{CC} = 600V, I_C = 1400A, V_{GE} = ±15V, R_G = 0Ω, Inductive Load	—	—	900	ns
Rise Time	t_r		—	—	250	ns
Turn-off Delay Time	$t_{d(off)}$		—	—	950	ns
Fall Time	t_f		—	—	350	ns
Emitter-Collector Voltage (Terminal)	V_{EC}*1	I_E = 1400A, V_{GE} = 0V, T_j = 25°C*6	—	1.65	2.10	Volts
		I_E = 1400A, V_{GE} = 0V, T_j = 125°C*6	—	1.65	—	Volts
		I_E = 1400A, V_{GE} = 0V, T_j = 150°C*6	—	1.65	—	Volts
Emitter-Collector Voltage (Chip)	V_{EC}*1	I_E = 1400A, V_{GE} = 0V, T_j = 25°C*6	—	1.65	2.10	Volts
		I_E = 1400A, V_{GE} = 0V, T_j = 125°C*6	—	1.65	—	Volts
		I_E = 1400A, V_{GE} = 0V, T_j = 150°C*6	—	1.65	—	Volts
Reverse Recovery Time	t_{rr}*1	V_{CC} = 600V, I_E = 1400A, V_{GE} = ±15V	—	—	450	ns
Reverse Recovery Charge	Q_{rr}*1	R_G = 0Ω, Inductive Load	—	90	—	µC
Turn-on Switching Energy per Pulse	E_{on}	V_{CC} = 600V, $I_C = I_E$ = 1400A,	—	82.2	—	mJ
Turn-off Switching Energy per Pulse	E_{off}	V_{GE} = ±15V, R_G = 0Ω, T_j = 150°C,	—	260	—	mJ
Reverse Recovery Energy per Pulse	E_{rr}*1	Inductive Load	—	122	—	mJ
Internal Lead Resistance	$R_{CC' + EE'}$	Main Terminals-Chip, Per Switch, T_C = 25°C*4	—	0.286	—	mΩ
Internal Gate Resistance	r_g	Per Switch	—	1.7	—	Ω

*1 Represent ratings and characteristics of the anti-parallel, emitter-to-collector clamp diode.
*4 Case temperature (T_C) and heatsink temperature (T_s) is measured on the surface (mounting side) of the baseplate and the heatsink side just under the chips. Refer to the figure to the right for chip location. The heatsink thermal resistance should be measured just under the chips.
*6 Pulse width and repetition rate should be such as to cause negligible temperature rise.



Tr1, Tr2: IGBT, Di1, Di2: FWDi
Each mark points to the center position of each chip.

CM1400DUC-24S
Mega Power Dual IGBT
1400 Amperes/1200 Volts

Electrical Characteristics, T_j = 25°C unless otherwise specified (continued)

Thermal Resistance Characteristics

Thermal Resistance, Junction to Case*4	$R_{th(j-c)}Q$	Per Inverter IGBT	—	—	16	K/kW
Thermal Resistance, Junction to Case*4	$R_{th(j-c)}D$	Per Inverter Diode	—	—	26	K/kW
Contact Thermal Resistance, Case to Heatsink	$R_{th(c-f)}$	Thermal Grease Applied (Per 1 Module)*7	—	6	—	K/kW

Mechanical Characteristics


Mounting Torque	M_t	Main Terminals, M6 Screw	22	27	31	in-lb
	M_s	Mounting to Heatsink, M6 Screw	22	27	31	in-lb
Creepage Distance	d_s	Terminal to Terminal	24	—	—	mm
		Terminal to Baseplate	33	—	—	mm
Clearance	d_a	Terminal to Terminal	14	—	—	mm
		Terminal to Baseplate	33	—	—	mm
Weight	m		—	1450	—	Grams
Flatness of Baseplate	e_c	On Centerline X, Y*5	-50	—	+100	µm

Recommended Operating Conditons, T_a = 25°C


(DC) Supply Voltage	V_{CC}	Applied Across P-N	—	600	850	Volts
Gate-Emitter Drive Voltage	$V_{GE(on)}$	Applied Across G-Es	13.5	15.0	16.5	Volts
External Gate Resistance	R_G	Per Switch	0	—	2.2	Ω

*4 Case temperature (T_C) and heatsink temperature (T_s) is measured on the surface (mounting side) of the baseplate and the heatsink side just under the chips.
Refer to the figure to the right for chip location.
The heatsink thermal resistance should be measured just under the chips.

*5 Baseplate (mounting side) flatness measurement points (X, Y) are shown in the figure below.




*7 Typical value is measured by using thermally conductive grease of λ = 0.9 [W/(m • K)].




Tr1, Tr2: IGBT, Di1, Di2: FWDi
Each mark points to the center position of each chip.

CM1400DUC-24S
Mega Power Dual IGBT
1400 Amperes/1200 Volts


OUTPUT CHARACTERISTICS (CHIP - TYPICAL)




COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (CHIP - TYPICAL)




COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (CHIP - TYPICAL)




FREE-WHEEL DIODE FORWARD CHARACTERISTICS (CHIP - TYPICAL)




CAPACITANCE VS. V_{CE} (TYPICAL)




HALF-BRIDGE SWITCHING CHARACTERISTICS (TYPICAL)




HALF-BRIDGE SWITCHING CHARACTERISTICS (TYPICAL)



SWITCHING TIME VS. GATE RESISTANCE (TYPICAL)




SWITCHING TIME VS. GATE RESISTANCE (TYPICAL)




CM1400DUC-24S
Mega Power Dual IGBT
1400 Amperes/1200 Volts


REVERSE RECOVERY CHARACTERISTICS (TYPICAL)




REVERSE RECOVERY CHARACTERISTICS (TYPICAL)




GATE CHARGE VS. V_{GE}




HALF-BRIDGE SWITCHING CHARACTERISTICS (TYPICAL)




HALF-BRIDGE SWITCHING CHARACTERISTICS (TYPICAL)



HALF-BRIDGE SWITCHING CHARACTERISTICS (TYPICAL)





TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (MAXIMUM)

