

CMI300-810

Slim Type for IBASE MI810 Mini-ITX Motherboard

Mini-ITX System



Features

- Fanless system supports IBASE MI810F Mini-ITX motherboard
- Onboard Intel® Atom™ Processor N270,1.6GHz
- Available in black color
- One 2.5" HDD drive bay
- Light and small
- 2x USB in front easy for connection
- Rear panel I/O for USB, VGA, DVI, COM, KB/ mouse, LAN and DC-In jack
- HDD status LED bar and power button with LED in the front

Specifications

System Mainboard	MI810F
CPU Type	Intel® Atom™ Processor N270
System Speed	1.6GHz
Memory	2x DDR2 DIMM, Max. 2GB
Construction	Steel
Chassis Color	Black
Front Panel External I/O	Power button, 2x USB ports
Rear Panel External I/O	1x VGA, 1x DVI, 2x COM, 6x USB ports, 2x RJ45 connectors, PS/2 KB/MS connector, audio, DC-in jack
Storage	1x 2.5" HDD drive bay
Power Supply	60W power adaptor
Mounting	Desktop or wall mount
Dimensions	200mm(W) x 200mm(D) x 62mm(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	Non-Operating : 1.0 grms / 5~500Hz / random Operating : 0.25 grms / 5~500Hz / random

Ordering Information

CMI300-810F	Mini-ITX system with MI810F, Intel® Atom™ N270 (1.6GHz) CPU, 1GB DDR2 DIMM, 2.5" 250GB HDD, 60W power adaptor
CMI300-810FC	Chassis for MI810F Mini-ITX, 2.5" HDD holder, 60W power adaptor
CMI300-810FM	Mini-ITX system with MI810F, 2.5" HDD holder, 60W power adaptor

CMI211-6COM

Expandable Type for IBASE Mini-ITX Motherboards

Mini-ITX System



Features

- Mini-ITX system for IBASE Mini-ITX motherboards w/ CPU =< 65W TDP
- Supports up to 6x COM ports with ID394
- With motherboard's I/O shields and extra 2x USB ports
- Supports 1x 2.5" SATA HDD drive bay
- Supports one PCI slot
- Wall mount kit included

Specifications

System Mainboard	IBASE Mini-ITX motherboards
CPU Type	Intel® or AMD with TDP =<65W
Expansion	1x PCI
Chassis Color	Black
Construction	SECC
Front Panel	Power button Reset button Power LED HDD LED 2x USB ports 2x DB9 / DB15 (RS232 / VGA)
Rear Panel	Mini-ITX motherboard I/O shield 4x DB9 / DB15 (RS232 / VGA) PCI expansion slot AC-Inlet
Storage	1x 2.5" HDD drive bay
Power Supply	180W / 250W Flex ATX power supply Input Voltage : 90 ~ 264 Volt Input Frequency : 47 ~ 63 Hz
Mounting	Optional wall mount kit
Dimensions	300mm(W) x 205mm(D) x 72mm(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	Non-Operating : 1.0 grms / 5~500Hz / random Operating : 0.25 grms / 5~500Hz / random

Ordering Information

CMI211-6COM-180	Chassis for Mini-ITX (low power), w/ 6 DB9 ports , 1x PCI slot, 2.5" HDD holder, 180W PSU
CMI211-6COM-250	Chassis for Mini-ITX (low power), w/ 6 DB9 ports , 1x PCI slot, 2.5" HDD holder, 250W PSU

*Use only CPU/heatsink with height fitting the chassis-not touching the chassis top cover.

Remarks: 1. Specifications are subject to change without prior notice.
2. ODM/OEM is available