IP55
SUITABILITY

CPB Series Compact Pendant Stations, Two Button, NEMA 4X

Description	Catalog Number
Single-speed normally open-normally closed without mechanical interlock.	**CPB20**
Single-speed with mechanical interlock between pushbuttons.	**CPB21**
Two-speed with mechanical interlock between pushbuttons.	**CPB22**

Note: Included with product: nylon cord grip and sealing washer (must be installed to achieve NEMA 4X rating).
Indication label pack. Cord dia. range .375–.625 in. (9.5–15.9)
Ambient temperatures: 25°F to 140°F (32°C to 60°C).
Typical applications: Package electric motor hoists. Remote control of machinery.


Contact Ratings, CPB Series

Single-Speed	Voltage	Current
AC	120V	6A
35% PF	240V	3A
DC	125V	1.1A
IND	250V	.55A
Two-Speed	**Voltage**	**Current**
AC	120V	3A
35% PF	240V	1.5A



CPB21

Wiring Diagram CPB2 Series



**Mechanical "floating ball" interlock prevents activating both Pushbuttons simultaneously.*

IP44
SUITABILITY

PBS Series Heavy Duty Pendant Pushbutton Stations, NEMA 3R

Description	Catalog Number
2 button, single speed. 2 button, two speed.	**PBS2** **PBS22**
4 button, single speed. 4 button, two speed.	**PBS4** **PBS42**
6 button, single speed. 6 button, two speed.	**PBS6** **PBS62**
8 button, single speed. 8 button, two speed.	**PBS8** **PBS82**



PBS6


Product Dimensions, PBS Series

Style	A	Approx. Wt. Assembled	Catalog Number
2 button	7.88" (200.0)	2.5 lbs	**PBS2**
4 button	13.69" (347.6)	4.5 lbs	**PBS4**
6 button	18.0" (457.2)	5.5 lbs	**PBS6**
8 button	22.31" (566.7)	7.5 lbs	**PBS8**

Note: Housing: Yellow vinyl rubber.

Contact Interrupting Ratings, PBS Series

Two-Speed Single Break	Voltage	Current
AC	120V	6A
35% PF	240V	3A
DC	125V	.4A
IND	250V	.2A
Single-Speed Double Break	**Voltage**	**Current**
AC	120V	6A
35% PF	240V	3A
DC	125V	1.1A
IND	250V	.55A



Dimensions in Inches (mm)