CPC1927
ISOPLUS™-264 Power Relay

Parameter	Rating	Units
Blocking Voltage	250	V_P
Load Current, T_A=25°C		
With 5°C/W Heat Sink	6.7	A_{rms}
No Heat Sink	2.7	
On-resistance	0.2	Ω
$R_{\theta JC}$	0.30	°C/W


Features

- 100% Solid State
- Compact ISOPLUS-264 Power Package
- Low Thermal Resistance (0.30°C/W)
- 6.7A_{rms} Load Current with 5°C/W Heat Sink
- Low Drive Power Requirements
- Electrically Non-conductive Thermal Pad for Heat Sink Applications
- Arc-Free With No Snubbing Circuits
- 2500V_{rms} Input/Output Isolation
- No EMI/RFI Generation
- Machine Insertable, Wave Solderable

Applications

- Industrial Controls
- Motor Control
- Robotics
- Medical Equipment—Patient/Equipment Isolation
- Instrumentation
  - Multiplexers
  - Data Acquisition
  - Electronic Switching
  - I/O Subsystems
  - Energy Meters
- Transportation Equipment
- Aerospace/Defense

Pin Configuration



Description

Clare and IXYS have combined to bring OptoMOS® technology, reliability and compact size to a new family of high power Solid State Relays.

As part of this family, the CPC1927 single pole normally open (1-Form-A) Solid State Power Relay is rated for up to 6.7A_{rms} continuous load current with a 5ºC/W heat sink.

The CPC1927 employs optically coupled MOSFET technology to provide 2500V_{rms} of input to output isolation. The output is constructed with efficient MOSFET switches and photovoltaic die that use Clare's patented OptoMOS architecture while the input, a highly efficient GaAlAs infrared LED provides the optically coupled control. The combination of low on-resistance and high load current handling capability makes this relay suitable for a variety of high performance switching applications.

The unique ISOPLUS-264 package pioneered by IXYS allows solid state relays to achieve the highest load current and power ratings. This package features a unique IXYS process where the silicon chips are soft soldered onto the Direct Copper Bond (DCB) substrate instead of the traditional copper leadframe. The DCB ceramic, the same substrate used in high power modules, not only provides 2500V_{rms} isolation but also very low thermal resistance (0.3 °C/W).


Approvals

- UL recognized component: File # E69938
- Certified to: UL 508

Ordering Information

Part Number	Description
CPC1927J	ISOPLUS-264 (25 per tube)

Switching Characteristics of Normally Open (Form A) Devices



RoHS 2002/95/EC

e3

Absolute Maximum Ratings

Parameter	Ratings	Units
Blocking Voltage	250	V_P
Reverse Input Voltage	5	V
Input Control Current	100	mA
Peak (10ms)	1	A
Input Power Dissipation	150	mW
Isolation Voltage, Input to Output	2500	V_{rms}
Operational Temperature	-40 to +85	°C
Storage Temperature	-40 to +125	°C

Electrical absolute maximum ratings are at 25°C

Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at conditions beyond those indicated in the operational sections of this data sheet is not implied.

Electrical Characteristics

Parameter	Conditions	Symbol	Min	Typ	Max	Units
Output Characteristics	T_A=25°C					
Load Current [1]						
Peak	t ≤ 10ms	I_L	-	-	25	A_P
Continuous	No Heat Sink				2.7	A_{rms}
Continuous	T_C=25ºC				15	
Continuous	T_C=99ºC	$I_{L(99)}$			3.25	
On-Resistance [2]	I_F=10mA, I_L=1A	R_{ON}	-	0.15	0.2	Ω
Off-State Leakage Current	V_L=250V	I_{LEAK}	-	-	1	µA
Switching Speeds						
Turn-On	I_F=20mA, V_L=10V	T_{ON}	-	12	25	ms
Turn-Off		T_{OFF}	-	0.22	10	
Output Capacitance	V=25V, f=1MHz	C_{OUT}	-	1100	-	pF
Input Characteristics	T_A=25°C					
Input Control Current [3]	I_L=1A	I_F	-	-	10	mA
Input Dropout Current	-	I_F	0.6	-	-	mA
Input Voltage Drop	I_F=5mA	V_F	0.9	1.2	1.4	V
Reverse Input Current	V_R=5V	I_R	-	-	10	µA
Common Characteristics	T_A=25°C					
Capacitance Input to Output	-	$C_{I/O}$	-	1	-	pF

[1] Higher load currents are possible with proper heat sinking.
[2] Measurement taken within 1 second of on time.
[3] For applications requiring high temperature operation (greater than 60ºC) an LED drive current of 20mA is recommended.

Thermal Characteristics

Parameter	Conditions	Symbol	Min	Typ	Max	Units
Thermal Resistance (junction to case)	-	$R_{\theta JC}$	-	-	0.3	°C/W
Thermal Resistance (junction to ambient)	Free air	$R_{\theta JA}$	-	33	-	°C/W
Junction Temperature (operation)	-	T_J	-40	-	100	°C

Thermal Management

Device high current characterization was performed using Kunze heat sink KU 1-159, phase change thermal interface material KU-ALC 5, and transistor clip KU 4-499/1. This combination provided an approximate junction-to-ambient thermal resistance of 12.5°C/W.

Heat Sink Calculation

Higher load currents are possible by using lower thermal resistance heat sink combinations.

Heat Sink Rating


$$R_{\theta CA} = \frac{(T_J - T_A)\, I_{L(99)}^{2} \cdot R_{\theta JC}}{I_L^{2}} - R_{\theta JC}$$

T_J = Junction Temperature (°C), $T_J \leq 100°C$ *
T_A = Ambient Temperature (°C)
$I_{L(99)}$ = Load Current with Case Temperature @ 99°C (A_{rms})
I_L = Desired Operating Load Current (A_{rms}), $I_L \leq I_{L(MAX)}$
$R_{\theta JC}$ = Thermal Resistance, Junction to Case (°C/W) = 0.3°C/W
$R_{\theta CA}$ = Thermal Resistance of Heat Sink & Thermal Interface Material , Case to Ambient (°C/W)


* Elevated junction temperature reduces semiconductor lifetime.

PERFORMANCE DATA*


CPC1927
Typical LED Forward Voltage Drop
(N=50, T_A=25°C, I_L=1A_{DC}, I_F=10mA)




CPC1927
Typical On-Resistance Distribution
(N=50, T_A=25°C, I_L=1A_{DC}, I_F=10mA)




CPC1927
Typical Turn-On Time
(N=50, T_A=25°C, I_L=1A_{DC}, I_F=20mA)




CPC1927
Typical Turn-Off Time
(N=50, T_A=25°C, I_L=1A_{DC}, I_F=20mA)




CPC1927
Typical Blocking Voltage Distribution
(T_A=25°C)




CPC1927
Maximum Load Current
vs. Temperature with Heat Sink
(I_F=20mA)




CPC1927
Typical Leakage vs. Temperature
at Maximum Rated Voltage
(Measured Across Pins 1 & 2)




CPC1927
Blocking Voltage vs. Temperature




CPC1927
Typical Turn-On vs. Temperature
(I_L=1A_{DC})




CPC1927
Typical Turn-Off vs. Temperature
(I_L=1A_{DC})



CPC1927
Typical LED Forward Voltage Drop
vs. Temperature



CPC1927
Typical Turn-On vs. LED Forward Current
(I_L=1A_{DC})




*The Performance data shown in the graphs above is typical of device performance. For guaranteed parameters not indicated in the written specifications, please contact our application department.


Unless otherwise specified, all performance data was acquired without the use of a heatsink.

PERFORMANCE DATA*


CPC1927
Typical Turn-Off vs. LED Forward Current
(I_L=1A_{DC})




CPC1927
Typical I_F for Switch Operation vs. Temperature
(I_L=1A_{DC})




CPC1927
Typical On-Resistance vs. Temperature
(I_L=1A_{DC})



CPC1927
Typical Load Current vs. Load Voltage
(T_A=25°C, I_F=10mA)



CPC1927
Energy Rating Curve
(Free Air, No Heat Sink)



*The Performance data shown in the graphs above is typical of device performance. For guaranteed parameters not indicated in the written specifications, please contact our application department.

Unless otherwise specified, all performance data was acquired without the use of a heatsink.

Manufacturing Information

Soldering

For proper assembly, the component must be processed in accordance with the current revision of IPC/JEDEC standard J-STD-020. Failure to follow the recommended guidelines may cause permanent damage to the device resulting in impaired performance and/or a reduced lifetime expectancy.

Washing


Clare does not recommend ultrasonic cleaning or the use of chlorinated solvents.

RoHS 2002/95/EC

e3

MECHANICAL DIMENSIONS:

ISOPLUS-264 Package



NOTE: Bottom heat sink meets 2500V_{rms} isolation to the pins.

For additional information please visit our website at: www.clare.com

Clare, Inc. makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Neither circuit patent licenses nor indemnity are expressed or implied. Except as set forth in Clare's Standard Terms and Conditions of Sale, Clare, Inc. assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including, but not limited to, the implied warranty of merchantability, fitness for a particular purpose, or infringement of any intellectual property right.

The products described in this document are not designed, intended, authorized or warranted for use as components in systems intended for surgical implant into the body, or in other applications intended to support or sustain life, or where malfunction of Clare's product may result in direct physical harm, injury, or death to a person or severe property or environmental damage. Clare, Inc. reserves the right to discontinue or make changes to its products at any time without notice.

DS-CPC1927-R01
©Copyright 2007, Clare, Inc.
OptoMOS® is a registered trademark of Clare, Inc.
ISOPLUS™ is a trademark of IXYS Corporation
All rights reserved. Printed in USA.
11/6/07