
cPCIS-2642/cPCIS-2842

Dual 3U CompactPCI® Subsystem with two 6-slot Backplanes and two CompactPCI® Power Modules


Features

- Dual 3U CompactPCI® systems, each with five peripheral slots and one system slot
- 1/1 250 W CompactPCI® Power supplies
- Temperature, voltage, and fan monitoring LEDs
- Supports current sharing on +5 V, +3.3 V, and +12 V
- PICMG® 2.11 47-pin power interface
- Hot-swappable cooling fans & filter
- Supports rear I/O backplane with P2 connectors for cPCI 50mm/80mm depth RTMs





cPCIS-2642R/cPCIS-2842R Inside Front View



cPCIS-2642R/cPCIS-2842R Inside Rear View

Ordering Information

Model Name	Segment	System	Peripheral	Rear	Alarm Module	PSU QTY	PSU MAX	PICMG®
cPCIS-2642/cPCIS-2842	2	1/1	5/5	1/1 *system slot only	Yes	1/1	250 W	2.0, 2.1, 2.11
cPCIS-2642R/cPCIS-2842R	2	1/1	5/5	6/6	Yes	1/1	250 W	2.0, 2.1, 2.11

Note: All models above do not include any system or peripheral boards.

cPCIS-1100A/1102

3U Enclosure with 32-bit Backplane and ATX/CompactPCI® Redundant Power Supply

Features

- 3U CompactPCI® single system, seven peripheral slot configuration or dual system, five peripheral slot configuration
- Equipped with single PS/2 form factor 400 W ATX power supply or CompactPCI® redundant power supply (Max. output 500 W)
- Suitable for both rackmount and desktop applications
- Comprehensive EMC shielding
- Optional rear I/O configuration (cPCI 50mm depth RTMs)



Specifications

CompactPCI® Standard

2.0 R3.0, 2.1 R2.0
Form Factor: 3U cPCI
Enclosure: 19" 3U rackmount enclosure

Power Supply

Optional industrial grade ATX power supply or PICMG® 2.11 47-pin 3U cPCI power module(s), dependent on subsystem configuration

Backplane

3U backplane(s), model dependent on subsystem configuration
Dimensions: 482.56 x 133.35 x 250.0 mm (W x H x D)

Certifications

DIN IEC 68-2-6 test FC
DIN IEC 68-2-27 test Ea
DIN41 494, part 5
IEC 60297-3, EIA 310-D

Ordering Information

Model Name	Segment	System	Peripheral	Rear	PSU QTY	PSU MAX	PICMG®
Single System, 400W ATX Power Supply							
cPCIS-1100A	1	1	7	1 *system slot only	1*	400 W	2.0, 2.1
cPCIS-1100AR	1	1	7	8	1*	400 W	2.0, 2.1
Single System, 250W x 2 CompactPCI® Power Supplies							
cPCIS-1102	1	1	7	1 *system slot only	2*	500 W (250 W x2)	2.0, 2.1, 2.11
cPCIS-1102R	1	1	7	8	2*	500 W (250 W x2)	2.0, 2.1, 2.11

Notes: 1. External cooling fan is required.
2. Power Supply Module description: • 1*: Universal Auto Switching 400 W Power Supply • 2*: CompactPCI® redundant power supply x2 (500 W)
3. All models above do not include any system or peripheral boards.
4. DC input models available for OEM programs.

All products and company name listed are trademarks or trade names of their respective companies.
Updated Mar. 10, 2017. ©2017 ADLINK Technology, Inc. All Rights Reserved.
All specifications are subject to change without further notice.