cPCIS-ET1100 Series

3U Enclosure with 32-bit Backplane and Wide Temperature Range CompactPCI® Redundant Power Supply

Features

- EN50155-Compliant Transportation Platforms
- 3U CompactPCI® single system, seven peripheral slot configuration
- Equipped with wide temperature range CompactPCI® redundant power supply (Max. output 500 W)
- Suitable for both rackmount and desktop applications
- Comprehensive EMC shielding
- Optional rear I/O configuration (cPCI 50mm depth RTMs)
- cPCI power supply support wide range temperature operation from -20°C to +70°C (-20°C to +50°C at full load with at least 400LFM air flow, power efficiency derating linearly to 50% at +70°C.)



Specifications

CompactPCI® Standard
2.0 R3.0, 2.1 R2.0
Form Factor: 3U cPCI
Enclosure: 19" 3U rackmount enclosure

Power Supply
PICMG® 2.11 47-pin 3U cPCI power module(s), dependent on subsystem configuration

Backplane
3U backplane(s), model dependent on subsystem configuration
Dimensions: 482.56 x 133.35 x 250.0 mm (W x H x D)

Certifications
DIN IEC 68-2-6 test FC
DIN IEC 68-2-27 test Ea
DIN41 494, part 5
IEC 60297-3, EIA 310-D

Ordering Information

Model name	Description
	Single System with 250W CompactPCI® Power Supply
cPCIS-ET1101	3U cPCI Rackmount & Portable subsystem w/ 3U encloure with 32-bit 8-slot BP and 1 ETT PSU, EN 50155 Compliance
cPCIS-ET1102	3U cPCI Sub-system with 3U Enclosure. 32-bit 8-slot B/P, cBP-3062A and two ETT 3U RPSUs
cPCIS-ET1102R	3U cPCI Sub-system with 3U Enclosure. 32-bit 8-slot B/P support rear IO, cBP-3062A and two ETT 3U RPSUs

cPCIS-1202 Series

3U Enclosure with 32-bit Backplane and CompactPCI® Redundant Power Supply

Features

- Dual 3U CompactPCI® systems, each with five peripheral slots and one system slot
- 1/1 250 W CompactPCI® Power supplies
- Suitable for both rackmount and desktop applications
- Comprehensive EMC shielding
- Optional rear I/O configuration (cPCI 50mm depth RTMs)



EN 50155 Compliant

Specifications

CompactPCI® Standard

2.0 R3.0, 2.1 R2.0
Form Factor: 3U cPCI
Enclosure: 19" 3U rackmount enclosure

Power Supply

PICMG® 2.11 47-pin 3U cPCI power module(s), dependent on subsystem configuration

Backplane

3U backplane(s), model dependent on subsystem configuration
Dimensions: 482.56 x 133.35 x 250.0 mm (W x H x D)

Certifications

DIN IEC 68-2-6 test FC
DIN IEC 68-2-27 test Ea
DIN41 494, part 5
IEC 60297-3, EIA 310-D

Ordering Information

Model Name	Segment	System	Peripheral	Rear	PSU QTY	PSU MAX	PICMG®
Dual System with CompactPCI® Power Supply							
cPCIS-1202	2	1/1	5/5	1/1 *system slot only	1/1*	250 W	2.0, 2.1, 2.11
cPCIS-1202R	2	1/1	5/5	6/6	1/1*	250 W	2.0, 2.1, 2.11

Notes: 1. External cooling fan is required.
2. Power Supply Module description: 1/1 = One power supply per segment
3. All models above do not include any system or peripheral boards. 4. DC input models available for OEM programs.

ADLINK Leading EDGE COMPUTING

www.adlinktech.com

All products and company name listed are trademarks or trade names of their respective companies.
Updated Mar. 10, 2017. ©2017 ADLINK Technology, Inc. All Rights Reserved.
All specifications are subject to change without further notice.