CPH3455

Power MOSFET
35V, 104mΩ, 3A, Single N-Channel

ON Semiconductor®

www.onsemi.com

This Power MOSFET is produced using ON Semiconductor's trench technology, which is specifically designed to minimize gate charge and low on resistance. This device is suitable for applications with low gate charge driving or low on resistance requirements.

Features

- Low On-Resistance
- 4V drive
- Pb-Free, Halogen Free and RoHS compliance

Typical Applications

- Load Switch
- Motor Drive

V_{DSS}	R_{DS}(on) Max	I_D Max
35V	104mΩ@ 10V	3A
	173mΩ@ 4.5V	
	208mΩ@ 4V	

ELECTRICAL CONNECTION
N-Channel



PACKING TYPE : TL



MARKING



ORDERING INFORMATION

See detailed ordering and shipping information on page 5 of this data sheet.

SPECIFICATIONS

ABSOLUTE MAXIMUM RATING at Ta = 25°C (Note 1, 2)

Parameter	Symbol	Value	Unit
Drain to Source Voltage	V_{DSS}	35	V
Gate to Source Voltage	V_{GSS}	±20	V
Drain Current (DC)	I_D	3	A
Drain Current (Pulse) PW ≤ 10μs, duty cycle ≤ 1%	I_{DP}	12	A
Power Dissipation When mounted on ceramic substrate (900mm^2 × 0.8mm)	P_D	1	W
Junction Temperature	Tj	150	°C
Storage Temperature	Tstg	−55 to +150	°C

Note 1 : Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

2 : This product is designed to "ESD immunity<200V*", so please take care when handling.

*Machine Model

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Value	Unit
Junction to Ambient When mounted on ceramic substrate (900mm^2 × 0.8mm)	$R_{\theta JA}$	125	°C/W

© Semiconductor Components Industries, LLC, 2015

ELECTRICAL CHARACTERISTICS at Ta = 25°C (Note 3)

Parameter	Symbol	Conditions	Value			Unit
			min	typ	max	
Drain to Source Breakdown Voltage	$V_{(BR)DSS}$	I_D=1mA, V_{GS}=0V	35			V
Zero-Gate Voltage Drain Current	I_{DSS}	V_{DS}=35V, V_{GS}=0V			1	μA
Gate to Source Leakage Current	I_{GSS}	V_{GS}=±16V, V_{DS}=0V			±10	μA
Gate Threshold Voltage	$V_{GS}(th)$	V_{DS}=10V, I_D=1mA	1.2		2.6	V
Forward Transconductance	g_{FS}	V_{DS}=10V, I_D=1.5A		1.7		S
Static Drain to Source On-State Resistance	$R_{DS}(on)1$	I_D=1.5A, V_{GS}=10V		80	104	mΩ
	$R_{DS}(on)2$	I_D=0.75A, V_{GS}=4.5V		123	173	mΩ
	$R_{DS}(on)3$	I_D=0.75A, V_{GS}=4V		148	208	mΩ
Input Capacitance	Ciss	V_{DS}=20V, f=1MHz		186		pF
Output Capacitance	Coss			36		pF
Reverse Transfer Capacitance	Crss			22		pF
Turn-ON Delay Time	$t_d(on)$	See specified Test Circuit		4.2		ns
Rise Time	t_r			4.7		ns
Turn-OFF Delay Time	$t_d(off)$			15		ns
Fall Time	t_f			5.7		ns
Total Gate Charge	Qg	V_{DS}=20V, V_{GS}=10V, I_D=3A		4		nC
Gate to Source Charge	Qgs			0.9		nC
Gate to Drain “Miller” Charge	Qgd			0.7		nC
Forward Diode Voltage	V_{SD}	I_S=3A, V_{GS}=0V		0.86	1.2	V

Note 3 : Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Switching Time Test Circuit




ID – VDS
Ta=25°C
8.0V
10.0V
16.0V
6.0V
4.5V
4.0V
VGS=3.0V
Drain Current, ID – A
Drain to Source Voltage, VDS – V
IT16442


ID – VGS
VDS=10V
Ta=75°C
25°C
–25°C
Drain Current, ID – A
Gate to Source Voltage, VGS – V
IT16443


RDS(on) – VGS
Ta=25°C
ID=0.75A
1.5A
Static Drain to Source On-State Resistance, RDS(on) – mΩ
Gate to Source Voltage, VGS – V
IT16444


RDS(on) – Ta
VGS=4V, ID=0.75A
VGS=4.5V, ID=0.75A
VGS=10V, ID=1.5A
Static Drain to Source On-State Resistance, RDS(on) – mΩ
Ambient Temperature, Ta – °C
IT16445


gFS – ID
VDS=10V
Ta= –25°C
75°C
25°C
Forward Transconductance, gFS – S
Drain Current, ID – A
IT16446


IS – VSD
VGS=0V
Ta=75°C
25°C
–25°C
Source Current, IS – A
Forward Diode Voltage, VSD – V
IT16447


SW Time – ID
VDD=15V
VGS=10V
td(off)
tf
tr
td(on)
Switching Time, SW Time – ns
Drain Current, ID – A
IT16519


Ciss, Coss, Crss – VDS
f=1MHz
Ciss
Coss
Crss
Ciss, Coss, Crss – pF
Drain to Source Voltage, VDS – V
IT16449


VGS – Qg
VDS=20V
ID=3A
Gate to Source Voltage, VGS – V
Total Gate Charge, Qg – nC
IT16450


S O A
IDP=12A (PW≤10μs)
ID=3A
100μs
1ms
10ms
100ms
DC operation (Ta=25°C)
Operation in this area
is limited by RDS(on).
Ta=25°C
Single pulse
When mounted on ceramic substrate (900mm2×0.8mm)
Drain Current, ID – A
Drain to Source Voltage, VDS – V
IT16451


PD – Ta
When mounted on ceramic substrate
(900mm2×0.8mm)
Power Dissipation, PD – W
Ambient Temperature, Ta – °C
IT16452


RθJA – Pulse Time
Duty Cycle=0.5
0.2
0.1
0.05
0.02
0.01
Single Pulse
When mounted on ceramic substrate
(900mm2×0.8mm)
Thermal Resistance, RθJA – °C/W
Pulse Time, PT – s
IT17923

PACKAGE DIMENSIONS

unit : mm

CPH3
CASE 318BA
ISSUE O





1 : Gate
2 : Source
3 : Drain

Recommended Soldering Footprint



ORDERING INFORMATION

Device	Marking	Package	Shipping (Qty / Packing)
CPH3455-TL-H	LM	CPH3 SC-59, SOT-23, TO-236 (Pb-Free / Halogen Free)	3,000 / Tape & Reel
CPH3455-TL-W			

† For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D. http://www.onsemi.com/pub_link/Collateral/BRD8011-D.PDF

Note on usage : Since the CPH3455 is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.