

LTCC Coupler

50Ω 2400 to 2500 MHz 6dB Coupling

CPJC-6-252R+



CASE STYLE: JC0603C

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications



Available Tape and Reel at no extra cost

Reel Size	Devices/Reel
7"	20, 50, 100, 200, 500, 1000, 4000

Maximum Ratings

Operating Temperature -40°C to 85°C

Storage Temperature* -40°C to 85°C


*Refer to product storage temperature after installation.
Suggestion for T&R unused product storage condition: +5--+35°C,
Humidity 45-75%RH, 12 Month max.
Permanent damage may occur if any of these limits are exceeded.

Pad Connections

Input	1
GND	2
Coupled	3
Termination	4
GND	5
Output	6

Outline Drawing

PCB Land Pattern




Outline Dimensions (inch)

A	B	C	D	E	F
.063	.031	.024	.012	.008	.006
1.60	0.79	0.61	0.30	0.20	0.15

G	H	J	K	wt
.020	.010	.022	.053	grams
0.51	0.25	0.56	1.35	0.005

Evaluation Board MCL P/N: TB-1031+ Suggested PCB Layout (PL-572)



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

Features

- miniature size 0603
- low cost
- aqueous washable

Applications

- ISM Band
- WLAN
- Bluetooth
- Zigbee




Electrical Specifications at 25°C

Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Frequency Range		2400		2500	MHz
Mainline Loss	2400 - 2500	—	1.27	1.83	dB
Coupling	2400 - 2500	—	6.5±1.0	—	dB
Directivity	2400 - 2500	13.5	18	—	dB
Return Loss (Input)	2400 - 2500	13.9	21	—	dB
Return Loss (Output)	2400 - 2500	13.9	21	—	dB
Input Power ¹	2400 - 2500	—	—	2	W


1. Derate linearly to 1W at 85°C.

Typical Performance Data

Frequency (GHz)	Mainline Loss (dB) In-Out	Coupling (dB) In-Cpl	Directivity (dB)	Return Loss (dB)		
				In	Out	Cpl
2.400	1.20	6.70	18.45	24.38	22.52	13.91
2.411	1.21	6.67	18.53	24.46	22.52	13.97
2.420	1.22	6.64	18.59	24.59	22.56	14.02
2.432	1.23	6.61	18.63	24.70	22.58	14.09
2.441	1.23	6.58	18.72	24.82	22.67	14.14
2.450	1.24	6.56	18.77	24.85	22.70	14.20
2.461	1.25	6.53	18.84	24.93	22.78	14.25
2.470	1.26	6.51	18.89	25.03	22.80	14.31
2.482	1.27	6.48	18.99	25.13	22.87	14.38
2.491	1.27	6.45	19.04	25.22	22.91	14.41
2.500	1.28	6.43	19.08	25.26	22.92	14.45



Electrical Schematic



* ELECTRICAL SCHEMATIC FOR DIRECTIONAL COUPLER THAT IS DESIGNED WITHOUT INTERNAL TRANSFORMERS.



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. OR
M172548
CPJC-6-252R+
SL/CP/AM
190424
Page 1 of 1