CHINA
SEMICONDUCTOR
CORPORATION

Spec. No.	PS-ND-08090202
Rev.	A

PRODUCT SPECIFICATION

Model No：CSQ-2842B7/2841B7

Descriptions:

- 0.28 Inch Quad Digit Display
- CSQ-2842: Common Anode
- CSQ-2841: Common Cathode
- Emitting Color：Super Bright Blue

CUSTOMER APPROVED SIGNATURES	APPROVED BY	CHECKED BY	PREPARED BY

CHINA SEMICONDUCTOR CORPORATION
Address:2FL. NO.909,Chung-Cheng Road,
Chung-Ho City Taipei Hsien,Taiwan.

Tel:886-2-2223-9696
Fax:886-2-2223-9377

OPTO PLUS TECHNOLOGIES CO.,LTD
Address:696 Shun jiang Rd.,Ji Shan St.Shaoxing,
ZheJiang,China

Tel:86-0575-88623888
Fax:86-0575-88623112

http://www.csctw.com.tw

Model No：CSQ-2842/2841B7


■ Features -

1. 0.28 inch (7.0mm) digit height.
2. Case mold type.
3. RoHS compliant.
4. Low power consumption.
5. Easy mounting on P.C. board or socket.

■ Device Selection Guide -

Part No.	Chip		Description
	Material	Emitted Color	
CSQ-2842B7	InGaN	Super Bright Blue	Common Anode
CSQ-2841B7	InGaN	Super Bright Blue	Common Cathode


■ Package Dimensions -




NOTE:
1. All pins are ø0.45 [.02"].
2. Dimension in millimeter (inch), and tolerance is ±0.25 [.01] unless otherwise noted.

Model No：CSQ-2842/2841B7

■ Internal Circuit Diagrams -





CSQ-2842 Common Anode
(CSQ-2841 Common Cathode)

■ Absolute Maximum Rating -

(Ta=25℃)

Parameter	Symbol	Rating	Unit
Power Dissipation Per Dice	P_{AD}	120	mW
Continuous Forward Current Per Dice	I_{AF}	30	mA
Peak Current Per Dice(duty cycle 1/10, 1kHz)	I_{PF}	100	mA
Derating Linear From 25℃ Per Dice	-	0.4	mA/℃
Reverse Voltage Per Dice	V_R	5	V
Operating Temp.	Topr	-35 ~ +85	℃
Storage Temp.	Tstg	-35 ~ +85	℃
Solder temperature 1/16 inch below seating plane for 3 seconds at 260℃			

Model No：CSQ-2842/2841B7

■ Electro-optical Characteristics -

(Ta=25℃)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Forward Voltage Per Segment	V_F	-	3.5	4	V	I_F=20mA
Luminous Intensity Per Segment	Iv	5	12	-	mcd	I_F=10mA
Peak Emission Wavelength	λp	-	468	-	nm	I_F=20mA
Dominant Wavelength	λd	-	470	-	nm	I_F=20mA
Spectrum Radiation Bandwidth	$\Delta \lambda$	-	30	-	nm	I_F=20mA
Reverse Current	IR	-	-	100	μA	V_R=5V
Luminous Intensity Matching Ratio	IV-m	-	-	2:1	-	I_F=10mA

Model No: CSQ-2842/2841B7

■ Typical Electrical / Optical Charateristics Curves -

(Ta = 25℃ Unless Otherwise Noted)




Fig.1 FORWARD CURRENT VS. FORWARD VOLTAGE




Fig.2 RELATIVE INTENSITY VS. WAVELENGTH




Fig.3 RELATIVE INTENSITY
VS. FORWARD CURRENT




Fig.4 RELATIVE INTENSITY VS.LEAD TEMPERATURE
(PULSED 20 mA; 300us
PULSE,10ms PERIOD)




Fig.5 FORWARD CURRENT
VS. AMBIENT TEMPERATURE






Fig.6 PEAK FORWARD VOLTAGE
VS.FORWARD(100us TEST PULSE,
1% DUTY CYCLE)


Model No：CSQ-2842/2841B7

■ Package Dimensions






15 Pcs Per Tube



90 Tubes Per Inner Box

Total Q'TY: 1350 Pcs



3 Inner Boxes Per Carton.

Total Q'TY: 4050 Pcs

Carton Size:
L540*W485*H305.5 mm