CHINA
SEMICONDUCTOR
CORPORATION

Spec. No.	PS-ND-08090206
Rev.	A

PRODUCT SPECIFICATION

Model No：CSQ-2842S/2841S

Descriptions:

- 0.28 Inch Quad Digit Display
- CSQ-2842: Common Anode
- CSQ-2841: Common Cathode
- Emitting Color：Super Bright Red

CUSTOMER APPROVED SIGNATURES	APPROVED BY	CHECKED BY	PREPARED BY

CHINA SEMICONDUCTOR CORPORATION
Address:2FL. NO.909,Chung-Cheng Road,
Chung-Ho City Taipei Hsien,Taiwan.

Tel:886-2-2223-9696
Fax:886-2-2223-9377

OPTO PLUS TECHNOLOGIES CO.,LTD
Address:696 Shun jiang Rd.,Ji Shan St.Shaoxing,
ZheJiang,China

Tel:86-0575-88623888
Fax:86-0575-88623112

http://www.csctw.com.tw

Model No：CSQ-2842/2841S


■ Features -


1. 0.28 inch (7.0mm) digit height.
2. Case mold type.
3. RoHS compliant.
4. Low power consumption.
5. Easy mounting on P.C. board or socket.

■ Device Selection Guide -

Part No.	Chip		Description
	Material	Emitted Color	
CSQ-2842S	AlGaAs	Super Bright Red	Common Anode
CSQ-2841S	AlGaAs	Super Bright Red	Common Cathode

■ Package Dimensions -






NOTE:
1. All pins are ø0.45 [.02"].
2. Dimension in millimeter (inch), and tolerance is ±0.25 [.01] unless otherwise noted.

Model No：CSQ-2842/2841S

■ Internal Circuit Diagrams -



CSQ-2842 Common Anode
(CSQ-2841 Common Cathode)

■ Absolute Maximum Rating -

(Ta=25℃)

Parameter	Symbol	Rating	Unit
Power Dissipation Per Dice	P_{AD}	75	mW
Continuous Forward Current Per Dice	I_{AF}	30	mA
Peak Current Per Dice (duty cycle 1/10, 1kHz)	I_{PF}	120	mA
Derating Linear From 25℃ Per Dice	-	0.42	mA/℃
Reverse Voltage Per Dice	V_R	5	V
Operating Temp.	Topr	-35 ~ +85	℃
Storage Temp.	Tstg	-35 ~ +85	℃
Solder temperature 1/16 inch below seating plane for 3 seconds at 260℃			

Model No：CSQ-2842/2841S

■ Electro-optical Characteristics -

(Ta=25℃)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Forward Voltage Per Segment	V_F	-	1.8	2.5	V	I_F=20mA
Luminous Intensity Per Segment	Iv	2400	6000	-	ucd	I_F=10mA
Peak Emission Wavelength	λp	-	660	-	nm	I_F=20mA
Dominant Wavelength	λd	-	644	-	nm	I_F=20mA
Spectrum Radiation Bandwidth	$\Delta \lambda$	-	20	-	nm	I_F=20mA
Reverse Current	IR	-	-	100	μA	V_R=5V
Luminous Intensity Matching Ratio	IV-m	-	-	2:1	-	I_F=10mA

Model No：CSQ-2842/2841S

■ Typical Electrical / Optical Charateristics Curves -

(Ta = 25℃ Unless Otherwise Noted)




Fig.1 FORWARD CURRENT VS. FORWARD VOLTAGE




Fig.2 SPECTRAL RESPONSE




Fig.3 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




Fig.5 LUMINOUS INTENSITY VS. DUTY CYCLE




Fig.4 MAXIMUM ALLOWABLE DC CURRENT PER SEGMENT VS. A FUNCTION OF AMBIENT TEMPERATURE






Fig.6 MAX PEAK CURRENT VS. DUTY CYCLE % (REFRESH RATE f=1 KHz)


Model No：CSQ-2842/2841S

■ Package Dimensions






15 Pcs Per Tube



90 Tubes Per Inner Box

Total Q'TY: 1350 Pcs



3 Inner Boxes Per Carton.

Total Q'TY: 4050 Pcs

Carton Size:
L540*W485*H305.5 mm