

Sales Region	Worldwide (except Japan)
Series	CSS
Model	CSS150
Status	 Production
Feature	2MOOP Medical certification
Options	Dual input fuses
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	
Brand	TDK-Lambda



Electrical Characteristics	
Input	Single-phase
Input Voltage Range[AC]	90 to 264Vac
Input Voltage Range[DC]	120 to 180Vdc
Efficiency	89% Typ.
Rated Output Voltage[DC]	36Vdc
Output Voltage Range[DC]	34.92 to 37.08Vdc
Maximum Output Current	4.2A
Maximum Output Power	150W

Package Type & Size	
Package / Mounting	Open frame
Industry Standard Size	3x5 inch size
Width(W)	127mm Nom. (5.00in Nom.)
Height(H)	33mm Nom. (1.30in Nom.)
Depth(D)	76.2mm Nom. (3.00in Nom.)
Weight	340g Typ. (0.7lbs Typ.)

Other	
Operating Temp. Range	0 to 70°C
Cooling	Forced air Convection

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Safety Standard(Certified)	IEC60601-1
	CSA60601-1
	EN60601-1
	ES60601-1
	UL60601-1
	IEC60950-1
	CSA60950-1
	EN60950-1
Safety Standard(Conformed)	UL60950-1
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.