

**N-Channel Enhancement MOSFET****Features**



- Drain-Source Breakdown Voltage V_{DS} 20 V
- Drain-Source On-Resistance
 - $R_{DS(ON)}$ 22m Ω , at V_{GS} = 4.5V, I_{DS} = 4.0A
 - $R_{DS(ON)}$ 27m Ω , at V_{GS} = 2.5V, I_{DS} = 3.0A
- Continuous Drain Current at $T_A=25^{\circ}\text{C}$ I_D = 4.0A
- Advanced high cell density Trench Technology
- RoHS Compliance & Halogen Free

Applications

- Power Management
- Lithium Ion Battery

Description

The CT2300-R3 uses high performance Trench Technology to provide excellent $R_{DS(ON)}$ and low gate charge which is suitable for most of the synchronous buck converter applications .

Package Outline**Schematic**

**CT2300-R3****N-Channel Enhancement MOSFET****Absolute Maximum Rating at 25°C**

Symbol	Parameters	Ratings	Units	Notes
V_{DS}	Drain-Source Voltage	20	V	
V_{GS}	Gate-Source Voltage	± 12	V	
I_D	Continuous Drain Current @ $T_A=25^\circ\text{C}$	4.0	A	1
I_{DM}	Pulsed Drain Current	13.5	A	1
P_D	Total Power Dissipation @ $T_A=25^\circ\text{C}$	1.25	W	2
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ\text{C}$	
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ\text{C}$	

Thermal Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
$R_{\theta JA}$	Thermal Resistance Junction-Ambient ($t=10\text{s}$)		-	175	-	$^\circ\text{C/W}$	1,4



N-Channel Enhancement MOSFET

Electrical Characteristics $T_A = 25^\circ\text{C}$ (unless otherwise specified)

Static Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
$B_{V_{DS}}$	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	20	-	-	V	
I_{DSS}	Drain-Source Leakage Current	$V_{DS}=20V, V_{GS}=0V$	-	-	1	μA	
I_{GSS}	Gate-Source Leakage Current	$V_{GS}=\pm 12V, V_{DS}=0V$	-	-	± 100	nA	

On Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
$R_{DS(ON)}$	Drain-Source On-Resistance	$V_{GS}=4.5V, I_D=4.5A$	-	22	33	m Ω	
		$V_{GS}=2.5V, I_D=4.0A$	-	27	40	m Ω	
$V_{GS(TH)}$	Gate-Source Threshold Voltage	$V_{GS}=V_{DS}, I_D=250\mu A$	0.4	-	1.0	V	

Dynamic Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
C_{ISS}	Input Capacitance	$V_{DS}=10V,$ $V_{GS}=0V,$ $f=1MHz$	-	600	-	pF	
C_{OSS}	Output Capacitance		-	85	-		
C_{RSS}	Reverse Transfer Capacitance		-	75	-		

Switching Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
$T_{D(ON)}$	Turn-On Delay Time	$V_{DS}=10V, V_{GS}=4.5V,$ $R_G=6\Omega, I_D=1A$	-	3.5	-	ns	Fig 11 & 12
T_R	Rise Time		-	23	-		
$T_{D(OFF)}$	Turn-Off Delay Time		-	39	-		
T_F	Fall Time		-	24	-		
Q_G	Total Gate Charge	$V_{DS}=10V, V_{GS}=4.5V,$ $I_D=4.5A$	-	7.5	-	nC	Fig 9 & 10
Q_{GS}	Gate-Source Charge		-	1	-		
Q_{GD}	Gate-Drain (Miller) Charge		-	2	-		




Drain-Source Diode Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
V _{SD}	Body Diode Forward Voltage	V _{GS} = 0V, I _{SD} = 4.0A			1.3	V	
I _{SD}	Body Diode Continuous Current				4.0	A	1

Note:

- 1. The power dissipation is limited by 150°C junction temperature.
- 2. Device mounted on a glass-epoxy board



FR-4
25.4 × 25.4 mm .
2 Oz Copper

Actual Size

- 3. The data tested by pulsed , pulse width ≤ 300μs , duty cycle ≤ 2%
- 4. Thermal Resistance follow JESD51-3.



Typical Characteristic Curves




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5






Figure 6





Test Circuits & Waveforms

Figure 9: Gate Charge Test Circuit




Figure 10: Gate Charge Waveform




Figure 11: Switching Time Test Circuit






Figure 12: Switching Time Waveform






Package Dimension (SC-59)



Note: Dimensions in mm


Recommended pad layout for surface mount leadform



Note: Dimensions in mm



Marking Information




2300 : Device Number

Ordering Information

Part Number	Description	Quantity
CT2300-R3	SC-59 Reel	3000 pcs



Reflow Profile



Profile Feature	Pb-Free Assembly Profile
Temperature Min. (T _{smin})	150 °C
Temperature Max. (T _{smax})	200 °C
Time (t _s) from (T _{smin} to T _{smax})	60-120 seconds
Ramp-up Rate (t _L to t _P)	3 °C/second max.
Liquidous Temperature (T _L)	217 °C
Time (t _L) Maintained Above (T _L)	60 – 150 seconds
Peak Body Package Temperature	260 °C +0 °C / -5 °C
Time (t _P) within 5 °C of 260 °C	30 seconds
Ramp-down Rate (T _P to T _L)	6 °C/second max
Time 25 °C to Peak Temperature	8 minutes max.



DISCLAIMER

CT MICRO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. CT MICRO DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

CT MICROELECTRONICS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT EXPRESS WRITTEN APPROVAL OF CT MICROELECTRONICS LTD.

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instruction for use provided in the labelling, can be reasonably expected to result in significant injury to the user.*
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.*