





Climatherm 305 Series

AIR TO AIR TE EXCHANGER STANDARD PRODUCT
RoHS EU Compliant



MECHANICAL CHARACTERISTICS



TYPICAL PERFORMANCE VALUES

Specifications	
Weight (kg)	4.8
Overtmp Thermostat	100°C ± 5°C (Both Sinks)
Operating Temp	-10°C to 60°C

Electrical Connections		
Color	PIN #	Description
White	1	TEC "+ "
Blue	2	TEC "- "
Red	3	Fans "+ "
Black	4	Fans "- "

Connectors	
Plug	Tyco P/N 480702-0
Socket	Tyco P/N 480703-0
PIN Plug	Tyco P/N 350547-1
PIN Socket	Tyco P/N 350550-1

Available Configurations					
Model Number	Voltage (nom/max)	Current (nom/max)	Cooling Power 0 dT	External Fan Rating	Curve
	V	A	W	dB-A	
CTA305-0001	24/28	7.5/9	143	51	A
CTA305-0002	24/28	10.6/12	185	51	B
CTA305-0003	24/28	14/16	239	58.5	C


IP55 RATED FANS

ORDERING OPTIONS

Model Number	Description
CTA305-0001-01	24V, Hot side wiring
CTA305-0001-02	24V, Cold side wiring
CTA305-0002-01	24V, Hot side wiring
CTA305-0002-02	24V, Cold side wiring
CTA305-0003-01	24V, Hot side wiring
CTA305-0003-02	24V, Cold side wiring

AVAILABLE MODIFICATIONS

For information regarding additional ordering options available, please contact a Marlow engineering representative.



For performance information, consult one of our Applications Engineers.

Installation

Recommended mounting methods: Attach through provided mounting holes with M5 hardware. Mounting template included with product.

Operation Cautions

For maximum reliability, storage and operation below 60°C in a non-condensing environment is recommended.

WARNING: This product contains a chemical known to the state of California to cause cancer, birth defects, or other reproductive harm.

CONTACT US:

For customer support or general questions please contact a local office below or consult our website for distributor information.

Marlow Industries, Inc.
10451 Vista Park Road
Dallas Texas 75238-1645
214-340-4900 (tel)
214-341-5212 (fax)
www.marlow.com

Marlow Industries Europe GmbH
Brunnenweg 19-21
64331 Weiterstadt
Germany
Tel.: +49 (0) 6150 5439 - 403
Fax: +49 (0) 6150 5439 - 400
info@marlow-europe.eu

II-VI Japan Inc.
WBG Marive East 17F
2-6 Nakase, Mihama-ku
Chiba-Shi, Chiba 261-7117
Japan
81 43 297 2693 (tel)
81 43 297 3003 (fax)
center@ii-vi.co.jp
www.ii-vi.co.jp

II-VI Singapore Pte., Ltd.
Blk. 5012, Techplace II
#04-07 & 05-07/12, Ang Mo Kio Ave. 5
Singapore 569876
(65) 6481 8215 (tel)
(65) 6481 8702 (fax)
info@ii-vi.com.sg
www.ii-vi.com.sg

Marlow Industries China, II-VI
Technologies Beijing
A subsidiary of II-VI Incorporated
Rm 202, 1# Lize 2nd Middle Road
Wangjing, Chaoyang District
Beijing 100102 China
010-64398226 ext 105 (tel)
010-64399315 (fax)
info@iivibj.com