Creation Date : September 17, 2020 (GMT)

AC-DC Power Supplies

CUS600M-32 New Product

RoHS

Sales Region	Worldwide (except Japan)
Series	CUS-M
Model	CUS600M
Status	Production
Feature	Peak Load Peak power capability Medical for Medical instruments 2MOPP 2MOPP
Options	
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to the catalog



Electrical Characteristics	
Input	Single-phase
Input Voltage Range[AC]	85 to 265Vac
Input Voltage Range[DC]	
Efficiency	96% Typ.
Rated Output Voltage[DC]	32Vdc
Output Voltage Range[DC]	Fixed
Maximum Output Current	18.8A
Maximum Output Power	601.6W

Package Type & Size	
Package / Mounting	Open frame
Width(W)	127mm Nom. (5.00in Nom.)
Height(H)	37mm Nom. (1.46in Nom.)
Depth(D)	76.2mm Nom. (3.00in Nom.)
Weight	470g Typ. (1.0lbs Typ.)

Other	
Operating Temp. Range	-20 to 70°C
Cooling	Forced air Convection

Safety Standard(Certified)	IEC60601-1 EN60601-1 ES60601-1 UL60601-1 IEC60950-1 EN60950-1 UL60950-1 IEC62368-1 EN62368-1 UL62368-1
Safety Standard(Conformed)	
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.