


Capacitors for Power Electronics (PEC) - Rectangular



FEATURES

- High impulse current rating up to 600 A
- Low self inductance of < 30 nH
- High reliability and life expectancy
- Withstands heavy duty shock and vibration
- Non-polar dielectric
- Dry, resin filled

APPLICATION

- DC linking in industrial and traction drives
- DC filtering in industrial and traction drives
- DC power storage for testing equipment
- Impulse discharge capacitors for magnetizing and welding

QUICK REFERENCE DATA	
DESCRIPTION	VALUE
Rated DC voltage min.	750 V
Rated DC voltage max.	10.0 kV
Capacitance min.	50 μ F
Capacitance max.	20 000 μ F
Technology	Metallized polypropylene film
Dissipation factor ($\tan \delta_0$)	< 2×10^{-4}
Capacitance tolerance	$\pm 5 \%$
Operating temperature (hotspot)	$\theta_{\min.} - 25 \text{ }^{\circ}\text{C}$ $\theta_{\max.} + 80 \text{ }^{\circ}\text{C}$
Inductance	< 100 nH
Lifetime expectancy	250 000 h at U_{NDC} and < 70 $^{\circ}\text{C}$ hotspot
Reliability	100 FIT
Test voltage	Terminal/terminal = $1.5 \times U_{\text{NDC}}$, 10 s; Terminal/case = $2 \times U_{\text{NDC}} + 1000 V_{\text{AC}}$, 60 s
Casing material	Aluminum or stainless steel, antimagnetic
Filling	Resin polyurethane R40
Standards	IEC 61071-1, IEC 61881, and EN 61071-1



TYPE DESCRIPTION												
TYPE	C _N [μF]	VOLTAGE V _{DC}	R _S [mΩ]	R _{th} [K/W]	I _{max.} [A]	I _P [kA]	İ [kA]	LENGTH [mm]	WIDTH [mm]	HEIGHT [mm]	WEIGHT [kg]	DRAWING NO.
DCMKP 0.9/625 μF												
DCMKP 0.9/625 μF	625	900	0.1	0.5	500.0	75	225	340	175	510	40	07-B-1091
DCMKP 0.9/20 mF												
DCMKP 0.9/20 mF	20 000	900	0.1	0.5	500.0	75	225	340	175	510	40	07-B-1091
DCMKP 1.1/9.0 mF												
DCMKP 1.1/9.0 mF	9000	1100	0.8	0.2	100.0	19	58	280	175	480	31	07-B-1132
DCMKP 1.9/2.7 mF												
DCMKP 1.9/2.7 mF	2700	1900	0.7	0.4	190.0	10.5	31.7	340	175	330	26	07-B-1285
DCMKP 1.9/4.0 mF/A												
DCMKP 1.9/4.0 mF/A	4000	1900	0.5	0.2	300.0	15.9	47.6	340	175	505	39	07-B-1170
DCMKP 2.0/4.0 mF												
DCMKP 2.0/4.0 mF	4000	2000	0.4	0.5	230.0	16.1	48.3	455	175	368	38	07-B-1270
DCMKP 2.0/7.25 mF												
DCMKP 2.0/7.25 mF	7250	2000	0.5	0.1	240.0	29.0	87.2	340	175	820	63	07-B-1255
DCMKP 2.05/3.0 mF/B												
DCMKP 2.05/3.0 mF/B	3000	2050	0.6	0.3	320	12.5	37.4	650	175	245	36	07-B-841
DCMKP 2.2/1.4 mF												
DCMKP 2.2/1.4 mF	1400	2200	0.4	0.5	200.0	13.2	39.7	340	175	250	20	07-B-1230
DCMKP 2.8/4.0 mF/2												
DCMKP 2.8/4.0 mF/2	4000	2800	0.3	0.2	560.0	45.5	136.6	1060	175	385	93	07-B-940
DCMKP 3.6/710 μF												
DCMKP 3.6/710 μF	710	3600	0.6	0.5	240.0	11.7	35.0	455	340	175	35	07-B-1150
DCMKP 3.63/1.5 mF/2												
DCMKP 3.63/1.5 mF/2	1500	3630	0.5	0.3	420.0	20.0	28.5	800	170	315	56	07-B-1134
DCMKP 3.75/1.25 mF/T												
DCMKP 3.75/1.25 mF/T	1250	3750	0.5	0.3	250.0	20.7	62.2	680	175	345	54	07-B-1265
DCMKP 4.0/625 μF												
DCMKP 4.0/625 μF	625	4000	0.8	0.7	150.0	10.1	30.2	250	175	450	26	07-B-1311
DCMKP 4.25/2.57 mF/2												
DCMKP 4.25/2.57 mF/2	2570	4250	0.4	0.3	600.0	36.8	11.0	420	175	1140	109	07-B-1222
DCMKP 4.25/2.57 mF/4												
DCMKP 4.25/2.57 mF/4	2570	4250	0.4	0.3	600.0	36.8	11.0	420	175	1140	109	07-B-1222

Notes

- Every voltage, current, capacitance value, casing and terminal design is available on request
- All above listed types are for reference only!



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.