
NEW PRODUCT

DCX53/-16

PNP SURFACE MOUNT TRANSISTOR

Features


- Epitaxial Planar Die Construction
- Complementary NPN Type Available (DCX56)
- Ideally Suited for Automated Assembly Processes
- Ideal for Medium Power Switching or Amplification Applications
- **Lead Free By Design/RoHS Compliant (Note 1)**
- **"Green" Device (Note 2)**



SOT89-3L

Mechanical Data

- Case: SOT89-3L
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Finish — Matte Tin annealed over Copper leadframe (Lead Free Plating). Solderable per MIL-STD-202, Method 208
- Marking & Type Code Information: See Page 3
- Ordering Information: See Page 3
- Weight: 0.072 grams (approximate)



Schematic and Pin Configuration

Maximum Ratings @T_A = 25°C unless otherwise specified

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	-100	V
Collector-Emitter Voltage	V_{CEO}	-80	V
Emitter-Base Voltage	V_{EBO}	-5	V
Peak Pulse Current	I_{CM}	-1.5	A
Continuous Collector Current	I_C	-1	A

Thermal Characteristics

Characteristic	Symbol	Value	Unit
Power Dissipation (Note 3) @ T_A = 25°C	P_D	1	W
Thermal Resistance, Junction to Ambient Air @ T_A = 25°C (Note 3)	$R_{\theta JA}$	125	°C/W
Operating and Storage Temperature Range	T_j, T_{STG}	-55 to +150	°C

Electrical Characteristics @T_A = 25°C unless otherwise specified

Characteristic		Symbol	Min	Typ	Max	Unit	Test Conditions
OFF CHARACTERISTICS (Note 4)							
Collector-Base Breakdown Voltage		$V_{(BR)CBO}$	-100	—	—	V	I_C = -100μA, I_E = 0
Collector-Emitter Breakdown Voltage		$V_{(BR)CEO}$	-80	—	—	V	I_C = -10mA, I_B = 0
Emitter-Base Breakdown Voltage		$V_{(BR)EBO}$	-5	—	—	V	I_E = -10μA, I_C = 0
Collector Cutoff Current		I_{CBO}	—	—	-100 -20	nA μA	V_{CB} = -30V, I_E = 0 V_{CB} = -30V, I_E = 0, T_A = 150°C
Emitter Cutoff Current		I_{EBO}	—	—	-100	nA	V_{EB} = -5V, I_C = 0
ON CHARACTERISTICS (Note 4)							
Collector-Emitter Saturation Voltage		$V_{CE(SAT)}$	—	—	-0.5	V	I_C = -500mA, I_B = -50mA
Base-Emitter Turn-On Voltage		$V_{BE(SAT)}$	—	—	-1.0	V	I_C = -500mA, V_{CE} = -2V
DC Current Gain	DCX53, DCX53-16	h_{FE}	63 40	— —	— —	— —	I_C = -5mA, V_{CE} = -2V I_C = -500mA, V_{CE} = -2V
	DCX53		63	—	250	—	I_C = -150mA, V_{CE} = -2V
	DCX53-16		100	—	250	—	I_C = -150mA, V_{CE} = -2V
SMALL SIGNAL CHARACTERISTICS							
Current Gain-Bandwidth Product		f_T	—	200	—	MHz	I_C = -50mA, V_{CE} = -5V, f = 100MHz
Output Capacitance		C_{obo}	—	—	25	pF	V_{CB} = -10V, f = 1MHz

Notes:
1. No purposefully added lead.
2. Diodes Inc.'s "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.
3. Device mounted on FR-4 PCB; pad layout as shown on page 4 or in Diodes Inc. suggested pad layout document AP02001, which can be found on our website at http://www.diodes.com/datasheets/ap02001.pdf.
4. Measured under pulsed conditions. Pulse width = 300μs. Duty cycle ≤2%.

© Diodes Incorporated

NEW PRODUCT




Fig. 1 Power Dissipation vs. Ambient Temperature (Note 3)




Fig. 2 Typical Collector Current vs. Collector-Emitter Voltage




Fig. 3 Typical DC Current Gain vs. Collector Current




Fig. 4 Typical Collector-Emitter Saturation Voltage vs. Collector Current




Fig 5. Typical Base-Emitter Turn-On Voltage vs. Collector Current




Fig. 6 Typical Base-Emitter Saturation Voltage vs. Collector Current

© Diodes Incorporated

NEW PRODUCT




Fig. 7 Typical Capacitance Characteristics





Fig. 8 Typical Gain-Bandwidth Product vs. Collector Current

Ordering Information (Note 5)

Device	Packaging	Shipping
DCX53-13	SOT89-3L	2500/Tape & Reel
DCX53-16-13	SOT89-3L	2500/Tape & Reel

Notes: 5. For packaging details, go to our website at http://www.diodes.com/ap02007.pdf.


Marking Information



= Manufacturer's code marking
XXX = Product type marking code Ex: P18 = DCX53
P18-16 = DCX53 -16

YWW = Date code marking
Y = Last digit of year ex: 7 = 2007
WW = Week code 01 - 52

Package Outline Dimensions




SOT89-3L			
Dim	**Min**	**Max**	**Typ**
A	1.40	1.60	1.50
B	0.45	0.55	0.50
B1	0.37	0.47	0.42
C	0.35	0.43	0.38
D	4.40	4.60	4.50
D1	1.50	1.70	1.60
E	2.40	2.60	2.50
e	—	—	1.50
H	3.95	4.25	4.10
L	0.90	1.20	1.05
All Dimensions in mm			

© Diodes Incorporated

NEW PRODUCT

Suggested Pad Layout



Unit: mm

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.

© Diodes Incorporated