P-CHANNEL ENHANCEMENT MODE MOSFET
POWERDI®

Product Summary

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D T_A = +25°C
-30V	7.5mΩ @ V_{GS} = -10V	-36A
	10mΩ @ V_{GS} = -4.5V	-31A

Description

This new generation 30V P-Channel Enhancement Mode MOSFET is designed to minimize $R_{DS(ON)}$ and yet maintain superior switching performance. This device is ideal for use in notebook battery power management and load switch.

Applications

- Notebook Battery Power Management
- DC-DC Converters
- Load Switch


Features

- Thermally Efficient Package - Cooler Running Applications
- High Conversion Efficiency
- Low $R_{DS(ON)}$ – Minimizes On State Losses
- Low Input Capacitance
- Fast Switching Speed
- <1.1mm Package Profile – Ideal for Thin Applications
- ESD HBM Protected up to 1kV
- **Lead-Free Finish; RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**
- **PPAP Available**


Mechanical Data

- Case: POWERDI®5060-8
- Case Material: Molded Plastic, "Green" Molding Compound; UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminal Connections: See Diagram Below
- Weight: 0.097 grams (Approximate)


POWERDI5060-8




Top View



Bottom View



Top View
Pin Configuration



Internal Schematic


Ordering Information (Notes 4 & 5)

Part Number	Qualification	Case	Packaging
DMP3010LPSQ-13	Automotive	POWERDI®5060-8	2,500 / Tape & Reel

Notes:
1. EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant. All applicable RoHS exemptions applied.
2. See http://www.diodes.com/quality/lead_free.html for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. Automotive products are AEC-Q101 qualified and are PPAP capable. Automotive, AEC-Q101 and standard products are electrically and thermally the same, except where specified. For more information, please refer to http://www.diodes.com/quality/product_grade_definitions/.
5. For packaging details, go to our website at http://www.diodes.com/products/packages.html.

Marking Information

POWERDI5060-8



= Manufacturer's Marking
P3010LS = Product Type Marking Code
YYWW = Date Code Marking
YY = Year (ex: 13 = 2013)
WW = Week (01 - 53)

POWERDI is a registered trademark of Diodes Incorporated.

© Diodes Incorporated

Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

Characteristic			Symbol	Value	Unit
Drain-Source Voltage			V_{DSS}	-30	V
Gate-Source Voltage			V_{GSS}	±20	V
Continuous Drain Current (Note 7) V_{GS} = 10V	Steady State	T_A = +25°C T_A = +70°C	I_D	-36 -29	A
Continuous Drain Current (Note 7) V_{GS} = 4.5V	Steady State	T_A = +25°C T_A = +70°C	I_D	-31 -25	A
Continuous Drain Current (Note 6) V_{GS} = 10V	Steady State	T_A = +25°C T_A = +70°C	I_D	-14.5 -11.5	A
Pulsed Drain Current (Notes 6 & 9)			I_{DM}	-100	A
Avalanche Current (Notes 10 & 11)			I_{AR}	-17.5	A
Repetitive Avalanche Energy (Notes 10 & 11) L = 1mH			E_{AR}	153	mJ

Thermal Characteristics

Characteristic	Symbol	Value	Unit
Power Dissipation (Note 6)	P_D	2.18	W
Thermal Resistance, Junction to Ambient @T_A = +25°C (Note 6)	$R_{\theta JA}$	55	°C/W
Power Dissipation (Note 7)	P_D	14.37	W
Thermal Resistance, Junction to Ambient @T_A = +25°C (Note 7)	$R_{\theta JA}$	8.7	°C/W
Power Dissipation (Notes 7 & 8)	P_D	58.7	W
Thermal Resistance, Junction to Case @T_C = +25°C (Notes 7 & 8)	$R_{\theta JC}$	2.13	°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150	°C

Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 11)						
Drain-Source Breakdown Voltage	BV_{DSS}	-30	—	—	V	V_{GS} = 0V, I_D = -250µA
Zero Gate Voltage Drain Current	I_{DSS}	—	—	-1	µA	V_{DS} = -30V, V_{GS} = 0V
Gate-Source Leakage	I_{GSS}	—	—	±100	nA	V_{GS} = ±20V, V_{DS} = 0V
ON CHARACTERISTICS (Note 11)						
Gate Threshold Voltage	$V_{GS(th)}$	-1.1	-1.6	-2.1	V	V_{DS} = V_{GS}, I_D = -250µA
Static Drain-Source On-Resistance	$R_{DS(ON)}$	—	5.7	7.5	mΩ	V_{GS} = -10V, I_D = -10A
		—	7.2	10		V_{GS} = -4.5V, I_D = -10A
Forward Transfer Admittance	$\|Y_{fs}\|$	—	30	—	S	V_{DS} = -15V, I_D = -10A
Diode Forward Voltage	V_{SD}	—	-0.65	-1	V	V_{GS} = 0V, I_S = -1A
DYNAMIC CHARACTERISTICS (Note 12)						
Input Capacitance	C_{iss}	—	6,234	—	pF	V_{DS} = 15V, V_{GS} = 0V, f = 1MHz
Output Capacitance	C_{oss}	—	1,500	—	pF	
Reverse Transfer Capacitance	C_{rss}	—	774	—	pF	
Gate Resistance	R_g	—	1.28	—	Ω	V_{DS} = 0V, V_{GS} = 0V, f = 1MHz
Total Gate Charge (V_{GS} = -10V)	Q_g	—	126.2	—	nC	V_{DS} = -15V, I_D = -10A
Total Gate Charge (V_{GS} = -4.5V)	Q_g	—	59.2	—	nC	V_{DS} = -15V, V_{GS} = -4.5V, I_D = -10A
Gate-Source Charge	Q_{gs}	—	16.1	—	nC	
Gate-Drain Charge	Q_{gd}	—	15.7	—	nC	
Turn-On Delay Time	$t_{D(on)}$	—	11.4	—	ns	V_{DS} = -15V, V_{GEN} = -10V, R_G = 6Ω, I_D = -1A
Turn-On Rise Time	t_r	—	9.4	—	ns	
Turn-Off Delay Time	$t_{D(off)}$	—	260.7	—	ns	
Turn-Off Fall Time	t_f	—	99.3	—	ns	

Notes:
6. Device mounted on FR-4 PCB with 1-inch square 2 oz. Copper, single sided.
7. Device mounted on FR-4 PCB with infinite heatsink.
8. $R_{\theta JC}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design.
9. Repetitive rating, pulse width limited by junction temperature, 10µs pulse, duty cycle = 1%.
10. I_{AR} and E_{AR} rating are based on low frequency and duty cycles to keep T_J = +25°C.
11. Short duration pulse test used to minimize self-heating effect.
12. Guaranteed by design. Not subject to production testing.

© Diodes Incorporated




Fig. 1 Typical Output Characteristic




Fig. 2 Typical Transfer Characteristic




Fig. 3 Typical On-Resistance
vs. Drain Current and Gate Voltage




Fig. 4 Typical On-Resistance
vs. Drain Current and Temperature




Fig. 5 On-Resistance Variation with Temperature




Fig. 6 On-Resistance Variation with Temperature

POWERDI is a registered trademark of Diodes Incorporated.

© Diodes Incorporated




Fig. 7 Gate Threshold Variation vs. Ambient Temperature




Fig. 8 Diode Forward Voltage vs. Current




Fig. 9 Typical Total Capacitance




Fig. 10 Typical Leakage Current vs. Drain-Source Voltage




Fig. 11 Gate-Source Voltage vs. Total Gate Charge




Fig. 12 SOA, Safe Operation Area

© Diodes Incorporated





Fig. 13 Transient Thermal Response

Package Outline Dimensions

Please see AP02002 at http://www.diodes.com/datasheets/ap02002.pdf for the latest version.

POWERDI®5060-8




POWERDI®5060-8			
Dim	**Min**	**Max**	**Typ**
A	0.90	1.10	1.00
A1	0.00	0.05	-
b	0.33	0.51	0.41
b2	0.200	0.350	0.273
b3	0.40	0.80	0.60
c	0.230	0.330	0.277
D	5.15 BSC		
D1	4.70	5.10	4.90
D2	3.70	4.10	3.90
D3	3.90	4.30	4.10
E	6.15 BSC		
E1	5.60	6.00	5.80
E2	3.28	3.68	3.48
E3	3.99	4.39	4.19
e	1.27 BSC		
G	0.51	0.71	0.61
K	0.51	-	-
L	0.51	0.71	0.61
L1	0.100	0.200	0.175
M	3.235	4.035	3.635
M1	1.00	1.40	1.21
θ	10°	12°	11°
θ1	6°	8°	7°
All Dimensions in mm			

© Diodes Incorporated

Suggested Pad Layout

Please see AP02001 at http://www.diodes.com/datasheets/ap02001.pdf for the latest version.



Dimensions	Value (in mm)
C	1.270
G	0.660
G1	0.820
X	0.610
X1	4.100
X2	0.755
X3	4.420
X4	5.610
Y	1.270
Y1	0.600
Y2	1.020
Y3	0.295
Y4	1.825
Y5	3.810
Y6	0.180
Y7	6.610

POWERDI is a registered trademark of Diodes Incorporated.

© Diodes Incorporated

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2015, Diodes Incorporated

www.diodes.com